

# Directed Virtual Path Layouts in ATM networks\*

Jean-Claude Bermond \*\*, Nausica Marlin \*\*, David Peleg \*\*\*, and Stéphane Perennes \*\*

**Abstract.** Motivated by Asynchronous Transfer Mode (ATM) in telecommunication networks, we investigate the problem of designing a directed virtual topology on a directed physical topology, which consists in finding a set of *directed virtual paths (VPs)* satisfying some constraints in terms of *load* (the number of VPs sharing a physical link) and *hop count* (the number of VPs used to establish a connection). For both general and particular networks, such as paths, cycles, meshes, tori and trees, we derive tight bounds on the *virtual diameter* (the maximum hop count for a connection) as a function of the *network capacity* (the maximum load of a physical link).

**Keywords :** ATM, Virtual Path Layout, Diameter, Embedding, Load

## 1 Introduction

The advent of fiber optic media has changed the classical views on the role and structure of digital communication networks. Specifically, the sharp distinction between telephone networks, cable television networks, and computer networks has been replaced by a unified approach. The most prevalent solution for this new network challenge is *Asynchronous Transfer Mode* (ATM for short), which is thoroughly described in the literature [19, 16]. The transfer of data in ATM is based on packets of fixed length, termed *cells*. Each cell is routed independently, based on two routing fields at the cell header, called *virtual channel identifier (VCI)* and *virtual path identifier (VPI)*. This method effectively creates two types of predetermined simple routes in the network, namely, routes which are based on VPIs (called *virtual paths* or VPs) and routes based on VCIs and VPIs (called *virtual channels* or VCs). VCs are used for connecting network users (e.g., a telephone call); VPs are used for simplifying network management - routing of VCs in particular. Thus the route of a VC may be viewed as a concatenation of complete VPs.

A major problem in this framework is the one of defining the set of VPs in such a way that some good properties are achieved.

1. A capacity (or bandwidth) is assigned to each VP. The sum of the capacities of the VPs that share a physical link constitutes the *load* of this link. Naturally, this load must not exceed the link's capacity, namely, the amount of data it can carry. The sum of the capacities of all the physical links is a major component in the cost of the network, and should be kept as low as possible.
2. The maximum number of VPs in a virtual channel, termed *hop count* in the literature, should also be kept as low as possible so as to guarantee low set up times for the virtual channels and high data transfer rates.

---

\* This work has been supported by the French-Israeli cooperation "AFIRST"

\*\* I3S Université de Nice, SLOOP joint project CNRS-UNSA-INRIA, 2004 route des Lucioles, BP93, F-06902 Sophia-Antipolis, France. ({Jean-Claude.Bermond, Nausica.Marlin, Stephane.Perennes}@sophia.inria.fr)

\*\*\* Department of Applied Mathematics and Computer Science, The Weizmann Institute, Rehovot 76100, Israel. (peleg@wisdom.weizmann.ac.il)

In its most general formulation, the *Virtual Path Layout (VPL)* problem is an optimization problem in which, given a certain communication demand between pairs of nodes and constraints on the maximum load and hop count, it is first required to design a system of virtual paths satisfying the constraints and then minimizing some given function of the load and hop count.

We employ a restricted model similar to the one presented by Cidon, Gerstel and Zaks in [13]. In particular, we assume that all VPs have equal capacities, normalized to 1. Hence the load of a physical link is simply the number of VPs that share this link.

Although links based on optical fibers and cables are directed, traditional research uses an undirected model. Indeed, this model imposes the requirement that if there exists a VP from  $u$  to  $v$  then there exists also a VP from  $v$  to  $u$ . In fact, that is the way ATM networks are implemented at the present time. However, the two VPs (the one from  $u$  to  $v$  and the one in the other direction) do not need to have the same capacity. Indeed, in many applications the flows on the VPs are not equal. For example, in a video application where  $u$  is a server and  $v$  a consumer there is a VP from  $u$  to  $v$  using a large capacity (transmission of video data) and a VP from  $v$  to  $u$  used only for control or acknowledgments with a very small capacity which can be considered as negligible. Therefore, it seems more reasonable to use a directed model like the one introduced by Chanas and Goldschmidt in [6]. This would allow us to model the situation described above by a single VP of capacity 1 in the main direction.

We focus on the *all-to-all problem* (all pairs of nodes are equally likely to communicate). Thus, the resulting maximum hop count can be viewed as the *diameter* of the graph induced by the VPs.

More formally, given a communication network, the VPs form a virtual directed graph (*digraph*) on the top of the physical one, with the same set of vertices but with a different set of arcs. (Specifically, a VP from  $u$  to  $v$  is represented by an arc from  $u$  to  $v$  in the virtual digraph.) This virtual digraph provides a *Directed Virtual Path Layout (DVPL)* for the physical graph. Each VC can be viewed as a simple dipath in the virtual digraph. Therefore, a central problem is to find a tradeoff between the maximum load and the virtual diameter. In this article, we consider the following problem:

*Given a capacity on each physical arc, minimize the diameter of an admissible virtual graph (a virtual digraph that doesn't load an arc more than its capacity)*

*Related Work* The problem has been considered in the undirected case, for example, in [13, 12, 22, 11, 17, 9]. Observe that the undirected and symmetric directed models are tightly coupled. Specifically, any solution of the undirected case with load  $c$  can be transformed into a solution for directed case with load  $c$ . Conversely, any solution of the directed case with load  $c$  can be transformed into a solution for the undirected case with load  $2c$ .

However, in general both of these transformations do not yield optimal results, neither for lower or upper bounds. This is mainly because optimal solutions for the directed case are far from being symmetric. Hence specialized methods are required for obtaining optimal solutions in either of the two models.

As an example, consider the case  $c = 1$ . In the undirected case, the only feasible solution is to take the original edges as virtual paths of length 1, and the resulting virtual diameter is the diameter of the original graph. For example, for an undirected cycle with  $c = 1$ , this results in a virtual diameter of  $n/2$ . So merely applying the above transformation will yield an upper bound of  $n/2$  for the directed case as well. In contrast, using a direct derivation we obtain a tight solution for this case which has a considerably lower diameter bound, namely,  $2n^{1/2}$ . As another

example, for cycles, the results of [1] or [8] combined with the above transformation yield upper bounds of order  $n^{1/c}$ , whereas here we obtain a (tight) bound of  $n^{1/2c}$ .

The problem of minimizing the maximum load over all VPL with bounded hop-count is studied in [10, 2], and minimizing also the average load is considered in [12]. The one-to-many problem is handled in [10, 12], where the focus is on minimizing the eccentricity of the virtual graph from a special point called the root (this problem is the *rooted virtual path layout problem*) rather than minimizing the diameter of the virtual graph. A duality in the chain network between the problem of minimizing the hop-count knowing the maximum load, and the one of minimizing the load, knowing the maximum hop-count, is established in [10]. The reader can find an excellent survey of the results in the undirected model in [23].

The techniques involved in our constructions bear a certain resemblance to various embedding techniques used previously in the context of parallel computing, in order to implement a useful virtual architecture on a given practical machine topology (cf. [20, 15]). The parameters of interest in such embeddings are the number of virtual processors mapped onto any physical processor, the load on the physical links, and the dilation of the embedding, namely, the maximum length of the physical path corresponding to a given virtual link. The relevant concerns in our context are somewhat different, as dilation is of no consequence, and on the other hand, we have the freedom of designing the virtual topology as desired, in order to optimize its diameter.

*Our Results* The following table summarizes our results, giving lower and upper bounds on the virtual diameter (the minimum diameter of an admissible virtual digraph) as a function of the number of vertices  $n$  in the physical graph, its diameter  $D_G$ , its maximum in- and out-degree  $d$ , and the capacity  $c$  considered as a constant. The results mentioned for the path in the special case  $c = 1$  are due to [4, 5].

Graph $G$	Capacity	Lower Bound	Upper Bound
General Graph	$c = o(n)$	$\frac{\log n}{\log(cd)} - 1$	$D_G$ $\mathcal{O}(c \cdot n^{\frac{1}{2c-1}})$ $\mathcal{O}(D_G^{1/(2c-1)} \cdot \log n)$
Path $P_n$	$c = 1$	$\frac{n}{2} + \log n - \mathcal{O}(1)$	$\frac{n}{2} + \log n$
	$c = o(n)$	$n^{\frac{1}{2c-1}}/2$	$\mathcal{O}(c \cdot n^{\frac{1}{2c-1}})$
Cycle $C_n$	$c = 1$	$2\sqrt{2n} + \mathcal{O}(1)$	$2\sqrt{2n} + 1$
	$c = o(n)$	$n^{\frac{1}{2c}}/2$	$4c \left(\frac{n}{2}\right)^{\frac{1}{2c}} + 1$
Torus $TM(a, b)$ , $a \leq b$	$c = o(n)$	$\Omega((a \cdot b)^{1/2ac})$	$\mathcal{O}(a \cdot b^{1/2ac})$
Mesh $M(a, b)$ , $\log b \leq a \leq b$	$c = o(n)$	$\Omega(\log n)$	$\mathcal{O}(\log n)$
Arbitrary Tree $T$	$c = o(n)$	$D_T^{1/(2c-1)}/2$	$10c \cdot n^{1/(2c-1)}$ $\mathcal{O}(c \cdot D_T^{1/(2c-1)} \cdot \log n)$
Complete $k$ -ary Tree $T$ $h = \text{depth}(T)$	$c = 2, k = 2$	$h$ ( $h$ even) $h - 1$ ( $h$ odd)	$h + 1$
	$c = o(n)$	$2 \left\lfloor \frac{h-1}{\lfloor \log_k c \rfloor + 1} \right\rfloor + 1$	$2 \left\lfloor \frac{h}{\lfloor \log_k c \rfloor + 1} \right\rfloor + 2$

## 2 The model


A physical network is represented by a *capacitated digraph*  $G = (V, E, c)$ , that is a directed graph with vertex set  $V$  and arc set  $E$ , together with a positive integral capacity function  $c$  on the

set of arcs. We always denote by  $n$  the number of vertices and in this paper we mostly consider constant capacity functions, i.e.  $\forall e \in E, c(e) = c_0$ .

The network formed by a set of VPs is represented by a digraph  $H = (V, E')$  together with a layout  $P$  assigning to each arc  $e' = (x, y) \in E'$  a simple directed path (dipath)  $P(e')$  connecting  $x$  to  $y$  in  $G$ . In our terminology, the pair  $(H, P)$  is a *virtual digraph on  $G$* , an arc of  $H$  is a *virtual arc*, and the dipath  $P(e')$  in  $G$  associated with a virtual arc  $e'$  is a *virtual dipath (VP)*.

The *load* of an arc  $e$  of  $G$  is the number of virtual dipaths containing the arc  $e$ , that is,  $l(e) = \#\{e' \in E' \mid e \in P(e')\}$ . A virtual digraph  $(H, P)$  satisfying the requirement  $\forall e \in E, l(e) \leq c(e)$  is referred to as a  *$c$ -admissible Directed Virtual Paths Layout* of  $G$ , shortly denoted  *$c$ -DVPL* of  $G$ . The aim is to design  $c$ -DVPL of  $G$  with minimum hop-count, i.e, to find a virtual digraph with minimum diameter.

For any digraph  $F$ ,  $d_F(x, y)$  denotes the distance from  $x$  to  $y$  in  $F$ , and  $D_F$  denotes diameter of  $F$ . The *virtual diameter*,  $\tilde{D}(G, c)$ , of the digraph  $G$  with respect to the capacity  $c$ , is the minimum of  $D_H$  over all the  $c$ -DVPL  $H$  of  $G$ .



**Fig. 1.** Example of VPL: the cycle, capacity 1

In Fig. 1,  $G$  consists of the symmetric directed cycle  $C_n$ . The virtual graph  $H$  consists of arcs  $(i, i + 1)$  in the clockwise direction and arcs  $(ip, (i - 1)p)$  in the opposite direction (assuming that  $p$  divides  $n$ ).  $H$  is in fact a circuit-bracelet (see details in section 3.2). The load of every arc of  $C_n$  is 1. Choosing  $p = \sqrt{\frac{n}{2}}$  gives good DVPL with diameter at most  $2\sqrt{2n} + 1$ .

### 3 The Cycle $C_n$

In this section the physical digraph  $G$  is  $C_n$ , the symmetric directed cycle of length  $n$ . We choose arbitrarily a direction on  $C_n$ . For concreteness, consider as positive, or forward (resp., negative or backward) the clockwise (resp., counterclockwise) direction. We assume that  $\forall e \in E, c(e) = c^+$  if  $e$  is a forward arc and  $c(e) = c^-$  if  $e$  is a backward arc, for some constant nonnegative integers  $c^+, c^-$ .

It turns out that our bounds can be expressed as functions of  $\sigma = c^+ + c^-$ . It is then convenient to define  $ub_C(n, \sigma)$  (resp.,  $lb_C(n, \sigma)$ ) as an upper bound (resp., lower bound) on  $\tilde{D}(C_n, c)$  valid if  $c$  satisfies  $c^+ + c^- = \sigma$ . By the definition,  $lb_C(n, \sigma) \leq \tilde{D}(C_n, c) \leq ub_C(n, \sigma)$ .

### 3.1 The general Case


**Proposition 1.**

$$\frac{n^{\frac{1}{\sigma}}}{2} \leq \tilde{D}(C_n, c) \leq 2\sigma \left\lceil \left(\frac{n}{2}\right)^{\frac{1}{\sigma}} \right\rceil - 2\sigma + 1 < 2\sigma \left(\frac{n}{2}\right)^{\frac{1}{\sigma}} + 1$$

Upper and lower bounds are both proved by induction from the next two lemmas.

**Lemma 2.**  $lb_C(n, \sigma) \geq \min_{p \in N^+} \{\max(\frac{n}{2p}, lb_C(p, \sigma - 1))\}$ .

*Proof.* Let  $H$  be an optimal  $c$ -DVPL of  $C_n$  and let  $[x_1, y_1]^+$  be the dipath consisting of all the vertices of  $C_n$  between  $x_1$  and  $y_1$  in the positive direction. Let  $d^+(x_1, y_1)$  denote the number of arcs in  $[x_1, y_1]^+$ . We say that  $[x_1, y_1]^+$  is covered by  $H$  if (the VP corresponding to) some virtual arc  $e'$  contains  $[x_1, y_1]^+$ .



**Fig. 2.** Collapsing a cycle

First we prove that if  $[x_1, y_1]^+$  is covered by  $e'$  then  $D_H \geq lb_C(d^+(x_1, y_1), \sigma - 1)$ . For this, we shorten the cycle by identifying all the nodes in  $[y_1, x_1]^+$  with  $x_1$ , obtaining a cycle  $C'$  of length  $d^+(x_1, y_1)$ . Virtual arcs are just transformed according to this graph quotient (see Fig. 2). As example a virtual arc from  $x \in [x_1, y_1]^+$  to  $y \in [x_1, y_1]^+$  is left unchanged; and a virtual arc from  $x \in [x_1, y_1]^+$  to  $y \in [y_1, x_1]^+$  is transformed into the arc  $(x, x_1)$ . Note that the virtual arc containing the positive arcs of  $[x_1, y_1]^+$  is transformed into a loop. We also remove loops or multiple virtual dipaths in order to get a simple DVPL on  $C'$ .

This transformation does not increase the load of any arc; furthermore the virtual arc  $e'$  that contained  $[x_1, y_1]^+$  disappears, so the congestion of any positive arc decreases. Moreover, our transformation does not increase the virtual diameter.

Consequently, we obtain a  $c'$ -DVPL of  $C'$  (a cycle of length  $d^+(x_1, y_1)$ ) with  $c'^+ + c'^- = \sigma - 1$ , and diameter at most  $D_H$ . It follows that

$$D_H \geq lb_C(d^+(x_1, y_1), \sigma - 1) \tag{1}$$

Now we argue that there exist vertices  $u$  and  $v$  with large  $d^+(u, v)$  such that  $[u, v]^+$  is covered. Let  $\mathcal{P}$  be the shortest dipath in  $H$  from 0 to  $n/2$ , and assume w.l.o.g. that  $\mathcal{P}$  contains the arcs of

$[0, n/2]^+$ . Let  $\mathcal{S}$  denote the set of vertices of  $\mathcal{P}$  between  $x$  and  $y$  in the positive direction. Then  $|\mathcal{S}| \leq D_H + 1$ , and therefore there exist vertices  $u$  and  $v$  such that  $[u, v]^+$  is covered and with

$$d^+(u, v) \geq \frac{n}{2D_H}. \quad (2)$$

Let  $p = \max\{d^+(u, v) \mid [u, v]^+ \text{ is covered}\}$ . From (2) we have  $D_H \geq \frac{n}{2p}$ , and from (1) it follows that  $D_H \geq lb_C(p, \sigma - 1)$ .  $\blacksquare$

**Lemma 3.**  $ub_C(n, \sigma) \leq \min_{p \in N^+} \{2(p - 1) + ub_C(\lceil \frac{n}{p} \rceil, \sigma - 1)\}$ .

*Proof.* Let us construct a  $c$ -DVPL on  $C_n$ . Without loss of generality suppose that  $c^+ \geq c^-$ , so  $c^+ \neq 0$ . Let  $p \in N^+$ , we proceed as follows.

- Use  $n$  virtual arcs  $(i, i + 1)_{i \in [0..n-1]}$  of dilation 1 in the positive direction.
- Let  $S$  be the set of vertices  $\{0, -p, -2p, \dots, -(\lceil \frac{n}{p} \rceil - 1)p\}$ , and note that vertices of  $S$  form a cycle  $C_{\lceil \frac{n}{p} \rceil}$ .
- Use an optimal  $c'$ -DVPL for  $C_{\lceil \frac{n}{p} \rceil}$  with  $c'^+ = c^+ - 1$ , and  $c'^- = c^-$ , that is  $c'^+ + c'^- = \sigma - 1$ .

By construction, the diameter  $\Delta(S)$  of the set  $S$  (i.e., the maximal distance of two vertices in  $S$ ) is at most  $ub_C(\lceil \frac{n}{p} \rceil, \sigma - 1)$ ; moreover, for any vertex  $x$ , we have  $d(S, x) \leq p - 1$  and  $d(x, S) \leq p - 1$ . Hence  $d(x, y) \leq d(S, x) + d(y, S) + \Delta(S) \leq 2(p - 1) + ub_C(\lceil \frac{n}{p} \rceil, \sigma - 1)$ .  $\blacksquare$

*Proof (proposition 1).* First we consider the lower bound. We prove by induction on  $\sigma$  that  $lb_C(n, \sigma) \geq \frac{1}{2}n^{\frac{1}{\sigma}}$ . For the initial case we have  $lb_C(n, 1) = n - 1 \geq \frac{n}{2}$ . Now to go from  $\sigma - 1$  to  $\sigma$  we use lemma 2 which states that  $lb_C(n, \sigma) \geq \min_{p \in N^+} \max(\frac{n}{2p}, \frac{1}{2}p^{\frac{1}{\sigma-1}})$ . An elementary analysis shows that  $\max(\frac{n}{2p}, \frac{1}{2}p^{\frac{1}{\sigma-1}}) \geq \frac{1}{2}n^{\frac{1}{\sigma}}$  attained for  $p = n^{1-1/\sigma}$ . Hence  $lb_C(n, \sigma) \geq \frac{1}{2}n^{\frac{1}{\sigma}}$  and the proof is completed.

Now, we prove the upper bound. First we show by induction on  $\sigma$  that for  $n = 2a^\sigma, a \in N$ ,  $ub_C(n, \sigma) \leq 2\sigma \left(\frac{n}{2}\right)^{1/\sigma} - 2\sigma + 1 = 2\sigma a - 2\sigma + 1$ . For  $\sigma = 1$ ,  $ub_C(n, 1) \leq n - 1$  is true. For the inductive step from  $\sigma - 1$  to  $\sigma$ , we apply lemma 3 with  $p = a$ , getting  $ub_C(n, \sigma) \leq 2(a - 1) + ub_C(2a^{\sigma-1}, \sigma - 1)$ . By induction,  $ub_C(2a^{\sigma-1}, \sigma - 1) \leq 2(\sigma - 1)a - 2(\sigma - 1) + 1$ ; so we get the expected result.

For other values of  $n$ , the claim is proved as follows. Let  $a = \lceil \left(\frac{n}{2}\right)^{1/\sigma} \rceil$ .  $a$  is such that  $n \leq 2a^\sigma$ . As  $ub_C$  is an increasing function on  $n$ , we obtain  $ub_C(n, \sigma) \leq 2\sigma a - 2\sigma + 1 = 2\sigma \left[\left(\frac{n}{2}\right)^{1/\sigma}\right] - 2\sigma + 1$ . As  $a < \left(\frac{n}{2}\right)^{\frac{1}{\sigma}} + 1$ , this implies  $ub_C(n, \sigma) < 2\sigma \left(\frac{n}{2}\right)^{\frac{1}{\sigma}} + 1$ .  $\blacksquare$

In particular we get

**Corollary 4.** *If  $c^+ = c^- = c$  then*

$$\frac{n^{\frac{1}{2c}}}{2} \leq \tilde{D}(C_n, c) < 4c \left(\frac{n}{2}\right)^{\frac{1}{2c}} + 1.$$

### 3.2 The case $c = 1$

In the case of capacity 1 we have been able to determine  $\tilde{D}(C_n, 1)$  up to an additive constant.

**Proposition 5.**

$$2\sqrt{2n} - \mathcal{O}(1) \leq \tilde{D}(C_n, 1) \leq 4 \left\lceil \sqrt{\frac{n}{2}} \right\rceil - 3 < 2\sqrt{2n} + 1$$

The upper bound is the one given for the general case. We conjecture that this bound is tight. It would be desirable to obtain a simpler argument that could extend to higher capacities.


Note also that using lemma 2 from the starting condition  $lb_C(n, 2) \geq 2\sqrt{2n} + \Theta(1)$  would slightly improve the lower bound on  $lb_C(n, \sigma)$ . The lower bound proof requires some care so we first give some definitions.

Let  $H$  be an optimal virtual digraph on  $G$  with respect to the capacity 1. The following definitions are given for the positive direction, but similar notions apply for the negative direction as well.

**Definition 6.** – The *forward successor* of a vertex  $x$  is denoted  $x^+$ ,  
 –  $[x, y]^+$  denotes the dipath from  $x$  to  $y$  in  $C_n$  in the positive direction,  
 – a path  $Q = (e'_1, \dots, e'_q)$  from  $x$  to  $y$  in  $H$  is said to be *of type +* if  $[x, y]^+ \subset W(Q)$ . Where  $W(Q)$  is the route in  $G$  associated to the dipath  $Q$  in  $H$ .

**Definition 7.** A *circuit-bracelet* of size  $n$  is a digraph  $A$  of order  $n$  constructed as follows (see Fig. 3):

- The digraph is made of a set of cycles  $C_i, i \in I$  directed in a clockwise manner.
- For any  $i$ ,  $C_i$  and  $C_{i+1 \bmod I}$  share a unique vertex  $v_{i+1 \bmod I}$ .
- The length of the dipath in  $C_i$  from  $v_{i-1}$  to  $v_i$  is denoted  $p_i$  and is called the *positive length* of  $C_i$ ; similarly, the length of the dipath in  $C_i$  from  $v_i$  to  $v_{i-1}$  is denoted  $n_i$  and is called the *negative length* of  $C_i$ .
- We denote the successor of  $v_i$  in  $C_i$  by  $w_i$ , and the ancestor of  $v_{i+1}$  in  $C_i$  by  $z_i$ .



**Fig. 3.** A circuit-bracelet

Let  $f(n)$  be the minimal value of  $D_A$ , where  $A$  is any circuit-bracelet of size  $n$ . In the remaining of the section indices are taken modulo  $I$ .

**Lemma 8.**  $f(n) = \tilde{D}(C_n, 1)$

*Proof.* Notice that if an arc  $e$  of  $G$  is not used by a virtual dipath  $P(e')$  with  $e' \in E'$ , we add a virtual arc  $e'$  such that  $P(e') = (e)$ . This transformation can only decrease the diameter of  $H$ , which is of no consequence since we only seek for a lower bound on the virtual diameter. Using this manipulation, we know that  $\forall e \in E, \exists e' \in E'$  s.t.  $e \in P(e')$ . This implies

$$\sum_{e' \text{ arc of type } -} w(e') = \sum_{e' \text{ arc of type } +} w(e') = n . \quad (3)$$

Where  $w(e')$  is the *dilation* of a VP  $e'$ , i.e. the length of  $P(e')$ .

Now, we show that : *If  $e' = (x, y) \in E'$  is an arc of type + of dilation  $w(e') \geq 3$  then all the arcs of type - between  $y^-$  and  $x^+$  are of dilation 1.*

Since the capacity of any arc of  $G$  is 1, and there is already a virtual arc of type + between  $x$  and  $y$ , there is no virtual arc of type + ending at any vertex between  $x^+$  and  $y^-$ . Since  $H = (V, E')$  is strongly connected, there is at least one arc ending at each one of these vertices. These arcs are of type -. For the same reasons of capacity and connectivity, these virtual arcs are of dilation 1.

Due to this property it is easy to see that there exists a digraph isomorphism between  $H$  and a circuit-bracelet of size  $n$  (see Fig. 3). ■

**Lemma 9.**  $f(n) = \Theta(\sqrt{n})$  and the total number of circuits in an optimal circuit-bracelet is also  $\Theta(\sqrt{n})$ .

*Proof.* By the construction of lemma 3, there exists a regular circuit-bracelet with diameter at most  $2\sqrt{2n} + 1$ , so  $f(n) = \mathcal{O}(\sqrt{n})$ . Note that the size of any circuit in an optimal circuit-bracelet is at most  $f(n) + 2 = \mathcal{O}(\sqrt{n})$ , otherwise the distance from  $w_i$  to the second neighbor of  $v_i$  on the bigger cycle  $C_i$  is more than  $f(n)$ . Hence there are at least  $\Omega(\sqrt{n})$  circuits. Moreover the total number of circuits is less than  $2f(n) = \mathcal{O}(\sqrt{n})$ , otherwise there exist two vertices at distance more than  $f(n)$ . Thus  $f(n) = \Omega(\sqrt{n})$  and the lemma follows. ■

We first prove proposition 5 for the special case of a *regular circuit-bracelet*, namely, a circuit-bracelet satisfying  $n_i = 1$  for every  $i$ . The circuits of a regular circuit-bracelet all consist of a single arc of type - and  $p_i$  arcs of type +. Remark that  $p_i$  is then the length of  $C_i$ . Let  $g(n)$  denote the minimal value of  $D_A$  where  $A$  is any regular circuit-bracelet of size  $n$ .

**Lemma 10.**  $g(n) = 2\sqrt{2n} + \mathcal{O}(1)$ .

*Proof.* We prove here that  $g(n) \geq 2\sqrt{2n} + \mathcal{O}(1)$ . We assume that  $n$  is sufficiently large. Let  $p$  be an integer and  $D$  the diameter of the considered circuit-bracelet. Call a circuit *big* if its size is greater than  $\frac{D}{p}$ , *small* otherwise. Recall that the size of any circuit is less than  $D + 2$ . Let  $b$  denote the number of big circuits and  $s$  denote the number of small circuits. We have

$$n \leq s \frac{D}{p} + b(D + 2) \quad \text{and} \quad s + b \leq 2D. \quad (4)$$



Suppose that big circuits are ordered cyclically according to the circuit-bracelet structure:  $C_{i_0}, C_{i_1}, \dots, C_{i_{b-1}}$  as shown on Fig. 3. Let  $k \in \{0, 1, \dots, b-1\}$  and consider dipaths from  $w_{i_k}$  to  $z_{i_{k+p}}$ . In the positive direction the cost is exactly  $d_k = \sum_{j \in [k, k+p]} p_{i_j} - 2$ ; as these circuits are big,  $p_{i_j} \geq \frac{D}{p}$  and hence  $d_k \geq \frac{p+1}{p}D - 2 > D$  if  $p < \frac{D}{2}$ . So we must use the negative direction. The length is then  $d'_k = p_{i_k} + p_{i_{k+p}} + b + s - (i_{k+p} - i_k) - 3 \leq D$ . Summing on all the  $k$ 's we get:

$$\sum_{k=0}^{k=b-1} d'_k = 2(n - \delta) + b(b + s) - p(b + s) - 3b \leq bD.$$

Where  $\delta$  denote the number of vertices in the small circuits.

So  $\frac{2(n-\delta)}{b} + b + s - p - p\frac{s}{b} - 3 \leq D$ . Note now that  $\delta \leq s\frac{D}{p}$ , so

$$\frac{2n}{b} + b + s\left(1 - \frac{2D}{bp} - \frac{p}{b}\right) - p \leq D \quad (5)$$

If the coefficient of  $s$  in inequality (5) is positive then the left factor of that inequality is greater than  $\frac{2n}{b} + b - p - 3$  which is greater than  $2\sqrt{2n} - p - 3$ . In turn, the coefficient of  $s$  is positive if  $b \geq \frac{2D}{p} + p$ .

(4) implies  $n \leq 2\frac{D^2}{p} + 2bD$  and so  $b \geq \frac{n}{2D} - \frac{D}{p}$ . Using the fact that  $D \leq 2\sqrt{2n}$ , we obtain  $b \geq \sqrt{2n} \left(\frac{p-16}{8p}\right)$ . But

$$\sqrt{2n} \left(\frac{p-16}{8p}\right) \geq \frac{2D}{p} + p$$

if  $\frac{p}{8} - 4 - \frac{p^2}{\sqrt{2n}} \geq 0$ , and the latter inequality is true if  $p \geq 33$  and  $n$  is large enough. It follows that  $g(n) \geq 2\sqrt{2n} - 36$ . ■

**Proposition 11.**

$$\tilde{D}(C_n, 1) = f(n) = 2\sqrt{2n} + \Theta(1)$$

*Proof.* Recall that  $D = \Theta(\sqrt{n})$ . Consider a circuit-bracelet, and recall that  $n_i + p_i \leq D + 1$ , so that we can find an integer  $k$  such that  $\sum_{i \in [1, k]} (n_i + p_i) \geq 2D + 1$  with  $\sum_{i \in [1, k]} (n_i + p_i) = \Theta(\sqrt{n})$ . Consider the shortest dipath from  $v_1$  to  $v_{k+1}$  and suppose that it uses the positive direction; so  $\sum_{i \in [1, k]} p_i \leq D$ . It follows that  $\sum_{i \in [1, k]} n_i > D$ . So, the dipath from  $v_k$  to  $v_1$  cannot use the negative direction, and must use the positive one. It follows that  $\sum_{i \notin [1, k]} p_i \leq D$ . Globally,  $\sum p_i \leq 2D = \Theta(\sqrt{n})$ . If we remove this  $\Theta(\sqrt{n})$  vertices we obtain a regular circuit-bracelet with lesser diameter. It follows that  $f(n) \geq g(n - \Theta(\sqrt{n})) = 2\sqrt{2n}\sqrt{1 + \Theta(\frac{1}{\sqrt{n}})} = 2\sqrt{2n} + \Theta(1)$ . A new constant appears here in the bound. ■

## 4 The Path $P_n$

In this section the physical digraph  $G$  is the  $n$ -vertex symmetric directed path  $P_n$ . Our bounds are valid for any capacity function  $c$  such that positive (resp., negative) arcs have capacity  $c^+$  (resp.,  $c^-$ ) and the additional requirement  $c^+ \geq 1, c^- \geq 1$ . Let  $\sigma = c^+ + c^-$ ,

**Proposition 12.**

$$\frac{n^{\frac{1}{\sigma-1}}}{2} \leq \tilde{D}(P_n, c) \leq 2(\sigma - 1) \left[ \left( \frac{n-1}{2} \right)^{\frac{1}{\sigma-1}} \right] - 2\sigma + 4$$

*Proof.* Let us first prove the lower bound. Let  $H$  be a  $c$ -DVPL of  $P_n$ . We say that a sub-path  $[x, y]$  is *covered* by  $H$  if the dipaths from  $x$  to  $y$  and from  $y$  to  $x$  are both contained in (the VP corresponding to) some virtual arc.

First we show that if  $[x, y]$  is covered then  $D_H \geq lb_C(d(x, y), \sigma - 2)$ . Indeed if  $[x, y]$  is covered we identify  $x$  and  $y$  and collapse the path into a cycle of length  $d(x, y)$ , we then ignore the virtual paths covering  $[x, y]$  (see the proof of lemma 2 for details). So doing we obtain a  $c'$ -DVPL for  $C_{d(x, y)}$  with  $c'^+ + c'^- = \sigma - 2$ .

Now, consider two shortest dipaths in  $H$ , one from 0 to  $n - 1$  and the second from  $n - 1$  to 0. There are at most  $2D_H$  intermediate points (including 0 and  $n - 1$ ) on these two dipaths. Hence we can find two consecutive intermediate vertices  $x$  and  $y$ , with  $[x, y]$  covered, such that  $d(x, y) \geq \frac{n}{2D_H}$ . Thus, if  $m = \max\{d(x, y) \mid [x, y] \text{ is covered}\}$ , we have  $D_H \geq \frac{n}{2m}$ . But due to the covering property  $D_H \geq lb_C(m, \sigma - 2)$ . Hence  $lb_P(m, \sigma) \geq \max(\frac{n}{2m}, lb_C(m, \sigma - 2))$ . Using the lower bound on  $lb_C(m, \sigma)$  given in proposition 1, and maximizing in  $m$ , completes the lower bound proof.

To prove the upper bound, we construct a VPL based on the best VPL we know on the cycle  $C_{n-1}$  with  $c'^+ = c^+$  and  $c'^- = c^- - 1$ . In this VPL, no VP passes over vertex 0. So, we cut the cycle at vertex 0 and consider it as the path  $P_n$ . On the negative direction, we add a VP of dilation  $n$  from  $n - 1$  to 0 (See Fig. 4). The added VP is used at most once in a path on  $H$ . The bound is the one for the cycle  $C_{n-1}$ , sum of capacities  $\sigma - 1$  plus 1. ■



Fig. 4.  $P_n, c = 2$

## 5 The Complete Symmetric $k$ -ary Tree $T(k, h)$

In this section the physical digraph  $G$  is  $T(k, h)$ , the directed symmetric complete  $k$ -ary tree of depth  $h$  rooted at  $r_0$ . Recall that in a complete  $k$ -ary tree, each nonleaf vertex has exactly  $k$  children. The *depth* of a vertex is its distance from the root, and the depth of the tree is the maximum depth of any of its vertices. The root  $r_0$  is the only vertex of in and out-degree  $k$ .  $T(k, h)$  has  $\frac{k^{h+1}-1}{k-1}$  vertices and diameter  $2h$ .


The *ancestors* of a vertex  $x$  are all vertices except  $x$  on the shortest path connecting  $r_0$  and  $x$ . The deepest ancestor of a vertex is its *parent*, denoted by  $f(x)$ . A vertex  $y$  is said to be *below*  $x$  if  $\exists i \geq 0$  s.t.  $f^i(y) = x$ . Note that  $x$  is below itself.

**Proposition 13.**

$$2 \left\lfloor \frac{h-1}{\lfloor \log_k c \rfloor + 1} \right\rfloor + 1 \leq \tilde{D}(T(k, h), c) \leq 2 \left\lfloor \frac{h}{\lfloor \log_k c \rfloor + 1} \right\rfloor + 2$$

*Proof.* Let us start with proving the lower bound. Let  $H$  be a  $c$ -DVPL of  $T(k, h)$ . Let  $\gamma = \lfloor \log_k c \rfloor + 1$ . Let  $r$  be a vertex of depth  $d$ ,  $1 \leq d \leq h - \gamma$ ; Let  $B(\gamma, r)$  denote the complete  $k$ -ary

subtree of  $T(k, h)$  of depth  $\gamma$  rooted at  $r$ . A leaf  $x$  of  $B(\gamma, r)$  is said to be *upward-bad* for  $r$  if there does not exist any virtual arc  $e'$  that starts in a vertex below  $x$  and ends in a vertex not below  $r$ . If there doesn't exist any virtual arc  $e'$  that starts not below  $r$  and ends below  $x$  then  $x$  is said to be *downward-bad* for  $r$ .




**Fig. 5.**  $k = 2$ ,  $c = 2$  or  $3$ ,  $\gamma = 2$ , there exist no arcs from A to B; (on the right)  $k = 2$ ,  $\gamma = 2$ ,  $h = 6$ , one cannot do better than 5 from  $l_3$  to  $r_3$

We claim the following: *For any vertex  $r$  of depth  $d$ ,  $1 \leq d \leq h - \gamma$  there exist an upward-bad vertex and a downward-bad vertex for  $r$ .*


Indeed, suppose that all the  $k^\gamma$  leaves of  $B(\gamma, r)$  are not upward-bad. There exists a virtual arc that starts below each leaf and ends not below  $r$ . Then the load of the arc  $(r, f(r))$  is at least  $k^\gamma$ . Contradicting the fact that the capacity of this arc is  $c < k^{\lfloor \log_k c \rfloor + 1}$ , there exists at least one leaf that is upward-bad for  $r$ . The same argument considering the load of arc  $(f(r), r)$  completes the proof of the claim.

Now we prove that  $D_H \geq 2(\lfloor \frac{h-1}{\gamma} \rfloor) + 1$ . Let  $i_0 = \lfloor (h-1)/\gamma \rfloor + 1$ . Define two sequences of vertices  $(l_i)_{i=1..i_0}$  and  $(r_i)_{i=1..i_0}$  as follows. Let  $l_1$  and  $r_1$  be the leftmost and the rightmost neighbors of  $r_0$ , respectively. If  $i \leq i_0 - 1$ , choose for  $l_{i+1}$  a leaf of  $B(\gamma, l_i)$  which is an upward-bad vertex for  $l_i$ . By induction, the depth of  $l_i$  is  $1 + \gamma(i-1)$  and if  $i \leq i_0 - 1$  it is less than  $h - \gamma$  so, from the claim,  $l_{i+1}$  exists. Symmetrically, we define the sequence  $(r_i)_{i=1..i_0}$  by choosing  $r_{i+1}$  as one of the downward-bad vertices for  $r_i$ .

Let us now consider the shortest path  $\mathcal{P}$  in  $H$  from  $l_{i_0}$  to  $r_{i_0}$ . Let  $y$  be the first vertex of  $\mathcal{P}$  not below  $l_1$ . By construction,  $\mathcal{P}$  uses at least  $i_0$  virtual arcs from  $l_{i_0}$  to  $y$ . Also  $x$ , the predecessor of  $y$  in  $\mathcal{P}$ , is below  $l_1$  and thus not below  $r_1$ . Hence,  $\mathcal{P}$  uses at least  $i_0$  virtual arcs from  $x$  to  $r_{i_0}$ . In summary,  $\mathcal{P}$  uses at least  $2i_0 - 1$  virtual arcs. So  $D_G \geq 2i_0 - 1$  that is  $2(\lfloor (h-1)/\gamma \rfloor) + 1$ .



**Fig. 6.** Binary Tree,  $c = 4$ ,  $h = 6$



**Fig. 7.** Case  $c = 2$ ,  $k = 2$

To establish the upper bound, we describe a symmetric layout. An example is illustrated in Fig. 6. Each vertex of depth more than  $h - \lfloor \log_k c \rfloor$  is linked to all its descendants. The load induced is less than  $\frac{k^{\lfloor \log_k c \rfloor - 1}}{k-1} \leq c$ . Each vertex of depth exactly  $h - \lfloor \log_k c \rfloor - t$  ( $\lfloor \log_k c \rfloor + 1$ ) with  $t \geq 0$  is linked to all its ancestors of depth more than  $h - \lfloor \log_k c \rfloor - (t+1)(\lfloor \log_k c \rfloor + 1)$ . If  $h = \lfloor \log_k c \rfloor + t(\lfloor \log_k c \rfloor + 1) + \alpha$  with  $t \geq 0$  and  $0 \leq \alpha < \lfloor \log_k c \rfloor + 1$ , the diameter is  $2(t+1)$  if  $\alpha = 0$  and  $2(t+2)$  if  $\alpha > 0$ , that is  $2 \lfloor \frac{h}{\lfloor \log_k c \rfloor + 1} \rfloor + 2$ .

In the special case of  $c = 2$ ,  $k = 2$  we add two VPs between the two neighbors of the root as shown on Fig. 7. We get an upper bound of  $h + 1$ . ■

## 6 Arbitrary Trees

In this section the physical graph  $G$  is  $T$  a tree rooted at  $r$ . We assume that  $\forall e \in E$ ,  $c(e) = c^+ \geq 1$  if  $e$  is an arc going up (from a vertex to its parent) and  $c(e) = c^- \geq 1$  if  $e$  is an arc going down. Again, it turns out that our bound can be expressed as a function of  $\sigma = c^+ + c^-$ , and therefore it is convenient to define  $ub_T(\sigma)$  as an upper bound on  $\tilde{D}(T, c)$  valid if  $c$  satisfies  $c^+ + c^- = \sigma$  and  $g(\sigma, n)$  an upper bound on  $ub_T(\sigma)$  valid if  $T$  has  $n$  vertices. By the definition,  $\tilde{D}(T, c) \leq ub_T(\sigma) \leq g(\sigma, n)$ .

The lower bound follows from our bound for the  $n$ -vertex path  $P_n$ , upon noting the following. Let  $D_T$  denote the depth of  $T$ .

**Proposition 14.**

$$\tilde{D}(T, c) \geq \tilde{D}(P_{D_T}, c) \geq (D_T)^{\frac{1}{2c-1}} / 2$$

*Proof.* Let  $H$  be an admissible virtual graph on  $T$ . Let  $u$  and  $v$  be two vertices at maximum distance,  $d_T(u, v) = D_T$ . Consider the shortest dipath  $\mathcal{Q}$  in  $T$  from  $u$  to  $v$ .

We build a VPL on  $\mathcal{Q}$  based on  $H$ . To each VP  $P(e')$  on  $T$  is associated a VP on  $\mathcal{Q}$  that is the intersection of  $P(e')$  and  $\mathcal{Q}$  (i.e. the dipath formed by all the common arcs of  $P(e')$  and  $\mathcal{Q}$ ). Since  $T$  is a tree, the intersection of two paths is a well-defined path.

Thus,  $H$  induces a VPL on  $\mathcal{Q}$  that loads physical arcs no more than the original VPL on  $G$ . Furthermore the diameter of this new VPL is no more than the diameter of the original one. ■

**Proposition 15.**

$$\tilde{D}(T, c) \leq \tilde{D}(C_{2n-2}, c/2) \leq 2c(n-1)^{1/c} + 1$$

*Proof.* This natural upper bound follows by embedding a cycle around the tree. Consider a cycle  $C_{2n-2}$  embedded around the tree  $T$  in a depth-first fashion. Let  $c^+ = \lceil c/2 \rceil$  and  $c^- = \lfloor c/2 \rfloor$ . An admissible graph  $H$  on  $C_{2n-2}$  with respect to  $c^+$  on positive arcs and  $c^-$  on negative ones gives us an admissible virtual graph on  $T$ . ■

Our main VPL construction for trees makes use of  $\rho$ -dominating sets. Hence to establish an upper bound on  $\tilde{D}(T, c)$ , we need the following two preliminary lemmas regarding the existence of small  $\rho$ -dominating sets in arbitrary trees.

**Definition 16.** Let  $\rho$  be a positive integer. A  $\rho$ -dominating set is a subset  $S$  of  $V(T)$  such that for all  $x \in V(T)$ ,  $d(x, S) \leq \rho$

**Lemma 17.** For any  $\rho$ , there exists a  $\rho$ -dominating set of cardinality at most  $\frac{n-1}{\rho+1} + 1$ .

*Proof.* Let  $L_i = \{x \in T ; d(x, r) = i\}$  for  $i = 0..D_T$  and  $V_j = \bigcup_{i=j \bmod (\rho+1)} L_i \cup \{r\}$  for  $j = 0..\rho$ .

Each  $V_j$  is a  $\rho$ -dominating set and the family  $(V_j - \{r\})_{j=0..\rho}$  is a partition of  $V(T) - \{r\}$ . Thus, by choosing the  $V_j$  of smallest cardinality, we get lemma 17. ■

**Lemma 18.** For any  $\rho$ , there exists a  $\rho$ -dominating set  $S$  of cardinality at most  $2 \frac{n-1}{\rho+1}$  such that the paths from a vertex of  $S$  to its deepest ancestor in  $S$  are pairwise arc-disjoint.

*Proof.* Let  $S$  be a  $\rho$ -dominating set of cardinality  $s_0$ . We apply the following algorithm to  $S$ :

```

Initialization  $S' := S$ .
while there exist two distinct vertices  $x$  and  $y$  in  $S'$  such that the deepest common
ancestor  $z$  of  $x$  and  $y$  is not in  $S$  do
  begin
    Choose a triple  $x, y, z$  such that the depth of  $z$  is maximum.
     $S' := (S' - \{x, y\}) \cup \{z\}$ .
     $S := S \cup \{z\}$ .
  end


```

Since the initial set  $S$  is a  $\rho$ -dominating set, the final set  $S$ , that contains the initial one, is also a  $\rho$ -dominating set.

Since  $r$  can never be deleted from  $S'$ , the cardinality of  $S'$  must be at least 3 ( $r, x$  and  $y$ ) to enter the loop. Thus, since at each step of the algorithm  $|S'|$  decreases by 1, the algorithm terminates at most after  $s_0 - 2$  steps. Since at each step  $|S|$  increases by 1, the final set  $S$  has cardinality at most  $2s_0 - 2$ . By lemma 17 if the initial set  $S$  is minimal then  $s_0 \leq \frac{n-1}{\rho+1} + 1$  and thus the cardinality of the final set  $S$  is no more than  $2 \frac{n-1}{\rho+1}$ .

It remains to prove that paths from a vertex of  $S$  to its deepest ancestor in  $S$  are pairwise arc-disjoint. Let  $t$  and  $u$  be two vertices in  $S$  such that this condition fails. Let  $w$  be their deepest common ancestor.  $w$  is not in  $S$ . We can suppose that there is no vertex of  $S$  between  $t$  (resp.

$u$ ) and  $w$ . Otherwise, replace  $t$  (resp.  $u$ ) by the last vertex of  $S$  on the dipath from  $t$  (resp.  $u$ ) to  $w$ . Since  $t$  and  $u$  are in the final set  $S$ , they both have been in some set  $S'$ . Since the algorithm is completed  $t$  and  $u$  are not both in the final  $S'$ . W.l.o.g we can suppose that  $t$  is deleted from  $S'$  before  $u$ . Let  $i$  be the step of the algorithm where  $t$  is deleted from  $S'$ , let  $t$  and  $y$  be the two vertices chosen by the algorithm at step  $i$  and let  $z$  is their deepest common ancestor. Since after step  $i$ ,  $z$  is in  $S$  and  $w$  is below the lowest ancestor of  $t$  in the final  $S$ ,  $w$  is strictly below  $z$ . Since



**Fig. 8.** Step  $i$  of the algo

at the end of the algorithm  $u$  is in  $S$ , there exists a vertex  $u'$  in  $S'$  such that  $w$  is the deepest common ancestor of  $u'$  and  $t$ . The triple  $(t, u', w)$  should have been chosen instead of  $(t, y, z)$  and thus  $w$  should be in the final set  $S$ . This contradicts our hypothesis and completes the proof of lemma 18. ■

**Proposition 19.**

$$\tilde{D}(T, c) \leq 5\sigma n^{\frac{1}{\sigma-1}}$$

*Proof.* The proof is by induction. We first construct a  $\rho$ -dominating set  $S$  of representative vertices in  $T$  using lemma 18. Hence every vertex is at distance at most  $\rho$  from  $S$ , and the paths between a vertex of  $S$  and its deepest ancestor in  $S$  are arc-disjoint. Then we construct a VPL by induction on  $\sigma$ , i.e., we apply induction on a tree built on the set  $S$  with capacity  $\sigma - 1$ .

Given  $S$ , let  $T'$  be the tree rooted at  $r$  defined by  $V(T') = S$  and

$$A(T') = \{(s, s'), (s', s) \mid s' \text{ is the deepest ancestor of } s \text{ in } S\}.$$

An arc of  $T'$  corresponds to a path in  $T$ . By lemma 18 arcs of  $T'$  correspond to arc disjoint paths in  $T$  and  $|V(T')| \leq 2 \frac{|V(T)|-1}{\rho+1}$ .

The VPL is built as follow.

**If  $c^+ \geq c^-$  then**

All arcs of  $T$  from a vertex to its parent are VPs.

All arcs of  $T$  from a vertex that is not an ancestor of a vertex of  $S$  to its child are VPs.


We construct the VPL for the tree  $T'$  with capacities  $c'^+ = c^+ - 1$  and  $c'^- = c^-$ .

**else**

All arcs of  $T$  from a vertex its child are VPs.

All arcs of  $T$  from a vertex that is not an ancestor of a vertex of  $S$  to its parent are VPs.

We construct the VPL for the tree  $T'$  with capacities  $c'^+ = c^+$  and  $c'^- = c^- - 1$ .



**Fig. 9.** A step in the construction of the VPL. case 1,  $c^+ \geq c^-$ .

To go from a vertex  $u$  to a vertex  $v$  in the virtual graph, we go from  $u$  to a vertex in  $S$  in at most  $\rho$  steps and then move on the virtual graph built on  $T'$  (in at most  $\tilde{D}(T', c')$  steps) and then go from a vertex in  $S$  to  $v$  in at most  $\rho$  steps. So,  $\tilde{D}(T, c) \leq 2\rho + \tilde{D}(T', c')$ .

For an arbitrary tree with capacity 1 on each link, the trivial VPL (where each arc becomes a VP) has diameter at most  $n$ .

$\tilde{D}(T, c) \leq 2\rho + \tilde{D}(T', c')$ . Thus,  $\forall T$ ,  $\tilde{D}(T, c) \leq 2\rho + g(\sigma - 1, 2\frac{n-1}{\rho-1})$  and thus,  $g(\sigma, n) \leq 2\rho + g(\sigma - 1, 2\frac{n-1}{\rho-1})$ .

Let us show by induction that  $\forall \epsilon > 0$ ,  $\exists N$  such that  $\forall n \geq N$ ,  $g(\sigma, n) \leq (4 + \epsilon)\sigma n^{\frac{1}{\sigma-1}}$ . The assertion is true for  $c = 1$  (i.e.  $\sigma = 2$ ). Suppose it is true for  $\sigma - 1$ . Then

$$g(\sigma, n) \leq 2\rho + (4 + \epsilon)(\sigma - 1) \left(2\frac{n-1}{\rho-1}\right)^{\frac{1}{\sigma-2}}.$$

Let  $\rho = 2(n-1)^{\frac{1}{\sigma-1}} + 1$ . Then

$$\begin{aligned} g(\sigma, n) &\leq 4(n-1)^{\frac{1}{\sigma-1}} + 2 + (4 + \epsilon)(\sigma - 1)(n-1)^{\frac{1}{\sigma-1}} \\ &= (4 + \epsilon)\sigma(n-1)^{\frac{1}{\sigma-1}} + 2 - \epsilon(n-1)^{\frac{1}{\sigma-1}}. \end{aligned}$$

For  $c = o(n)$  we get  $g(\sigma, n) \leq (4 + \epsilon)\sigma n^{\frac{1}{\sigma-1}}$  for  $n$  greater than some  $N$ .

Taking  $\epsilon = 1$  completes the proof of the proposition ( $N = 2^{\sigma-1} + 1$ ). ■

In particular we have


**Corollary 20.** *If  $c^+ = c^- = c$  then  $\tilde{D}(T, c) \leq 10cn^{\frac{1}{2c-1}}$ .*

Our final construction is given in the following claim.

**Proposition 21.**

$$\tilde{D}(T, c) \leq \tilde{D}(P_{D_T}, c) \cdot \log n = \mathcal{O}(c \cdot D_T^{1/(2c-1)} \cdot \log n)$$

*Proof.* Construct an admissible virtual graph  $H$  on  $T$  by recursively decomposing  $T$  using tree separators. A separator node  $S(T)$  breaks  $T$  into subtrees of cardinality less than  $n/2$ . It is well-known that such a separator always exists, and can be found via the following straightforward algorithm. Start with an arbitrary node as  $S(T)$ . While  $S(T)$  does not break the tree  $T$  into subtrees of cardinality less than  $n/2$ , one of the considered subtrees is of cardinality strictly more than  $n/2$ , move  $S(T)$  to its neighbor in this subtree.



**Fig. 10.**

Let  $T_i$  be a subtree of  $T$  rooted at  $r_i$  and  $v_i$  be the only neighbor of  $r_i$  that is not in  $T_i$ . We describe here a procedure  $A(T_i)$ , used for constructing  $H$ .

1. find  $S(T_i)$
2. apply the optimal path layout to the path  $P_i$  from  $v_i$  to  $S(T_i)$ .
3. consider the trees  $(T'_i)_{i=1..k}$  made of arcs not already involved in the layout rooted at a neighbor of  $S(T_i)$  or of a vertex of  $P_i$ .
4. apply  $A(T'_i)$  to each subtree  $T'_i$  that is not only one vertex.

The construction of  $H$  is as follows.

1. find  $S(T)$
2. recursively apply  $A(T_i)$  on each subtree.  
(Note that for the first use of the algorithm,  $v_i = S(T)$ .)

To analyze the diameter of the resulting virtual graph  $H$ , let

$$f(n) = \max_{T \text{ rooted at } r, |T|=n} \max_x (d_H(r, x), d_H(x, r)).$$

At this point, it is possible to derive a result very similar to that of Proposition 19, by observing that  $f(n)$  can be bounded recursively by

$$f(n) \leq f(n/2) + \tilde{D}(P_n, c).$$



This yields that there exists  $\alpha(c)$  such that  $f(n) \leq \alpha(c) \cdot n^{\frac{1}{2c-1}}$ . Indeed,  $\tilde{D}(P_n, c) \leq (4c - 2) \left(\frac{n-1}{2}\right)^{\frac{1}{2c-1}} + 2$  and thus for  $\alpha(c) \geq 8c$  the result is proved by induction. For  $c = 2$  it gives  $f(n) \leq 16n^{1/3}$  and thus  $\tilde{D}(T, 2) \leq 32n^{1/3}$ .

However, for low-depth trees  $T$  it may be preferable to use a different recursive bound for  $f(n)$ , namely,

$$f(n) \leq f(n/2) + \tilde{D}(P_{D_T}, c),$$

which gives the following upper bound:  $f(n) \leq \tilde{D}(P_{D_T}, c) \cdot \log n$ . ■

## 7 Grids and Toroidal Meshes

In this section we consider as our physical digraph  $G$  the toroidal mesh of dimensions  $a \times b$ ,  $TM(a, b)$ . Recall that  $TM(a, b) = C_a \square C_b$ , the Cartesian sum (also called product) of two cycles.

### Proposition 22.

$$\tilde{D}(TM(a, b), c) \leq 4(2c - 1) \cdot \left(\frac{a}{2}\right)^{\frac{1}{2c-1}} + 4ac \left(\frac{b}{2}\right)^{1/2ac} + 2a + 1$$

*Proof.*  $TM(a, b)$  can be viewed as composed of  $a$  different *main cycles* of length  $b$  each, numbered from 1 to  $a$  and connected to each other cyclically by  $b$  *transversal cycles* numbered from 1 to  $b$ .

On a cycle of length  $b$ , the best  $ac$ -DVPL we have is the one built in section 3. This DVPL is made of  $2ac$  VPs of lengths  $\left(\frac{b}{2}\right)^{\frac{i}{2ac}}$  for  $0 \leq i \leq 2ac - 1$ . Its diameter is  $D_m \leq 4ac \left(\frac{b}{2}\right)^{\frac{1}{2ac}} + 1$ .

The VPL we build on  $TM(a, b)$  is based on this one. On the  $i$ -th main cycle (of length  $b$ ), we build  $2c$  VPs of lengths

$$\left(\frac{b}{2}\right)^{\frac{(i-1)c}{2ac}}, \left(\frac{b}{2}\right)^{\frac{(i-1)c+1}{2ac}}, \dots, \left(\frac{b}{2}\right)^{\frac{ic-1}{2ac}},$$

in alternating directions, i.e., one in the positive direction and the next in the negative direction. The load is  $c$ .

On the  $b$  transversal cycles, we build the best DVPL we have with  $c^+ = c$  and  $c^- = c - 1$ , as described in section 3.1. The construction sets up  $2c - 1$  VPs of lengths

$$1, \left(\frac{a}{2}\right)^{\frac{1}{2c-1}}, \dots, \left(\frac{a}{2}\right)^{\frac{2c-2}{2c-1}},$$

again in alternating directions. Hence the load is  $c$  in the positive direction and  $c - 1$  in the negative one. The remaining unit of capacity in the negative direction is used to build VPs of length 1.

Finally, we have VPs of length 1 in both the directions on the transversal cycles and the virtual diameter of transversal cycles is  $D_t \leq 2(2c - 1) \left(\frac{a}{2}\right)^{\frac{1}{2c-1}} + 1$ .

To move from  $[i, j]$  to  $[i', j']$ , we first reach the first main cycle where we find main VPs of length  $1, \frac{b}{2}, \dots, \left(\frac{b}{2}\right)^{\frac{c-1}{2ac}}$ . It costs at most  $D_t$  hops to reach  $[1, j]$ . Then, we move to  $[1, j']$  using main VPs of increasing then decreasing dilation and moving between main cycles using transversal VPs of dilation 1. It costs at most  $2(a - 1) + D_m$ . We then reach  $[i', j']$  in at most  $D_t$  hops. Finally, we get an upper bound on the virtual diameter of  $2D_t + D_m + 2(a - 1)$ . ■

Note that in order to get a graph  $G$  such that  $\tilde{D}(G, c) \sim \log n$  with  $c \geq 1$  we can use a toroidal mesh  $T(\log n, \frac{n}{\log n})$ . Using the lower bound of  $\log n$  proved in section 8 we have the following :


**Proposition 23.** *There exists an infinite family of digraphs with  $n$  vertices and diameter  $n/\log n$ , such that  $\tilde{D}(G, 1) = \Theta(\log n)$ .*

For  $\lceil \log_2 b \rceil \leq a \leq b$  we do not need the toroidal structure to get a good upper bound. We present here a VPL on a mesh  $M(a, b) = P_a \square P_b$  that leads to the following bound.

**Proposition 24.**


$$\tilde{D}(M(a, b), 1) = \Omega(\log n)$$

*Proof.* Construct an admissible virtual graph  $H$  on  $M(a+1, b+1)$  by patching together a number of *strips*, defined as follows. Let  $A = \lceil \log_2 b \rceil$ ,  $B = \lceil \log(a - A + 1) \rceil$ , and  $C = b + 1 - \lfloor \frac{b+1}{B} \rfloor B$ .



**Fig. 11.** Position of the strips

$H$  is made of a horizontal strip of width  $A$ , and  $\lfloor \frac{b+1}{B} \rfloor$  vertical strips of width  $B$ . (See Fig. 11.) Also, there is a last “remainder” strip of width  $C$  put in the opposite direction. A horizontal strip of width  $k$  is made of  $k$  rows, where row  $i$ ,  $1 \leq i \leq k$  uses horizontal symmetric arcs of dilation  $2^{i-1}$ . (See Fig. 12.) A vertical strip is similarly defined for vertical virtual arcs. All physical arcs



**Fig. 12.** Composition of a strip

that are not used in virtual arcs involved in the strips are used as virtual arcs of length 1. An example of this construction is depicted in Fig. 13. We next show that the diameter of such a graph is at most  $4A + 5B - C - 6$ . Towards that proof, define special vertices named *main points*.




Fig. 13.  $M(10, 13)$ ,  $A = 4$ ,  $B = 3$ ,  $C = 2$

These are the vertices on the  $A$ th line from the top, at columns that are multiples of  $B$  from the left. The routing strategy is based on reaching a main point from the initial vertex, then reaching the main point closest to the destination vertex using virtual arcs of the horizontal strip, and finally reach the destination point itself. The worst case occurs when the initial vertex is in the last vertical strip (the one of width  $C$ ) and the destination point is in a vertical strip of width  $B$ .




Fig. 14. How to move in a strip

As illustrated in Fig. 14, to reach a main point in a strip of width  $W$ , one needs at most  $l(W) = 2W - 1$  hops.

The entire route is composed of a number of segments. One needs at most  $l(C)$  hops to reach the border of the strip of length  $C$ , at most  $B - C$  hops (using horizontal VPs of length 1) to reach the good row in the neighbor strip of length  $B$ , at most  $l(B - C)$  hops to reach a main point, at most  $2l(A) - 1$  hops (using VPs of the strip of length  $A$ ) to reach the good main point for the destination vertex, and then at most  $l(B)$  hops to the destination vertex. Hence the total route is of length at most  $4A + 5B - C - 6 \leq 5 \log n$ . ■

## 8 General Bounds

For most digraphs it turns out that  $\tilde{D}(G, c_0)$  is logarithmic even for  $c_0 = 1$ . Hence the ratio  $\frac{\tilde{D}(G, c_0)}{\log n}$  is of importance. For  $d$ -bounded degree digraphs<sup>1</sup>, a classical result states that  $\frac{\log n}{\log(c_0 d)} - 1 \leq$

<sup>1</sup> where both the in- and out- degrees are upper-bounded by  $d$

$\tilde{D}(G, c_0)$ . It is obtained by applying the Moore bound to the virtual digraph with  $n$  nodes, degree at most  $c_0 d$ , and diameter  $\tilde{D}(G, c_0)$  (see [17, 22]). Note also that  $\tilde{D}(G, 1) \leq D_G$ . Here we derive a tighter bound related to the expansion-congestion parameters of  $G$ . First we recall three standard definitions. A *routing* for  $G$  is a mapping associating with each ordered pair of vertices  $(x, y)$  a *route* (i.e. a dipath in  $G$ ) from  $x$  to  $y$ ; the *congestion* of a routing is the maximal *load* of an arc of  $G$  (i.e., the maximum number of routes going through an arc); the *arc-forwarding index* of  $G$ , denoted  $\pi(G)$ , is the minimum congestion over all possible routings.

The parameter  $\pi(G)$  has been extensively studied and many relations exist between  $\pi$  and other parameters like bisection or expansion, see [14, 18, 21]. There are strong relationships between  $\pi(G)$  and the DVPL issue. A routing for  $G$  is a DVPL of  $G$  where  $H$  is the complete digraph, and so  $\pi(G)$  is the smallest integer  $c_0$  such that  $\tilde{D}(G, c_0) = 1$ .

**Proposition 25.** *Let  $G$  be a  $d$ -bounded digraph.*

$$\frac{\log \pi(G)}{\log(c_0 d)} + O(\log \tilde{D}(G, c_0)) \leq \tilde{D}(G, c_0)$$

*Proof.* With every  $c_0$ -DVPL  $H$  of  $G$  one can associate a routing for  $G$  as follows. Note that for any ordered pair of vertices  $(x, y)$  there exists at least one dipath in  $H$  from  $x$  to  $y$  with length smaller than  $D_H$ . We select one such dipath and choose the associated real dipath as the route from  $x$  to  $y$ . Due to the capacity constraint, at most  $c_0 d$  virtual dipaths enter (resp., leave) any given vertex of  $G$ ; one can easily check that the number of dipaths in  $H$  of length  $k$  that use an arc is at most  $kc_0(c_0 d)^{k-1}$ . Hence the congestion of our routing is upper-bounded by

$$M = c_0 + 2c_0(c_0 d) + 3c_0(c_0 d)^2 + \dots + D_H c_0(c_0 d)^{D_H-1}.$$

By definition,  $\pi \leq M$ ; as  $M \leq c_0 \frac{D_H(c_0 d)^{D_H}}{c_0 d - 1}$ , taking the logarithm we obtain the result. ■

*Remark 26.* The lower bound of proposition 25 is rather similar to the one derived on the gossip time of a network under WDM or wormhole models [7, 3]. In both cases one must construct a route between any pair of vertices: for gossip problems the route is built along  $T$  time steps, whereas in the context of VPL design it is constructed by using  $\tilde{D}(G, c)$  jumps.

The following proposition is the counterpart of proposition 23, and in some sense establishes its tightness. Specifically, it indicates that for *bounded*  $c_0$ , one can expect  $\tilde{D}(G, c_0)$  to be logarithmic only if  $D_G$  is not too large. The result is valid for (distance-) symmetric digraphs (namely, such that  $d(x, y) = d(y, x)$ ).

**Proposition 27.** *Let  $G$  be a symmetric bounded degree digraph with  $\log D_G = \Omega(\log n)$ .*

$$\tilde{D}(G, c) = \Theta(\log n) \implies c = \Omega(D_G \log n / n)$$

*In particular, if  $c$  is constant*

$$\tilde{D}(G, c) = \Theta(\log n) \implies D_G = O(n / \log n).$$

*Proof.* The idea is that the design of an efficient DVPL is prevented by the existence of a long geodesic dipath contained in  $G$ . Let us first formalize the notion that a digraph “contains” some bad sub-structure.

Define a *retraction* of a digraph  $G$  as a digraph  $G'$  such that there exists a mapping  $f$  from  $V(G)$  onto  $V(G')$  satisfying the following *contraction* condition:  $d_G(x, y) \geq d_{G'}(f(x), f(y))$ .

Define the *total load* of  $G$  for virtual diameter  $D_0$  as

$$\mathcal{L}(G, D_0) = \min(\sum_{e \in E} l(e)),$$

where the minimum is taken on all DVPL such that  $D_H \leq D_0$ .

Due to the contraction condition, for any retraction  $G'$  of  $G$  we have  $\mathcal{L}(G, D_0) \geq \mathcal{L}(G', D_0)$ . Moreover, denoting the number of arcs of  $G$  by  $|E|$ , the maximum load is greater than or equal to the average load. Hence we have proven the following.

**Lemma 28.** *If  $G'$  is a retraction of  $G$  then*

$$\pi(G, D_0) \geq \frac{\mathcal{L}(G, D_0)}{|E|} \geq \frac{\mathcal{L}(G', D_0)}{|E|}.$$

Next, we claim that the path  $P_{D_G}$  of length  $D_G$  is a retraction of  $G$ . To prove this, consider the following mapping. Label the vertices of  $P_{D_G}$  by  $0, 1, \dots, D_G$ , and choose a pair of vertices  $(x, y)$  of  $G$  such that  $d(x, y) = d(y, x) = D$ ; then map any vertex at distance  $i$  from  $x$  onto vertex  $i$  of the path. Due to the triangle inequality, and to symmetry, the mapping is contracting.

Now, suppose that we are given a bounded degree digraph  $G$  with  $\log D_G = \Theta(\log n)$ , and the capacity function  $c_0$ . Consider any DVPL with diameter  $D_H = \Theta(\log n)$ . By lemma 28 we have  $c_0 \geq \mathcal{L}(L_{D_G}, D_H)/|E|$ . We also know that if  $D_0 \sim \log D_G$  then  $\mathcal{P}(L_{D_G}, D_0) \sim D_G \log D_G$  [23]. It follows that  $c_0 \geq D_G \log D_G / |E|$ . As  $|E| \leq nd$ , we obtain  $c_0 \geq \frac{D_G \log n}{dn}$ . ■

## 9 Open problems and directions

Some of our bounds are not tight, and the remaining gaps may be narrowed. Establishing upper and lower bounds on  $\tilde{D}$  for other families of graphs may also be interesting and useful.

Looking for the minimum diameter is reasonable when all the connections may be requested with roughly the same probability, which is also not always realistic. In case of non-uniform traffic, instead of studying  $\tilde{D}$ , one may try to optimize its weighted counterpart,  $\sum r(i, j) \cdot d_H(i, j)$ , where  $r(i, j)$  denotes the traffic requirements between  $i$  and  $j$ ; such a target function may make it desirable to place the VPs between the node pairs which communicate the most.

Finally, there may be other parameters of the directed ATM model worth studying. One may also consider variations on the model with variable capacity of the VPs.

## Acknowledgments

The authors would like to thank Amotz Bar-Noy, Bruno Beauquier, Pascal Chanas, Michele Flammini, Cyril Gavoille and Daniel Kofman for helpful discussions.

## References

1. W. Aiello, S. Bhatt, F. Chung, A. Rosenberg, and R. Sitaraman. Augmented ring networks. *J. Math. Modelling and Scientific Computing*, 1997.
2. L. Becchetti, P. Bertolazzi, C. Gaibisso, and G. Gambosi. On the design of efficient ATM routing schemes. 1997.
3. J.-C. Bermond, L. Gargano, S. Perennes, A. Rescigno, and U. Vaccaro. Effective collective communication in optical networks. In *Proceedings of ICALP 96*, volume 1099 of *Lectures Notes In Computer Science*, pages 574–585. Springer Verlag, July 1996.
4. M. Burlet, P. Chanas, and O. Goldschmidt. Optimization of VP layout in ATM networks. In preparation, 1998.
5. P. Chanas. *Dimensionnement de réseaux ATM*. PhD thesis, CNET Sophia, Sept. 1998. In preparation.
6. P. Chanas and O. Goldschmidt. Conception de réseau de VP de diamètre minimum pour les réseaux ATM. In *Road-f'98*, pages 38–40, 1998.
7. O. Delmas and S. Perennes. Circuit-Switched Gossiping in 3-Dimensional Torus Networks. In *Proceedings of the Euro-Par'96 Parallel Processing / Second International EURO-PAR Conference*, volume 1123 of *Lecture Notes in Computer Science*, pages 370–373, Lyon, France, Aug. 1996. Springer Verlag.
8. Y. Dinitz, Feiglstein, and S. Zaks. On optimal graphs embedded into paths and rings, with analysis using 11-spheres. In *Proc. 23rd Int. Workshop on Graph-Theoretic Concepts in Computer Science (WG)*. Springer Verlag, 1997.
9. T. Eilam, M. Flammini, and S. Zaks. A complete characterization of the path layout construction problem for ATM networks with given hop count and load. In *24th International Colloquium on Automata, Languages and Programming (ICALP)*, volume 1256 of *Lecture Notes in Computer Science*, pages 527–537. Springer-Verlag, 1997.
10. M. Feiglstein and S. Zaks. Duality in chain ATM virtual path layouts. In *4th International Colloquium on Structural Information and Communication Complexity (SIROCCO)*, Monte Verita, Ascona, Switzerland, July 1997.
11. O. Gerstel, I. Cidon, and S. Zaks. The layout of virtual paths in ATM networks. *IEEE/ACM Transactions on Networking*, 4(6):873–884, 1996.
12. O. Gerstel, A. Wool, and S. Zaks. Optimal layouts on a chain ATM network. *Lecture Notes in Computer Science*, 979:508–??, 1995.
13. O. Gerstel and S. Zaks. The virtual path layout problem in fast networks. In *Symposium on Principles of Distributed Computing (PODC '94)*, pages 235–243, New York, USA, Aug. 1994. ACM Press.
14. M.-C. Heydemann, J.-C. Meyer, and D. Sotteau. On forwarding indices of networks. *Discrete Appl. Math.*, 23:103–123, 1989.
15. J.-W. Hong, K. Mehlhorn, and A. Rosenberg. Cost trade-offs in graph embeddings, with applications. *J. ACM*, 30:709–728, 1983.
16. D. Kofman and M. Gagnaire. *Réseaux Haut Débit, réseaux ATM, réseaux locaux et réseaux tout-optiques*. InterEditions-Masson, 1998. 2eme édition.
17. Kranakis, Krizanc, and Pelc. Hop-congestion trade-offs for high-speed networks. *IJFCS: International Journal of Foundations of Computer Science*, 8, 1997.
18. Y. Manoussakis and Z. Tuza. The forwarding index of directed networks. *Discrete Appl. Math.*, 68:279–291, 1996.
19. M. D. Pricker. *Asynchronous Transfer Mode, Solution for Broadband ISDN*. Prentice Hall, August 1995. 3rd edition 332p.
20. A. Rosenberg. Issues in the study of graph embeddings. In *Graph-Theoretic concepts in computer science*. Springer, 1980.
21. P. Solé. Expanding and forwarding. *Discrete Appl. Math.*, 58:67–78, 1995.
22. L. Stacho and I. Vrt'o. Virtual path layouts for some bounded degree networks. In *Structure, Information and Communication Complexity, 3rd Colloquium, SIROCCO*, pages 269–278, june 1996.
23. S. Zaks. Path layout in ATM networks - a survey. In *The DIMACS Workshop on Networks in Distributed Computing, DIMACS Center, Rutgers University*, Oct. 1997. manuscript.