

Interpreter & Compiler: exercises

Lectures 14-15-16

Formal Languages and Compilers 2011

Nataliia Bielova

Exercises for compiler

- for each in vectors (test_FOREACH.cre)

```
var 1: array[5] of int;  
...  
for each i in v do  
    begin  
        i := n;  
        n := n - 1;  
    end;
```

Intermediate code for FOR

- Node in syntax tree For (i, 1, n, cmd)
- Generated code (gencommand in commands.ml)

```
startfor: CG      increg      n   tmp      // tmp = (increg > n)
           JNE      tmp       0   endfor // if (increg > n) then jump
           ...
           ...                                // code generated for cmd
           ADD      increg      1   tmp
           CPY      tmp        NULL increg
           GOTO    startfor    NULL    NULL
endfor:  ...
```

Intermediate code for FOR EACH

- Node in syntax tree Foreach (e, v, cmd)
- Lower bound start=0
- Upper bound finish= dim-1
- Take a new increg = start
- start loop (increg <= finish)
- $e \leftarrow v[increg]$
- generate commands for cmd
- $v[increg] \leftarrow e$
- $increg \leftarrow increg + 1$
- end loop

Exercises for compiler

- interactive input from console (test_read.cre)

```
var i: int;
var f: float;
...
readInt(i);
readFloat(f);
```

- change: lexer, parser, syntax tree
- type checking (semantic.ml)
- intermediate code generation (commands.ml)
- + declaration of new intermediate code command (intermediate.ml)
- + target code generation (target.ml)

Exercises for interpreter

- Lecture 9: code of the interpreter
- Implement **for each** in vectors (test_FOREACH.cre)

```
var 1: array[5] of int;  
...  
for each i in v do  
    begin  
        i := n;  
        n := n - 1  
    end;
```

For: semantics

$C \parallel \text{for } i := \text{min} \text{ to } \text{max} \text{ do } c \parallel_{rs} =$

$= C' \parallel \text{for } i := \text{min} \text{ to } \text{max} \text{ do } c \parallel_{rs0}$

where :

$l_1 = \Lambda \parallel i \parallel_{rs}$

$s0 = \text{updatemem}(s, l_1, \text{min})$

$C' \parallel \text{for } i := \text{min} \text{ to } \text{max} \text{ do } c \parallel_{rs0} =$

$= \begin{cases} C' \parallel \text{for each } e \text{ in } v \text{ do } c \parallel_{rs''} & \text{if } B[i < \text{max}] = \text{true} \\ s' & \text{otherwise} \end{cases}$

where :

$s' = C \parallel c \parallel_{rs}$

$v = E \parallel i \parallel_{rs}$

$s'' = \text{updatemem}(s', l_1, v + 1)$

For each : semantics

$C \parallel \text{for each } e \text{ in } v \text{ do } c \parallel_{rs} =$
 $= \begin{cases} C \parallel \text{for each } e \text{ in } v \text{ do } c \parallel_{rs} & \text{if } i \leq \max \\ s & \text{otherwise} \end{cases}$

local variables : $\min = \text{lb}$, $\max = \text{ub}$, $i = \min$

where :

$s_0 = \text{updatemem}(s, l_e, v_{vi})$

$l_e = \Lambda \parallel e \parallel_{rs}$

$v_{vi} = E \parallel v[i] \parallel_{rs}$

$s' = C \parallel c \parallel_{rs0}$

$s'' = \text{updatemem}(s', l_{vi}, v_e)$

$l_{vi} = \Lambda \parallel v[i] \parallel_{rs'}$

$v_e = E \parallel e \parallel_{rs'}$