ProActive
Architecture of an Open Middleware for the Grid

Romain Quilici
www.objectweb.org/ProActive
ObjectWeb Architecture meeting
July 2nd 2003

ProActive
A Java API + Tools for Parallel, Distributed Computing

- A uniform framework: **An Active Object pattern**
- A formal model behind: **Prop. Determinism, insensitivity to deploy.**

Main features:

- Remotely accessible Objects (RMI, JINI, --> UDDI)
- Asynchronous Communications with synchro: automatic Futures
- Group Communications, Migration (mobile computations)
- XML Deployment Descriptors
- Interfaced with various protocols: rsh,ssh,LSF,Globus,--> SOAP
- Visualization and monitoring: IC2D

In the ObjectWeb Consortium
since April 2002 (LGPL License)

Table of Contents

- **ProActive Runtime**
- **Active Objects Model**
- **Future Objects and Automatic Continuation**
- **Groups Communication**
- **Active Objects Migration**
- **Abstract Deployment Model**
- **Components Infrastructure**
- **Security**

ProActive Runtime

- Transparently created when using ProActive
- Only one by JVM -- Singleton pattern
- Offer basics services to create or receive Active Objects
- Accessible remotely
- Partially hidden from users --> Use of Nodes (look like remote)
- ProActive Nodes are defined on PART --> possibly N nodes by JVMs
- Use of patterns to improve integration
  - Smart Proxy
  - Adapter
  - Factory ....

ProActive Runtime Architecture
RMI case



Table of Contents

- **ProActive Runtime**
- **Active Objects Model**
- **Future Objects and Automatic Continuation**
- **Groups Communication**
- **Active Objects Migration**
- **Abstract Deployment Model**
- **Components Infrastructure**
- **Security**

Active Object Model

- Active objects : coarse-grained structuring entities (subsystems)
- Each active object: - possibly owns many passive objects
  - has exactly one thread.
- No shared passive objects -- Parameters are passed by deep-copy
- Asynchronous Communication between active objects
- Future objects and wait-by-necessity.
- Full control to serve incoming requests (reification)



Creating active objects

- **Instantiation-based:**

```
A a = (A)ProActive.newActive(«A», params, node);
```

To get a non-FIFO behavior (Class-based):

class pA extends A implements **RunActive** { … }

- **Object-based:**

```
A a = new A (obj, 7);
...
...

a = (A)ProActive.turnActive (a, node);
```


ProActive: Reuse and seamless

- Two key features:
- Polymorphism between standard and active objects
  - Type compatibility for classes (and not only interfaces)
  - Needed and done for the future objects also
  - Dynamic mechanism (dynamically achieved if needed)




```
foo (A a)
{
  a.g (...);
  v = a.f (...);
  ...
  v.bar (...);
}
```

```
O.foo(a) : a.g()
and a.f() are
« local »
O.foo(p_a): a.g()
and a.f()are
remote + Async.»
```

- Wait-by-necessity: inter-object synchronization
  - Systematic, implicit and transparent futures (“value to come”)
    Ease the programming of synchronizations, and the reuse of routines

Active Object Components



Components of an Active Object

Active Object Architecture

RMI case



Body Architecture



Request to an Active Object



Table of Contents

- **ProActive Runtime**
- **Active Objects Model**
- **Future Objects and Automatic Continuation**
- **Groups Communication**
- **Active Objects Migration**
- **Abstract Deployment Model**
- **Components Infrastructure**
- **Security**

Future Objects

```
A res = ActiveObject.foo();
```



• The caller receives a Future : it continues its execution

• If it tries to access to the value or **res**, it is blocked in the future proxy (*Wait By Necessity*), until this value is available

Future Objects

```
A res = ActiveObject.foo();
```



• When the called object finish the computation of res, the value is returned to the caller

• Future is updated transparently

Automatic Continuation



Automatic Continuation

A Future can be passed by parameter or by result: chains of futures will be updated by **Automatic Continuation**.



Automatic Continuation

A Future can be passed by parameter or by result: chains of futures will be updated by **Automatic Continuation**.



Automatic Continuation

A Future can be passed by parameter or by result: chains of futures will be updated by **Automatic Continuation**.



Automatic Continuation

A Future can be passed by parameter or by result: chains of futures will be updated by **Automatic Continuation**.



Automatic Continuation

A Future can be passed by parameter or by result: chains of futures will be updated by **Automatic Continuation**.



Automatic Continuation

A Future can be passed by parameter or by result: chains of futures will be updated by **Automatic Continuation**.



Automatic Continuation

A Future can be passed by parameter or by result: chains of futures will be updated by **Automatic Continuation**.



Table of Contents

- ProActive Runtime
- Active Objects Model
- Future Objects and Automatic Continuation
- Groups Communication
- Active Objects Migration
- Abstract Deployment Model
- Components Infrastructure
- Security

Group Communication

- Manipulate groups of Active Objects in a simple and typed manner
  - Typed groups of active and remote objects.
  - Maintain the 'dot ' notation, language property
  - Dynamic generation of groups of results
- Be able to express high-level collective communication
  - broadcast
  - scatter, gather
- Based on the ProActive communication mechanism
  - Replication of N ' single ' communications
  - Preservation of the « rendez-vous »
  - Asynchronous

Group Structure



Construction of a Result Group

```
A ag = newActiveGroup (…)
V v = ag.foo(param);
v.bar();
```



Typed Group Java or Active Object

Table of Contents

- ProActive Runtime
- Active Objects Model
- Future Objects and Automatic Continuation
- Groups Communication
- Active Objects Migration
- Abstract Deployment Model
- Components Infrastructure
- Security

Migration of Active Objects

Migration is initiated by the active object itself through a primitive: migrateTo

Can be initiated from outside through any public method

The active object migrates with:
- all pending requests
- all its passive objects
- all its future objects

Automatic and transparent forwarding of:
- requests (remote references remain valid)
- replies (its previous queries will be fullfilled)

Characteristics and optimizations

- Same semantics guaranteed (RDV, FIFO order point to point, asynchronous)
- Safe migration (no agent in the air!)
- Local references if possible when arriving within a VM
- Tensionning (removal of forwarder)



ObjectWeb

31

Characteristics and optimizations

- Same semantics guaranteed (RDV, FIFO order point to point, asynchronous)
- Safe migration (no agent in the air!)
- Local references if possible when arriving within a VM
- Tensionning (removal of forwarder)



ObjectWeb

32

Characteristics and optimizations

- Same semantics guaranteed (RDV, FIFO order point to point, asynchronous)
- Safe migration (no agent in the air!)
- Local references if possible when arriving within a VM
- Tensionning (removal of forwarder)



ObjectWeb

33

Characteristics and optimizations

- Same semantics guaranteed (RDV, FIFO order point to point, asynchronous)
- Safe migration (no agent in the air!)
- Local references if possible when arriving within a VM
- Tensionning (removal of forwarder)



ObjectWeb

34

Characteristics and optimizations

- Same semantics guaranteed (RDV, FIFO order point to point, asynchronous)
- Safe migration (no agent in the air!)
- Local references if possible when arriving within a VM
- Tensionning (removal of forwarder)



ObjectWeb

35

Characteristics and optimizations

- Same semantics guaranteed (RDV, FIFO order point to point, asynchronous)
- Safe migration (no agent in the air!)
- Local references if possible when arriving within a VM
- Tensionning (removal of forwarder)



ObjectWeb

36

Characteristics and optimizations

- Same semantics guaranteed (RDV, FIFO order point to point, asynchronous)
- Safe migration (no agent in the air!)
- Local references if possible when arriving within a VM
- Tensionning (removal of forwarder)



Characteristics and optimizations

- Same semantics guaranteed (RDV, FIFO order point to point, asynchronous)
- Safe migration (no agent in the air!)
- Local references if possible when arriving within a VM
- Tensionning (removal of forwarder)



API for Mobile Agents

- Basic primitive: migrateTo
  - public static void migrateTo (String u)
  - public static void migrateTo (Node n)
    // String or ProActive node (VM)
  - public static void migrateTo (Object o)
    // joinning another active object
- Primitive to automatically execute action upon migration
  - public static void onArrival (String r)
    // execute r upong arrival on a new Node
  - public static void onDeparture (String r)

Migration



Migration



Table of Contents

- **ProActive Runtime**
- **Active Objects Model**
- **Future Objects and Automatic Continuation**
- **Groups Communication**
- **Active Objects Migration**
- **Abstract Deployment Model**
- **Components Infrastructure**
- **Security**

Abstract Deployment Model Objectives

- Problem:
  - Difficulties and lack of flexibility in deployment
  - Avoid scripting for: configuration, getting nodes, connecting, etc.
- A key principle:
  - **Abstract Away from source code:**
    - Machines
    - Creation Protocols
    - Lookup and Registry Protocols
- Context:
  - Grid
  - Distributed Objects, Java
  - Not legacy-code driven, but adaptable to it

Descriptors: based on Virtual Nodes

- Virtual Node (VN):
  - Identified as a string name
  - Used in program source
  - Configured (mapped) in an XML descriptor file --> Nodes
- Operations specified in descriptors:
  - Mapping of VN to JVMs (leads to Node in a JVM on Host)
  - Register or Lookup VNs, Create or Acquire JVMs
  - Components Definition, Security Settings

Program Source Descriptor (RunTime)
|----------| |----------|
Activities (AO) --> VN VN --> JVMs --> Hosts
Runtime structured entities: 1 VN --> n Nodes in n JVMs

Mapping Virtual Nodes: example

Definitions and mapping

```
<virtualNodesDefinition>
    <virtualNode name="Dispatcher"/>
</virtualNodesDefinition>

<map virtualNode="Dispatcher">
    <jvmSet>
        <vmName value="Jvm1"/>
    </jvmSet>
</map>

<jvm name="Jvm1">
    <acquisition method="rmi"/>
    <creation>
        <processReference refid="jvmProcess"/>
    </creation>
</jvm>
```

Definition of Virtual Nodes

Mapping of Virtual Nodes

Mapping Virtual Nodes: example

Infrastructure informations

```
<processDefinition id="jvmProcess">
    <jvmProcess
    class="org.objectweb.proactive.core.process.JVMNodeProcess"/>
</processDefinition>

<processDefinition id="rshProcess">
    <rshProcess
    class="org.objectweb.proactive.core.process.rsh.RSHJVMProcess"
            hostname="sea.inria.fr">
        <processReference refid="jvmProcess"/>
    </rshProcess>
</processDefinition>
```

JVM on the current Host

JVM started using RSH

Virtual Nodes in Programs

1. Load the descriptor file

*Descriptor pad = ProActive.**getDescriptor** ("file://ProActiveDescriptor.xml");*

2. Activate the mapping

*VirtualNode vn = pad.**activateMapping** ("Dispatcher"); // Triggers the JVMs*

3. Use nodes

*Node node = vn.**getNode();***
...
C3D c3d = ProActive.newActive("C3D", param, node);
log (... "created at: " + node.name() + node.JVM() + node.host());

Table of Contents

- **ProActive Runtime**
- **Active Objects Model**
- **Future Objects and Automatic Continuation**
- **Active Objects Migration**
- **Groups Communication**
- **Abstract Deployment Model**
- **Components Infrastructure**
- **Security**

Components based on Fractal Model



ObjectWeb

49

Distributed and Parallel Components



ObjectWeb

50

Components Infrastructure



ObjectWeb

51

Components Infrastructure



ObjectWeb

52

Components Request



ObjectWeb

53

Table of Contents

- **ProActive Runtime**
- **Active Objects Model**
- **Future Objects and Automatic Continuation**
- **Active Objects Migration**
- **Groups Communication**
- **Abstract Deployment Model**
- **Components Infrastructure**
- **Security**

ObjectWeb

54

Security

- **Non-functionnal security**
  - located inside the meta-level, transparent for applications.
- **Hierarchical domains**
- **Dynamic policy negotiation**
- **Certification chain to identify users, JVMs, objects**
  - User certificate => Application certificate => active object certificate
  - User private key used only once for generating application certificate
- **Security policies set by <u>deployment descriptors</u>**

Request to an Active Object



Request path

Security mechanims