

From EULER Project

PmWiki: Custom Wiki Styles

This page describes the predefined [Wiki Styles](#) and how a [Wiki Administrator](#) can define additional [Wiki Styles](#) as a local customization for all pages (in local/config.php) or specific groups (in local/\$Group.php).

All predefined [Wiki Styles](#) are setup in the global array `$WikiStyle`. To define your own [Wiki Styles](#), add the setting of the correspondent WikiStyle within the array.

Predefined Wiki Styles

The following array-values are set by `scripts/wikistyles.php` using the [SDV\(\)](#)-function (so you can overwrite them by setting them prior in config.php or farmconfig.php):

markup:	definition:
text colors:	
(equiv. to %define=xxxx color=xxxx%	
%black%	<code>\$WikiStyle['black']['color'] = 'black';</code>
%white%	<code>\$WikiStyle['white']['color'] = 'white';</code>
%red%	<code>\$WikiStyle['red']['color'] = 'red';</code>
%yellow%	<code>\$WikiStyle['yellow']['color'] = 'yellow';</code>
%blue%	<code>\$WikiStyle['blue']['color'] = 'blue';</code>
%gray%	<code>\$WikiStyle['gray']['color'] = 'gray';</code>
%silver%	<code>\$WikiStyle['silver']['color'] = 'silver';</code>
%maroon%	<code>\$WikiStyle['maroon']['color'] = 'maroon';</code>
%green%	<code>\$WikiStyle['green']['color'] = 'green';</code>
%navy%	<code>\$WikiStyle['navy']['color'] = 'navy';</code>
%purple%	<code>\$WikiStyle['purple']['color'] = 'purple';</code>
list-styles:	
%decimal%	<code>\$WikiStyle['decimal']['apply'] = 'list'; \$WikiStyle['decimal']['list-style'] = 'decimal';</code>
%roman%	<code>\$WikiStyle['roman']['apply'] = 'list'; \$WikiStyle['roman']['list-style'] =</code>

	'lower-roman';
%ROMAN%	\$WikiStyle['ROMAN']['apply'] = 'list'; \$WikiStyle['ROMAN']['list-style'] = 'upper-roman';
%alpha%	\$WikiStyle['alpha']['apply'] = 'list'; \$WikiStyle['alpha']['list-style'] = 'lower-alpha';
%ALPHA%	\$WikiStyle['ALPHA']['apply'] = 'list'; \$WikiStyle['ALPHA']['list-style'] = 'upper-alpha';
special:	
open links in a new browser-window:	
%newwin%	\$WikiStyle['newwin']['target'] = '_blank';
Turns markup into a comment via display:none CSS	
%comment%	\$WikiStyle['comment']['display'] = 'none';

Author-Defined Wiki Styles

1. The first index of the array defines the style name (e.g. mynewstyle, projectentry etc)
2. the second index defines the attribute name (e.g. color, background-color, etc.)
3. the value set defines the attribute value (e.g. red, bold, #00ffcc, etc.)

Sample: If you want to define a (site-wide) style the same as the page style

```
%define=projectentry color:red%
use
```

```
$WikiStyle['projectentry']['color'] = 'red';
```

The \$WikiStyle['projectentry']['apply'] variable may be defined if the wikistyle concerns a particular tag. It may be 'item' (for li|dt), 'list' (for ul|ol|dl), 'div', 'pre', 'img', 'p' or the combining 'block' (for p|div|ul|ol|dl|li|dt|pre|h[1-6]).

Example:

```
$WikiStyle['top']['apply'] = 'item';
$WikiStyle['top']['class'] = 'top';
```

then a markup

```
* %top% An important list-item
```

will output

```
<li class="top">An important list-item</li>
```

Printer-Friendly Styles

If your custom-styles (in local/config.php) are getting very colorful it might be useful to disable them in print-view. This can be done easily by putting them into a condition.

```
if($action!="print") {  
    // your custom-styles  
}
```

Notes

To be done:

Questions:

I tried this but background didn't work, thou border and float worked? /Vincent 2008-04-08

```
$WikiStyle['vMenu']['background']='#ffffcc' ;  
$WikiStyle['vMenu']['float']='left' ;  
$WikiStyle['vMenu']['border']='1px dotted red' ;
```

Try using \$WikiStyle['vMenu']['background-color']='#ffffcc'; -- unlike background, background-color is defined in the \$WikiStyleCSS array, which is checked for valid properties.

Retrieved from <https://www-sop.inria.fr/mascotte/EULER/wiki/pmwiki.php/PmWiki/CustomWikiStyles>
Page last modified on February 14, 2009, at 03:36 PM