

From EULER Project

PmWiki: Initial Setup Tasks

Once you have PmWiki running on your site (see [Installation](#)), you can customize it for your particular needs.

Most PmWiki configuration is performed in files called *local/config.php* and *pub/css/local.css*. Some configuration is done on special pages in the [Site](#) and [SiteAdmin](#) groups, such as the [Site.SideBar](#) menu.

The local configuration file (*local/config.php*)

When you first install PmWiki, the *local/config.php* file does not exist. Copy the *sample-config.php* file (in the *docs/* directory) to *local/config.php* and use it as a starting point. You could create *local/config.php* from scratch, but *sample-config.php* is already populated with many of the options you might want to adjust.

Here is a simple *config.php* file:

```
<?php if (!defined('PmWiki')) exit();
$WikiTitle = "My New Wiki";
$PageLogoUrl = "http://example.com/mylogo.gif";

$DefaultPasswords['admin'] = crypt('onesecret');

$EnableUpload = 1;
$DefaultPasswords['upload'] = crypt('secrettwo');

putenv("TZ=EST5EDT");
$TimeFmt = '%B %d, %Y, at %I:%M %p EST';
```

Note that *config.php* begins with `<?php`. The PHP end tag `?>` is optional, and can be left off to improve compatibility with some operating systems. Be sure there aren't any blank lines or spaces before the `<?php` or after any closing `?>`, or else you may get strange PHP error messages at the beginning of your wiki pages.

The *config.php* file above sets the value of PHP variables used by PmWiki:

- The `$WikiTitle` variable gives the name of your site as it will appear in a user's browser title bar.
- The `$PageLogoUrl` variable specifies the URL of the icon image that will appear in the upper-left corner of each wiki page.
- The `$DefaultPasswords['admin']` sets an administrative password.
- Setting `$EnableUpload` to "1" enables Uploads ("Attached files").
`$DefaultPasswords['upload']` sets an upload password.
- The TZ environment variable defines a particular time zone (see [Cookbook:ChangeTimeFormat](#)).
- The `$TimeFmt` variable defines the appearance of time strings and (along with TZ) localizes the wiki to a specific time zone (see [Cookbook:ChangeTimeFormat](#)).

By setting these (and other) variables in *local/config.php*, you can change the look and feel of PmWiki from its default, sometimes substantially so. See [PmWiki.Variables](#) for a list of variables that PmWiki uses, and see [PmWiki:PmWikiUsers](#) for examples of sites that use PmWiki in customized ways.

Other common setup tasks

The following variables are often requested when preparing a new wiki

- Author required when editing a page `$EnablePostAuthorRequired = 1;`
- Set the `$DefaultGroup`

These common Cookbook recipes are also often installed immediately

- CleanUrls - Remove the `?n=Group.Page` arguments from the end of URLs

If you prepare an international wiki, potentially with characters in different alphabets (Cyrillic, Greek, Chinese) or many diacritical symbols (Czech + French), please look at PmWiki.UTF-8 and Cookbook:UTF-8.

Security

Review and set up any security required.

Setting an administrative password

The pages in the Site group (except the Site.SideBar) are locked by default. In order to edit pages in this group you need to create a site-wide admin password in *local/config.php*. To set the site-wide admin password to "mysecret", change the line to the following:

```
$DefaultPasswords['admin'] = crypt('mysecret');
```

You must use the `crypt()` function, but set the password to a value with meaning for you. See PasswordsAdmin for details about making the password more secure.

Don't modify or rename *pmwiki.php*

PmWiki has been designed so that all customizations can be made without changing the distribution files -- one of its design goals is to provide seamless upgrades. PmWiki never writes to files in the *local/* or *cookbook/* directories, so placing your customizations here makes it easier to track the changes and upgrade PmWiki without losing the changes.

When changing the configuration of your site, always change the *local/config.php* file or add files to the *cookbook/* or *pub* directories. Do not change *pmwiki.php* or the files in the *scripts/* directory because the files are supposed to be overwritten upon upgrading.

You shouldn't rename *pmwiki.php* either. If you rename the file it will not be overwritten during an upgrade of the software and there will be a version mismatch. Many administrators add an *index.php* "wrapper script" in the *pmwiki* directory that contains the following single line:

```
<?php include('pmwiki.php');
```

Just make an text-file. Paste `<?php include('pmwiki.php');` into it. Save the file as *index.php* Send it via FTP to the same directory as *pmwiki.php* is located.

Other organisation

Upload directories

By default Pmwiki uses an upload directory for each group (see [Uploads administration](#). Deciding on accepting the default, or choosing an alternative (eg one directory for the entire wiki, or one directory per page) is best done when setting up your wiki.

Page store directories

By default Pmwiki uses a single page store directory (wiki.d). Deciding on accepting the default (recommended), or choosing the alternative (one directory per group) is best done when setting up your wiki.
[\[1\]](#)

Other customization

After setting up *local/config.php* file, you may wish to make other [local customizations](#). See the [PmWiki Cookbook](#) for a large number of customizations that have been contributed. And don't fear Cookbook recipes - they're well prepared, so that most of them require only to download a single file, add a one-line include command to config.php, and *voilà!* - they're working!

If you (or others sharing your server) want to maintain more than one wiki on the same server, see [Wiki Farms](#).

Now what?

Don't forget to join a [PmWiki mailing list](#), where you can email other [wiki administrators](#) for help on customizing PmWiki and participate in discussions about PmWiki improvements. Once you have your site operational, be sure to add it to [PmWiki:PmWikiUsers](#) so others will know about it!

Retrieved from <https://www-sop.inria.fr/mascotte/EULER/wiki/pmwiki.php/PmWiki/InitialSetupTasks>
Page last modified on July 07, 2009, at 10:07 PM