

## From EULER Project

# PmWiki: Page List Templates

## Default page list templates

PmWiki's default templates for page lists are in Site.PageListTemplates, which is replaced during upgrades. These default templates can be supplemented or overridden with custom templates stored in other locations.

If the page name is not specified as part of the template name, PmWiki's default configuration looks for templates in the following locations in the following order

1. the current page
2. Site.LocalTemplates?,
3. Site.PageListTemplates

Administrators can change those locations by using the \$FPLTemplatePageFmt variable.

If the template is on the current page, the current page must be saved for changes involving the template to show up (*preview alone will not work*).

## **Custom page list templates**

Custom templates are used in the same way as default templates: by referencing the desired format with the `fmt=#anchor` option. There are several ways to indicate which template to use:

- `fmt=#custom` uses the `#custom` section from the current page, Site.LocalTemplates?, or Site.PageListTemplates, (sections are denoted by `[ [#custom] ]` anchors).
- `fmt=MyTemplatePage#custom` uses a custom format from page `MyTemplatePage` from its `#custom` section.
- `fmt=MyTemplatePage` uses a custom format from the entire page `MyTemplatePage`.
- `fmt=custom` uses custom format which is defined in a cookbook script as *custom*.

See Cookbook:PagelistTemplateSamples for examples of custom pagelist formats.

## **Creating page list templates**

A pagelist template contains standard pmwiki markup. When creating pagelist output, pmwiki iterates over each page returned from the pagelist and will include the pagelist template markup once for every page in the list.

## **Special references**

During the page list iteration pmwiki sets 3 special page references: `=`, `<` and `>`. These special page references are updated on each pagelist iteration and can be used with the page variables syntax, such as `={$variable}`, to define a pagelist template which will format the pagelist output. The meaning of the special references are:

<pre>= current so page   {=\$Title}</pre>	displays the title of the current page in the iteration
<pre>&lt; previous so page   {&lt;\$Group}</pre>	displays the group of the previous page in the iteration
<pre>&gt; next so page   {&gt;\$Name}</pre>	displays the name of the next page in the iteration

The > and < references are most useful to help structure pagelist output before and after the actual pagelist.  
 Some common tests used to structure pagelist output are:

(:template first:)	<del>(:if equal (&lt;\$Group):)</del>	Iteration is at the beginning of list
(:template last:)	<del>(:if equal (&gt;\$Group):)</del>	Iteration is at the end of list
(:template first {\$Group}:)	<del>(:if ! equal (-\$Group)</del> <del>(&lt;\$Group):)</del>	Iteration is at the first item in a group
(:template last {\$Group}:)	<del>(:if ! equal (-\$Group)</del> <del>(&gt;\$Group):)</del>	Iteration is at the last item in a group
(:template defaults:)		Default options to be used in the pagelist command
(:template each:)		Signifies the repeated part

*Note:* the markup in column 2 is deprecated

## Page list template special markup

Pagelist templates may have special

- (:template first ...:)
  - (:template last ...:)
- sections to specify output for the first or last page in the list or a group.

There's also a

- (:template defaults ...:)

to allow a template to specify default options, and

- (:template each ...:)

to signify the repeated part.

These allow Pagelist templates to be easily separated into "sections" that are included or not included in the output based on a variety of conditions. These are intended to be improved versions of the (:if ...) conditions that have traditionally been used to control pagelist output (however, the (:if:) conditions still work as before).

## First, Each, Last

The simplest versions of the directives are:

```
(:template first:)      # markup to display only for first page in list
(:template each:)       # markup to display for each page in list
(:template last:)       # markup to display only on last page in list
```

So, a pagelist template can specify:

```
(:template first:)
Pages in the list:
(:template each:)
* [{=$FullName}])
(:template last:)
Displayed {$$PageCount} pages.
```

In addition, the "first" and "last" options can have control break arguments that identify markup to be displayed on the first or last page within a particular control section. For example, to specify markup to be displayed upon reaching the first or last page of a group, one can use

```
(:template first {=$Group}:)
(:template last {=$Group}:)
```

Thus, instead of writing control breaks using directives, as in

```
(:if ! equal {<$Group} {=$Group}:)
Group: {=$Group}
(:ifend:)
* [{=$FullName}])
```

one can now write

```
(:template first {=$Group}:)
Group: {=$Group}
(:template each:)
* [{=$FullName}])
```

## Default options

In addition, a template may specify default options to be used in the pagelist command. For example, a pagelist template to display a list of pages by their titles (and sorted by title) might use:

```
[ [#bytitle]]
```

```
(:template default order=title:)
* [[{=$FullName}|+]]
[[#bytitleend]]
```

Then an author could write (:pagelist fmt=#bytitle:) and the pages would automatically be sorted by title without having to specify an additional "order=title" option to the (:pagelist:) directive.

To specify multiple parameters to an option enclose the parameters in double quotes, eg to sort by a page text variable and then the page name

```
(:template defaults order="$:Database, name" :)
```

## Examples

```
(:template defaults ... :)
    default options for pagelists using this template
(:template each:)
    markup for each page in the pagelist
(:template first:)
    markup output only for the first page in the pagelist
(:template last:)
    markup output only for the last page in the pagelist
(:template first {=$Group}:)
    markup output only for a page where the value of {=$Group} has just changed
(:template last {=$Group}:)
    markup output only for a page where the value of {=$Group} will change with the next page
```

So, we have:

```
[[#template]]
(:template defaults order=name:)
(:template first:)
Pages ordered by group
(:template first {=$Group}:)

Pages in group [[{=$Group}/]]
(:template each:)
* [[{=$FullName}]]
(:template last {=$Group}:)
{=$Group} contains {$$GroupPageCount} pages.
(:template last:)
{$$PageCount} pages total.
[[#templateend]]
```

## Page list template additional page variables

Additional Page Variables that are only available during pagelist are:

{\$\$PageCount}	The current page count of this iteration
{\$\$GroupCount}	The current group count of this iteration
{\$\$GroupPageCount}	The current page count within the current group of this iteration
{\$\$option}	The argument option values from (:pagelist:)

Use of {\$\$option}: For example {\$\$trail} returns the page name entered in the trail= option of the pagelist directive. You can make up custom "options" with no other purpose than being displayed in the pagelist.

## Redirect

To enable searches that return only one page to automatically redirect to that page add the following to a pagelist template where the "jump to a page" functionality is desired:

```
(:template last:)
(:if equal {$$PageCount} 1:) (:redirect {=$FullName}:) (:ifend:)
```

## Closure of markup

Any open tables, divs, or other structures inside of (:pagelist:) are, by default, automatically closed at the end of the pagelist command. In other words, (:pagelist:) acts like its own complete page, as opposed to generating markup that is then inserted into the enclosing page.

For example a table generated by the (:cell:) directive in the first (:pagelist:) command is automatically closed at the end of the pagelist. The (:cell:) in the second (:pagelist:) command then starts a new table.

Note that the (:table:) directive doesn't actually start a new table, it's the (:cell:) or (:cellnr:) directive that does it. All that the (:table:) directive does is set attributes for any tables that follow.

## Usage

It is advisable to not modify the page [Site.PageListTemplates](#) directly so that you will still benefit from upgrades. Instead, modify your [Site.LocalTemplates?](#) page (which is not part of the PmWiki distribution). [Cookbook:PagelistTemplateSamples](#) has many examples of custom pagelist formats.

## Other recipes

In addition, the [Cookbook](#) has other recipes for special `fmt=` options, including [`fmt=dict index`](#) (alphabetical index) and [`fmt=forum`](#) (forum postings).

Retrieved from <https://www-sop.inria.fr/mascotte/EULER/wiki/pmwiki.php/PmWiki/PageListTemplates>  
Page last modified on March 28, 2009, at 08:44 PM