

From EULER Project

PmWiki: Security Variables

\$AuthUserFunctions

(Present only when the in-built AuthUser username/password functionality is used). An array of different authentication mechanisms to be used for user authentication. Array keys are a tag for the mechanism; values are a function callback that will be called with the properties \$pagename, \$id, \$password, and \$pwlist. Oh... could someone else make this make sense, please?!

\$DefaultPasswords

Specifies default passwords for user admin or actions (edit, read, upload). See PasswordsAdmin#settingsitewidepasswords.

\$EnablePostAttrClearSession

A switch to control whether or not changing a page's attributes causes any existing passwords to be forgotten. The default is that changing attributes forgets any passwords entered; this can be changed by setting \$EnablePostAttrClearSession to zero.

\$EnableSessionPasswords

Control whether passwords are saved as part of the session. If set to zero, then session passwords are never saved (although any AuthUser authentications are still remembered).

\$SessionEncode

Function to use to encode sensitive information in sessions. Set this to NULL if you want to not use any encoding. (See also \$SessionDecode below.)

\$SessionDecode

Function to reverse the decoding given by \$SessionEncode above. Set this to NULL if sensitive session values are not encoded.

\$HandleAuth

This sets the required authentication Level that is necessary to perform an action. When using the following example in your `config.php` you need to be authenticated as editor in order to view the page history:

```
$HandleAuth['diff'] = 'edit';
```

\$PageAttributes

Set the string shown on the attributes page when entering a password for an action.

\$AuthLDAPBindDN

For sites using AuthUser with LDAP authentication, this specifies the distinguished name (DN) to be used to bind to the LDAP server to check identity.

\$AuthLDAPBindPassword

For AuthUser with LDAP authentication, this specifies the password used for binding (in conjunction with \$AuthLDAPBindDN above).

\$EnablePublishAttr

Adds a new "publish" authorization level to distinguish editing of drafts from publishing - See \$EnableDrafts.

See also:

- Security
- \$EnablePageListProtect

Retrieved from <https://www-sop.inria.fr/mascotte/EULER/wiki/pmwiki.php/PmWiki/SecurityVariables>

