

From EULER Project

PmWiki: Wiki Styles

Contents

- [Basics](#)
- [Scopes](#)
- [Attributes](#)
- [Enabling Styles](#)
- [Custom style shortcuts](#)
- [Predefined Style Shortcuts](#)
- [Examples](#)
- [Known Issues](#)
- [See Also](#)

Wiki style basics

Wiki styles allow authors to modify the color and other styling attributes of a page's contents. A wikistyle is written using percent-signs, as in %red% or %bgcolor=lightblue%.

Text color and font

The most basic use of wiki styles is to change text attributes such as color, background color, and font. PmWiki defines several wikistyles for changing the text color to %black%, %white%, %red%, %yellow%, %blue%, %gray%, %silver%, %maroon%, %green%, %navy%, and %purple%.

The basket contains %red% apples, %blue% The basket contains apples, blueberries, eggplant, limes, blueberries, %purple% eggplant, %green% and more. limes, %% and more.

For colors other than the predefined colors, use the %color=...% wikistyle. (Note: RGB colors (#rrggbb) should always be specified with lowercase letters to avoid WikiWord conflicts.)

I'd like to have some %color=#ff7f00% I'd like to have some tangerines, too!
tangerines%%, too!

To change the background color, use %bgcolor=...% as a wikistyle:

This sentence contains %bgcolor=green% This sentence contains yellow text on a green background.
yellow% yellow text on a green
background.

See Wiki Style Colors for more color help.

Text justification

Styles are used to control the text justification

%center% This text is centered. This text is centered.

%right% Right justified.

Right justified.

and to create floating text:

```
%rfloat% This text floats to the right This text floats to the right
%rframe% floats to the right with a frame
Lorem ipsum dolor sit amet,
consectetuer sadipscing elitr
Lorem ipsum dolor sit amet, consectetuer sadipscing elitr
```

Scopes

Wikistyles can also specify a *scope*; with no scope, the style is applied to any text that follows up to the next wikistyle specification or the end of the paragraph, whichever comes first. The **apply=** attribute and its shortcuts allow to change the scope as follows:

apply attribute	shortcut	style applies to...
%apply=img ...%	-	any image that <i>follows</i>
%apply=p ...%	%p ...%	the current paragraph
%apply=pre ...%	-	the current preformatted text
%apply=list ...%	%list ...%	the current list
%apply=item ...%	%item ...%	the current list item
%apply=div ...%	-	the current div
%apply=block ...%	%block ...%	to the current block, whether it's a paragraph, list, list item, heading, or division.

thus **%p color=blue%** is the same as **%apply=p color=blue%**, and **%list ROMAN%** is the same as **%apply=list list-style=upper-roman%**.

Some predefined style shortcuts also make use of apply, thus **%right%** is a shortcut for **%text-align=right apply=block%**.

Example: Apply a style to a paragraph:

```
%p bgcolor=#ffeeee% The wikistyle specification at the beginning of this
line applies to the entire paragraph, even if there are %blue% other
wikistyle specifications %% in the middle of the paragraph.
```

The wikistyle specification at the beginning of this line applies to the entire paragraph, even if there are other wikistyle specifications in the middle of the paragraph.

Wiki styles can also be applied to tables and table directives:

```
||class="green"
style="font-style:italic; border:1px
solid blue; background-color:#ffffcc"
||Everything after the above line is
styled with green italic text, ||
|| ||
||This includes ||
||    preformatted text ||
```

Everything after the above line is styled with green italic text,
 This includes
 * lists
 preformatted text

EULER Project | PmWiki / Wiki Styles

```
||* lists ||                                -> indented items
||-> indented items ||
(:table class="green"
style="font-style:italic; border:1px
solid blue; background-color:#ffffcc":)
(:cellnr:)
Everything after the above line is      This includes
styled with green italic text,
This includes                                preformatted text
    preformatted text
* lists
-> indented items
(:tableend:)                                indented items
```

The **>>style<<** block can be used to apply a wikistyle to a large block of items. The style is applied until the next **>><<** is encountered.

```
>>blue font-style:italic           Everything after the above line is styled with blue italic text,
bgcolor=#ffffcc<<
Everything after the above line is      This includes
styled with blue italic text,
This includes                                preformatted text
    preformatted text
* lists
-> indented items
>><<                                indented items
```

The **(:div style:)** works in *almost* the same way as **>>style<<**, but the style information is encapsulated in a **style=""** attribute and nested div blocks are possible.

```
(:div class="green"
style="font-style:italic; border:1px
solid blue; background-color:#ffffcc":)
Everything after the above line is      This includes
styled with green italic text,
This includes                                preformatted text
    preformatted text
* lists
-> indented items
(:divend:)                                indented items
    (:div1 style="font-style:italic; outer style
background-color:#ffffcc":)
    outer style
    (:div2 style="color:red;
background-color:lightblue":)
    nested style
    (:div2end:)
    again outer style
    (:divlend:)
```

Caveat: An applied wikistyle will only take effect if it's on the line that starts the thing it's supposed to modify. In other words, a wikistyle in the third markup line of a paragraph can't change the attributes of the paragraph:

```
after the first line of the paragraph, after the first line of the paragraph, we try to change color.
we try to %apply=p color=blue% change   This doesn't work because the style comes
```

color.
 This does't work because the style
 comes
 However, this %p color=red% paragraph However, this paragraph *will* be in red because its block style
 ''will'' be in red because its block does occur in the first line of its text.
 style does
 occur in the first line of its text.
 * Here's a list item
 * %list red% Oops, too late to affect
 the list!
 • Here's a list item
 • Oops, too late to affect
 the list!

Wikistyle attributes

The style attributes recognized within a wikistyle specification are:

----- CSS -----		--HTML--
color	bgcolor	class
background-color	margin	id
text-align	padding	hspace
text-decoration	border	vspace
font-size	float	target
font-family	list-style	rel
font-weight	width*	accesskey
font-style	height*	value
display		

Special: define, apply

The attributes in the first two columns correspond to the *cascading style sheet(approve sites)* (CSS) properties of the same name. The attributes in the last column apply only to specific items:

- **class=** and **id=** assign a CSS class or identifier to an HTML element
- **target=name** opens links that follow in a browser window called "name"
- **rel=name** in a link identifies the relationship of a target page
- **accesskey=x** uses 'x' as a shortcut key for the link that follows
- **value=9** sets the number of the current ordered list item

* The width and height attributes have asterisks because they are handled specially for tags. If used by themselves (i.e., without anything providing an "apply=" parameter to the wikistyle), then they set the 'width=' and 'height=' attributes of any tags that follow. Otherwise, they set the 'width:' and 'height:' properties of the element being styled.

Enabling Styles

Styles not listed above can be enabled by a PmWiki Administrator by modifying the local/config.php file. For instance to enable the "line-height" style attribute add the line

```
$WikiStyleCSS[] = 'line-height';
```

to the local/config.php file.

Custom style shortcuts

The **define=** attribute can be used to assign a shorthand name to any wikistyle specification. This shorthand name can then be reused in later wikistyle specifications.

```
%define=box block bgcolor="#dddddff some sort of text
border="2px dotted blue"%

%box% [@some sort of text@] some sort of text

%box font-weight=bold color=green%
[@some sort of text@]
```

Tip: It's often a good idea to put common style definitions into [Group Header](#) pages so that they can be shared among multiple pages in a group. Or, the [wiki administrator](#) can predefine styles site-wide as a [local customization](#) (see [Custom Wiki Styles](#)).

Tip: Use custom style definitions to associate meanings with text instead of just colors. For example, if warnings are to be displayed as green text, set `%define=warn green%` and then use `%warn%` instead of `%green%` in the document. Then, if you later decide that warnings should be styled differently, it's much easier to change the (one) definition than many occurrences of `%green%` in the text.

Tip: Any undefined WikiStyle is automatically treated as a request for a class, thus `%pre%` is the same as saying `%class=pre%`.

Predefined style shortcuts

PmWiki defines a number of style shortcuts.

- Text colors: black, white, red, yellow, blue, gray, silver, maroon, green, navy, purple (shortcut for `%color=...`)
- Justification: `%center%` and `%right%`
- Images and boxes
 - ◆ Floating left or right: `%rfloat%` and `%lfloat%`
 - ◆ Framed items: `%frame%`, `%rframe%`, and `%lframe%`
 - ◆ Thumbnail sizing: `%thumb%`
- Open link in new window: `%newwin%` (shortcut for `%target=_blank%`)
- Comments: `%comment%` (shortcut for `%display=none%`)
- Ordered lists: `%decimal%`, `%roman%`, `%ROMAN%`, `%alpha%`, `%ALPHA%` (see also [Cookbook:OutlineLists](#))

Examples

[Wiki Style Examples](#) contains a number of examples of ways to use wikistyles in pages.

Known Issues

- Percents in style definitions (like: `%block width=50%`) require the use of "pct" instead of "%".
- If you specify multiple values for an attribute, like `border="2px solid blue"` make sure you place the values in quotes.
- Be sure to use lowercase letters for red-green-blue hex colors, `%color=#aa3333%` will work, `%color=#AA3333%` may not.

See Also

- [Custom Wiki Styles](#) Predefined PmWiki styles & adding custom wiki styles
- [PmWiki:List Styles](#)

Retrieved from <https://www-sop.inria.fr/mascotte/EULER/wiki/pmwiki.php/PmWiki/WikiStyles>
Page last modified on July 14, 2009, at 01:34 AM