



How to Agree to Disagree: Managing Conceptual Diversity using Standpoint Logic

Lucía Gómez Álvarez

Inria, Université Grenoble Alpes

Contents


- Motivation for the framework
- First Order Standpoint Logic
- Complexity Landscape
 - The Standpoint SHIQ

Motivation

Multiperspective Reasoning

Motivation: Knowledge Integration


Motivation: Knowledge Integration



Diverse Knowledge Sources

Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available



Diverse Knowledge Sources

Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available



Diverse Knowledge Sources

Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available



Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available




Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available




Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available




Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available




Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available




Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available



Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available
Knowledge sources embed the perspectives of their creators!




Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available
Knowledge sources embed the perspectives of their creators!

Challenge: Integration

Private Lab



Tumor(t)
patientPart(p, t)

Process \sqcap Tissue $\sqsubseteq \perp$

Tumor \sqsubseteq Process

\exists hasProcess.Tumor \sqsubseteq HighRisk

Tumor \sqsubseteq Tissue

HighRisk(p)




Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available
Knowledge sources embed the perspectives of their creators!

Challenge: Integration

Private Lab



Tumor(t)
patientPart(p, t)

Knowledge Fusion

Process \sqcap Tissue $\sqsubseteq \perp$

Tumor \sqsubseteq Process

$\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}$

Tumor \sqsubseteq Tissue

HighRisk(p)




Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available
Knowledge sources embed the perspectives of their creators!

Challenge: Integration

$\text{Tumor}(t)$

Private Lab



$\text{Tumor}(t)$
 $\text{patientPart}(p, t)$

Knowledge Fusion

$\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp$

$\text{Tumor} \sqsubseteq \text{Process}$

$\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}$

$\text{Tumor} \sqsubseteq \text{Tissue}$

$\text{HighRisk}(p)$




Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available
Knowledge sources embed the perspectives of their creators!

Challenge: Integration

$\text{Tumor}(t)$
↙
 $\text{Process}(t)$

Private Lab



$\text{Tumor}(t)$
 $\text{patientPart}(p, t)$

Knowledge Fusion

$\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp$

$\text{Tumor} \sqsubseteq \text{Process}$

$\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}$

$\text{Tumor} \sqsubseteq \text{Tissue}$


$\text{HighRisk}(p)$




Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available
Knowledge sources embed the perspectives of their creators!

Challenge: Integration



Private Lab



Tumor(t)
patientPart(p, t)

Knowledge Fusion

$\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp$

$\text{Tumor} \sqsubseteq \text{Process}$

$\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}$

$\text{Tumor} \sqsubseteq \text{Tissue}$


HighRisk(p)




Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available
Knowledge sources embed the perspectives of their creators!

Challenge: Integration



Private Lab



Tumor(t)
patientPart(p, t)

Knowledge Fusion

$\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp$

$\text{Tumor} \sqsubseteq \text{Process}$

$\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}$

$\text{Tumor} \sqsubseteq \text{Tissue}$


HighRisk(p)




Motivation: Knowledge Integration

Non-trivial combinations of the huge diversity of knowledge sources available
Knowledge sources embed the perspectives of their creators!

Challenge: Integration



Private Lab



Tumor(t)
patientPart(p, t)

Knowledge Fusion

$\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp$

$\text{Tumor} \sqsubseteq \text{Process}$

$\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}$

$\text{Tumor} \sqsubseteq \text{Tissue}$

HighRisk(p)



Multiperspective Ontology Management

Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

➡ **Multimodal logic** characterised by **simplified Kripke semantics**

Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

- ➡ **Multimodal logic** characterised by **simplified Kripke semantics**
- ➡ Knowledge relative to “**points of view**” (standpoints)

Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

- ➔ **Multimodal logic** characterised by **simplified Kripke semantics**
- ➔ Knowledge relative to “**points of view**” (standpoints)

Process \sqcap Tissue $\sqsubseteq \perp$

Tumor \sqsubseteq Tissue

Tumor \sqsubseteq Process

$\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}$

Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

- ➔ **Multimodal logic** characterised by **simplified Kripke semantics**
- ➔ Knowledge relative to “**points of view**” (standpoints)

$$\Box_S [\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp]$$

$$\Diamond_L [\text{Tumor}] \sqsubseteq \Box_L [\text{Tissue}]$$

$$\Diamond_H [\text{Tumor}] \sqsubseteq \Box_H [\text{Process}]$$

$$\Box_H [\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}]$$

CONSISTENT

 \Box_e Unequivocal to e

 \Diamond_e Conceivable to e

Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

- ➔ **Multimodal logic** characterised by **simplified Kripke semantics**
- ➔ Knowledge relative to “**points of view**” (standpoints)

$$\Box_S [\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp]$$

$$\Diamond_L [\text{Tumor}] \sqsubseteq \Box_L [\text{Tissue}]$$

$$\Diamond_H [\text{Tumor}] \sqsubseteq \Box_H [\text{Process}]$$

$$\Box_H [\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}]$$

$$(L \cup H) \leq S$$

(L and H inherit the axioms of S)

CONSISTENT

\Box_e Unequivocal to e

\Diamond_e Conceivable to e

Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

- ➔ **Multimodal logic** characterised by **simplified Kripke semantics**
- ➔ Knowledge relative to “**points of view**” (standpoints)

$$\Box_S [\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp]$$

$$\Diamond_L [\text{Tumor}] \sqsubseteq \Box_L [\text{Tissue}]$$

$$\Diamond_H [\text{Tumor}] \sqsubseteq \Box_H [\text{Process}]$$

$$\Box_H [\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}]$$

$$(L \cup H) \leq S \quad (L \text{ and } H \text{ inherit the axioms of } S)$$

$$\Diamond_L [\exists \text{patientPart} . \text{Tumor}] \sqsubseteq \Box_H [\exists \text{hasProcess} . \text{Tumor}]$$

CONSISTENT

 \Box_e Unequivocal to e

 \Diamond_e Conceivable to e

Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

- ➔ **Multimodal logic** characterised by **simplified Kripke semantics**
- ➔ Knowledge relative to “**points of view**” (standpoints)

$$\Box_S [\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp]$$

$$\Diamond_L [\text{Tumor}] \sqsubseteq \Box_L [\text{Tissue}]$$

$$\Diamond_H [\text{Tumor}] \sqsubseteq \Box_H [\text{Process}]$$

$$\Box_H [\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}]$$


$$(L \cup H) \leq S \quad (L \text{ and } H \text{ inherit the axioms of } S)$$

$$\Diamond_L [\exists \text{patientPart} . \text{Tumor}] \sqsubseteq \Box_H [\exists \text{hasProcess} . \text{Tumor}]$$

CONSISTENT

\Box_e Unequivocal to e

\Diamond_e Conceivable to e



Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

- ➔ **Multimodal logic** characterised by **simplified Kripke semantics**
- ➔ Knowledge relative to “**points of view**” (standpoints)

$$\Box_S [\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp]$$

$$\Diamond_L [\text{Tumor}] \sqsubseteq \Box_L [\text{Tissue}]$$

$$\Diamond_H [\text{Tumor}] \sqsubseteq \Box_H [\text{Process}]$$

$$\Box_H [\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}]$$

$$(L \cup H) \leq S$$


(L and H inherit the axioms of S)

$$\Diamond_L [\exists \text{patientPart} . \text{Tumor}] \sqsubseteq \Box_H [\exists \text{hasProcess} . \text{Tumor}]$$

CONSISTENT

\Box_e Unequivocal to e

\Diamond_e Conceivable to e



Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

- ➔ **Multimodal logic** characterised by **simplified Kripke semantics**
- ➔ Knowledge relative to “**points of view**” (standpoints)

$$\Box_S [\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp]$$

$$\Diamond_L [\text{Tumor}] \sqsubseteq \Box_L [\text{Tissue}]$$

$$\Diamond_H [\text{Tumor}] \sqsubseteq \Box_H [\text{Process}]$$

$$\Box_H [\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}]$$


$$(L \cup H) \leq S \quad (L \text{ and } H \text{ inherit the axioms of } S)$$

$$\Diamond_L [\exists \text{patientPart} . \text{Tumor}] \sqsubseteq \Box_H [\exists \text{hasProcess} . \text{Tumor}]$$

CONSISTENT

\Box_e Unequivocal to e

\Diamond_e Conceivable to e



Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

- ➔ **Multimodal logic** characterised by **simplified Kripke semantics**
- ➔ Knowledge relative to “**points of view**” (standpoints)

$$\Box_S [\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp]$$

$$\Diamond_L [\text{Tumor}] \sqsubseteq \Box_L [\text{Tissue}]$$

$$\Diamond_H [\text{Tumor}] \sqsubseteq \Box_H [\text{Process}]$$

$$\Box_H [\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}]$$

$$(L \cup H) \leq S$$


(L and H inherit the axioms of S)

$$\Diamond_L [\exists \text{patientPart} . \text{Tumor}] \sqsubseteq \Box_H [\exists \text{hasProcess} . \text{Tumor}]$$

CONSISTENT

\Box_e Unequivocal to e

\Diamond_e Conceivable to e



Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

- ➔ **Multimodal logic** characterised by **simplified Kripke semantics**
- ➔ Knowledge relative to “**points of view**” (standpoints)

$$\Box_S [\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp]$$

$$\Diamond_L [\text{Tumor}] \sqsubseteq \Box_L [\text{Tissue}]$$

$$\Diamond_H [\text{Tumor}] \sqsubseteq \Box_H [\text{Process}]$$

$$\Box_H [\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}]$$

$$(L \cup H) \leq S$$


(L and H inherit the axioms of S)

$$\Diamond_L [\exists \text{patientPart} . \text{Tumor}] \sqsubseteq \Box_H [\exists \text{hasProcess} . \text{Tumor}]$$

CONSISTENT

\Box_e Unequivocal to e

\Diamond_e Conceivable to e



Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

- ➔ **Multimodal logic** characterised by **simplified Kripke semantics**
- ➔ Knowledge relative to “**points of view**” (standpoints)

$$\Box_S [\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp]$$

$$\Diamond_L [\text{Tumor}] \sqsubseteq \Box_L [\text{Tissue}]$$

$$\Diamond_H [\text{Tumor}] \sqsubseteq \Box_H [\text{Process}]$$

$$\Box_H [\exists \text{hasProcess} . \text{Tumor}] \sqsubseteq \text{HighRisk}$$

$$(L \cup H) \leq S$$


(L and H inherit the axioms of S)

$$\Diamond_L [\exists \text{patientPart} . \text{Tumor}] \sqsubseteq \Box_H [\exists \text{hasProcess} . \text{Tumor}]$$

CONSISTENT

\Box_e Unequivocal to e

\Diamond_e Conceivable to e



Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them

Standpoint Logic

- ➔ **Multimodal logic** characterised by **simplified Kripke semantics**
- ➔ Knowledge relative to “**points of view**” (standpoints)

$$\Box_S [\text{Process} \sqcap \text{Tissue} \sqsubseteq \perp]$$

$$\Diamond_L [\text{Tumor}] \sqsubseteq \Box_L [\text{Tissue}]$$

$$\Diamond_H [\text{Tumor}] \sqsubseteq \Box_H [\text{Process}]$$

$$\Box_H [\exists \text{hasProcess} . \text{Tumor} \sqsubseteq \text{HighRisk}]$$

$$(L \cup H) \leq S$$


(L and H inherit the axioms of S)

$$\Diamond_L [\exists \text{patientPart} . \text{Tumor}] \sqsubseteq \Box_H [\exists \text{hasProcess} . \text{Tumor}]$$

CONSISTENT

\Box_e Unequivocal to e

\Diamond_e Conceivable to e




Multiperspective Ontology Management

Challenge: combining diverse (potentially conflicting) sources without weakening them


Standpoint Logic

- ➡ **Multimodal logic** characterised by **simplified Kripke semantics**
- ➡ Knowledge relative to “**points of view**” (standpoints)

Standpoint FOL – Syntax and Semantics



First-Order Standpoint Logic: Syntax



First-Order Standpoint Logic: Syntax

Syntax of \mathcal{S}

First-Order Standpoint Logic: Syntax

Syntax of \mathcal{S}

Signature $\langle \mathcal{P}, \mathcal{C}, \mathcal{S} \rangle$ of predicates, constants and standpoints.

First-Order Standpoint Logic: Syntax

Syntax of \mathcal{S}

Signature $\langle \mathcal{P}, \mathcal{C}, \mathcal{S} \rangle$ of predicates, constants and standpoints.

The set of FOSL formulas is then given by

$$\phi, \psi ::= P(t_1, \dots, t_k) \mid \neg \phi \mid \phi \wedge \psi \mid \forall x \phi \mid \Box_e \phi$$

First-Order Standpoint Logic: Syntax

Syntax of \mathcal{S}

Signature $\langle \mathcal{P}, \mathcal{C}, \mathcal{S} \rangle$ of predicates, constants and standpoints.

The set of FOSL formulas is then given by

$$\phi, \psi ::= P(t_1, \dots, t_k) \mid \neg \phi \mid \phi \wedge \psi \mid \forall x \phi \mid \Box_e \phi$$

- $\Box_e \phi \longrightarrow$ “it is **unequivocal**, according to e , that ϕ ”

First-Order Standpoint Logic: Syntax

Syntax of \mathcal{S}

Signature $\langle \mathcal{P}, \mathcal{C}, \mathcal{S} \rangle$ of predicates, constants and standpoints.

The set of FOSL formulas is then given by

$$\phi, \psi ::= P(t_1, \dots, t_k) \mid \neg\phi \mid \phi \wedge \psi \mid \forall x\phi \mid \Box_e \phi$$

$$\Box_e \neg\phi \equiv \neg\Diamond_e \phi \text{ (dual)}$$

- $\Box_e \phi \longrightarrow$ “it is **unequivocal**, according to e , that ϕ ”
- $\Diamond_e \phi \longrightarrow$ “it is **conceivable**, according to e , that ϕ ”

First-Order Standpoint Logic: Syntax

Syntax of \mathcal{S}

Signature $\langle \mathcal{P}, \mathcal{C}, \mathcal{S} \rangle$ of predicates, constants and standpoints.

The set of FOSL formulas is then given by

$$\phi, \psi ::= P(t_1, \dots, t_k) \mid \neg \phi \mid \phi \wedge \psi \mid \forall x \phi \mid \Box_e \phi$$

$$\Box_e \neg \phi \equiv \neg \Diamond_e \phi \text{ (dual)}$$

The set of standpoint expressions is defined as follows:

$$e_1, e_2 ::= * \mid s \mid e_1 \cup e_2 \mid e_1 \cap e_2 \mid e_1 \setminus e_2$$

- $\Box_e \phi \longrightarrow$ “it is **unequivocal**, according to e , that ϕ ”
- $\Diamond_e \phi \longrightarrow$ “it is **conceivable**, according to e , that ϕ ”

First-Order Standpoint Logic: Syntax

Syntax of \mathcal{S}

Signature $\langle \mathcal{P}, \mathcal{C}, \mathcal{S} \rangle$ of predicates, constants and standpoints.

The set of FOSL formulas is then given by

$$\phi, \psi ::= P(t_1, \dots, t_k) \mid \neg \phi \mid \phi \wedge \psi \mid \forall x \phi \mid \Box_e \phi$$

$$\Box_e \neg \phi \equiv \neg \Diamond_e \phi \text{ (dual)}$$

The set of standpoint expressions is defined as follows:

$$e_1, e_2 ::= * \mid s \mid e_1 \cup e_2 \mid e_1 \cap e_2 \mid e_1 \setminus e_2$$

- $\Box_e \phi \longrightarrow$ “it is **unequivocal**, according to e , that ϕ ”
- $\Diamond_e \phi \longrightarrow$ “it is **conceivable**, according to e , that ϕ ”
- $\Box_{e \cup e'} \phi \longrightarrow$ “it is unequivocal, according to both e and e' , that ϕ ”

First-Order Standpoint Logic: Syntax

Syntax of \mathcal{S}

Signature $\langle \mathcal{P}, \mathcal{C}, \mathcal{S} \rangle$ of predicates, constants and standpoints.

The set of FOSL formulas is then given by

$$\phi, \psi ::= P(t_1, \dots, t_k) \mid \neg\phi \mid \phi \wedge \psi \mid \forall x\phi \mid \Box_e \phi$$

$$\Box_e \neg\phi \equiv \neg\Diamond_e \phi \text{ (dual)}$$

The set of standpoint expressions is defined as follows:

$$e_1, e_2 ::= * \mid s \mid e_1 \cup e_2 \mid e_1 \cap e_2 \mid e_1 \setminus e_2$$

- $\Box_e \phi \longrightarrow$ “it is **unequivocal**, according to e , that ϕ ”
- $\Diamond_e \phi \longrightarrow$ “it is **conceivable**, according to e , that ϕ ”
- $\Box_{e \cup e'} \phi \longrightarrow$ “it is unequivocal, according to both e and e' , that ϕ ”
- $\Box_{e \cap e'} \phi \longrightarrow$ “it is unequivocal, according to the fusion of e and e' , that ϕ ”

First-Order Standpoint Logic: Syntax

Syntax of \mathcal{S}

Signature $\langle \mathcal{P}, \mathcal{C}, \mathcal{S} \rangle$ of predicates, constants and standpoints.

The set of FOSL formulas is then given by

$$\phi, \psi ::= P(t_1, \dots, t_k) \mid \neg \phi \mid \phi \wedge \psi \mid \forall x \phi \mid \Box_e \phi$$

$$\Box_e \neg \phi \equiv \neg \Diamond_e \phi \text{ (dual)}$$

The set of standpoint expressions is defined as follows:

$$e_1, e_2 ::= * \mid s \mid e_1 \cup e_2 \mid e_1 \cap e_2 \mid e_1 \setminus e_2$$

+ (definable) sharpening statements: $e \leq e'$ denoting $\Box_{e \setminus e'} \mathbf{f}$

- $\Box_e \phi \longrightarrow$ “it is **unequivocal**, according to e , that ϕ ”
- $\Diamond_e \phi \longrightarrow$ “it is **conceivable**, according to e , that ϕ ”
- $\Box_{e \cup e'} \phi \longrightarrow$ “it is unequivocal, according to both e and e' , that ϕ ”
- $\Box_{e \cap e'} \phi \longrightarrow$ “it is unequivocal, according to the fusion of e and e' , that ϕ ”

First-Order Standpoint Logic: Syntax

Syntax of \mathcal{S}

Signature $\langle \mathcal{P}, \mathcal{C}, \mathcal{S} \rangle$ of predicates, constants and standpoints.

The set of FOSL formulas is then given by

$$\phi, \psi ::= P(t_1, \dots, t_k) \mid \neg \phi \mid \phi \wedge \psi \mid \forall x \phi \mid \Box_e \phi$$

$$\Box_e \neg \phi \equiv \neg \Diamond_e \phi \text{ (dual)}$$


The set of standpoint expressions is defined as follows:

$$e_1, e_2 ::= * \mid s \mid e_1 \cup e_2 \mid e_1 \cap e_2 \mid e_1 \setminus e_2$$

+ (definable) sharpening statements: $e \leq e'$ denoting $\Box_{e \setminus e'} \mathbf{f}$

- $\Box_e \phi \longrightarrow$ “it is **unequivocal**, according to e , that ϕ ”
- $\Diamond_e \phi \longrightarrow$ “it is **conceivable**, according to e , that ϕ ”
- $\Box_{e \cup e'} \phi \longrightarrow$ “it is unequivocal, according to both e and e' , that ϕ ”
- $\Box_{e \cap e'} \phi \longrightarrow$ “it is unequivocal, according to the fusion of e and e' , that ϕ ”
- $e \leq e' \longrightarrow$ “ e inherits or **extends** e' ”

First-Order Standpoint Logic: Semantics



First-Order Standpoint Logic: Semantics

Semantics of \mathcal{S}

Relational semantics:

First-Order Standpoint Logic: Semantics

Semantics of \mathcal{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

First-Order Standpoint Logic: Semantics

Semantics of \mathcal{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
- $\Pi = \{\pi_1, \pi_2, \pi_3\}$

ϵ_1	ϵ_2	Δ / Π
		π_1
		π_2
		π_3

First-Order Standpoint Logic: Semantics

Semantics of \mathcal{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
- $\Pi = \{\pi_1, \pi_2, \pi_3\}$
- $\sigma(\mathbf{R}) = \{\pi_1, \pi_2\}$

ϵ_1	ϵ_2	Δ / Π
		π_1
		π_2
		π_3

First-Order Standpoint Logic: Semantics

Semantics of \mathcal{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
- $\Pi = \{\pi_1, \pi_2, \pi_3\}$
- $\sigma(\mathbf{R}) = \{\pi_1, \pi_2\}$

ϵ_1	ϵ_2	Δ / Π
		π_1
		π_2
		π_3

} **R**

First-Order Standpoint Logic: Semantics

Semantics of \mathcal{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
- $\Pi = \{\pi_1, \pi_2, \pi_3\}$
- $\sigma(\mathbf{R}) = \{\pi_1, \pi_2\}$
- $\sigma(\mathbf{B}) = \{\pi_2, \pi_3\}$

ϵ_1	ϵ_2	Δ / Π
		π_1
		π_2
		π_3

} **R**


First-Order Standpoint Logic: Semantics

Semantics of \mathcal{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
- $\Pi = \{\pi_1, \pi_2, \pi_3\}$
- $\sigma(\mathbf{R}) = \{\pi_1, \pi_2\}$
- $\sigma(\mathbf{B}) = \{\pi_2, \pi_3\}$




First-Order Standpoint Logic: Semantics

Semantics of \mathbb{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
- $\Pi = \{\pi_1, \pi_2, \pi_3\}$
- $\sigma(\mathbf{R}) = \{\pi_1, \pi_2\}$
- $\sigma(\mathbf{B}) = \{\pi_2, \pi_3\}$




First-Order Standpoint Logic: Semantics

Semantics of \mathbb{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
- $\Pi = \{\pi_1, \pi_2, \pi_3\}$
- $\sigma(\mathbf{R}) = \{\pi_1, \pi_2\}$
- $\sigma(\mathbf{B}) = \{\pi_2, \pi_3\}$
- $\gamma(\pi_1) = (p \mapsto \emptyset, \dots)$



First-Order Standpoint Logic: Semantics


Semantics of \mathbb{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
- $\Pi = \{\pi_1, \pi_2, \pi_3\}$
- $\sigma(\mathbf{R}) = \{\pi_1, \pi_2\}$
- $\sigma(\mathbf{B}) = \{\pi_2, \pi_3\}$
- $\gamma(\pi_1) = (p \mapsto \emptyset, \dots)$

*Rigid domains and constants



First-Order Standpoint Logic: Semantics


Semantics of \mathbb{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
- $\Pi = \{\pi_1, \pi_2, \pi_3\}$
- $\sigma(\mathbf{R}) = \{\pi_1, \pi_2\}$
- $\sigma(\mathbf{B}) = \{\pi_2, \pi_3\}$
- $\gamma(\pi_1) = (p \mapsto \emptyset, \dots)$

*Rigid domains and constants



First-Order Standpoint Logic: Semantics

Semantics of \mathbb{S}


Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
- $\Pi = \{\pi_1, \pi_2, \pi_3\}$
- $\sigma(\mathbf{R}) = \{\pi_1, \pi_2\}$
- $\sigma(\mathbf{B}) = \{\pi_2, \pi_3\}$
- $\gamma(\pi_1) = (p \mapsto \emptyset, \dots)$

$$\mathcal{M} \models \Box_{\mathbf{B}} p(a)$$

*Rigid domains and constants



First-Order Standpoint Logic: Semantics


Semantics of \mathbb{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
 - $\Pi = \{\pi_1, \pi_2, \pi_3\}$
 - $\sigma(\mathbf{R}) = \{\pi_1, \pi_2\}$
 - $\sigma(\mathbf{B}) = \{\pi_2, \pi_3\}$
 - $\gamma(\pi_1) = (p \mapsto \emptyset, \dots)$
- $\mathcal{M} \models \Box_{\mathbf{B}} p(a)$
 - $\mathcal{M} \models \Diamond_{\mathbf{R}} p(a) \wedge \Diamond_{\mathbf{R}} \neg p(a)$

*Rigid domains and constants



First-Order Standpoint Logic: Semantics


Semantics of \mathbb{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
- $\Pi = \{\pi_1, \pi_2, \pi_3\}$
- $\sigma(\mathbf{R}) = \{\pi_1, \pi_2\}$
- $\sigma(\mathbf{B}) = \{\pi_2, \pi_3\}$
- $\gamma(\pi_1) = (p \mapsto \emptyset, \dots)$
- $\mathcal{M} \models \Box_{\mathbf{B}} p(a)$
- $\mathcal{M} \models \Diamond_{\mathbf{R}} p(a) \wedge \Diamond_{\mathbf{R}} \neg p(a)$
- $\mathcal{M} \models \Box_{\mathbf{R}} \forall x p(x) \rightarrow (\exists y r(x, y))$

*Rigid domains and constants



First-Order Standpoint Logic: Semantics


Semantics of \mathbb{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
- $\Pi = \{\pi_1, \pi_2, \pi_3\}$
- $\sigma(\mathbf{R}) = \{\pi_1, \pi_2\}$
- $\sigma(\mathbf{B}) = \{\pi_2, \pi_3\}$
- $\gamma(\pi_1) = (p \mapsto \emptyset, \dots)$
- $\mathcal{M} \models \Box_{\mathbf{B}} p(a)$
- $\mathcal{M} \models \Diamond_{\mathbf{R}} p(a) \wedge \Diamond_{\mathbf{R}} \neg p(a)$
- $\mathcal{M} \models \Box_{\mathbf{R}} \forall x p(x) \rightarrow (\exists y r(x, y))$

*Rigid domains and constants



First-Order Standpoint Logic: Semantics


Semantics of \mathbb{S}

Relational semantics:

$$\mathcal{M} = \langle \Delta, \Pi, \sigma, \gamma \rangle$$

- $\Delta = \{\epsilon_1, \epsilon_2\}$
- $\Pi = \{\pi_1, \pi_2, \pi_3\}$
- $\sigma(\mathbf{R}) = \{\pi_1, \pi_2\}$
- $\sigma(\mathbf{B}) = \{\pi_2, \pi_3\}$
- $\gamma(\pi_1) = (p \mapsto \emptyset, \dots)$
- $\mathcal{M} \models \Box_{\mathbf{B}} p(a)$
- $\mathcal{M} \models \Diamond_{\mathbf{R}} p(a) \wedge \Diamond_{\mathbf{R}} \neg p(a)$
- $\mathcal{M} \models \Box_{\mathbf{R}} \forall x p(x) \rightarrow (\exists y r(x, y))$

*Rigid domains and constants



Remark: The semantics of standpoint logic can also be expressed in standard Kripke (relational) semantics.

Extended Example



Knowledge Integration - Standpoint Logic

1. $\Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$

2. $\Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$

3. $\Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$

4. $L \leq S \wedge H \leq S$

Knowledge Integration - Standpoint Logic

1. $\Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$

2. $\Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$

3. $\Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$

4. $L \leq S \wedge H \leq S$

Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{ Tumor}(x)$$

Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$

Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$

Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$

$$\Delta / \Pi$$

Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$


$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{ Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{ Tumor}(x)$$

$$7. \forall x \Box_L \text{ Tissue}(x) \rightarrow \Box_H \text{ Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$


$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{ Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{ Tumor}(x)$$

$$7. \forall x \Box_L \text{ Tissue}(x) \rightarrow \Box_H \text{ Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$


$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{ Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{ Tumor}(x)$$

$$7. \forall x \Box_L \text{ Tissue}(x) \rightarrow \Box_H \text{ Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$

Inferences:



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$


$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$

Inferences:

$$9. \Box_L \text{Tumor}(a) \quad (5, 8)$$



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$


$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$

Inferences:

$$9. \Box_L \text{Tumor}(a) \quad (5, 8)$$



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$


$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$

Inferences:

$$9. \Box_L \text{Tumor}(a) \quad (5, 8)$$



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$


$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$

Inferences:

$$9. \Box_L \text{Tumor}(a) \quad (5, 8)$$

$$10. \Box_L \text{Tissue}(a) \quad (9, 3)$$



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$


$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$

Inferences:

$$9. \Box_L \text{Tumor}(a) \quad (5, 8)$$

$$10. \Box_L \text{Tissue}(a) \quad (9, 3)$$



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$


$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$

Inferences:

$$9. \Box_L \text{Tumor}(a) \quad (5, 8)$$

$$10. \Box_L \text{Tissue}(a) \quad (9, 3)$$

$$11. \Box_H \text{Tissue}(a) \quad (10, 7)$$



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$


$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$

Inferences:

$$9. \Box_L \text{Tumor}(a) \quad (5, 8)$$

$$10. \Box_L \text{Tissue}(a) \quad (9, 3)$$

$$11. \Box_H \text{Tissue}(a) \quad (10, 7)$$



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$


$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$

Inferences:

$$9. \Box_L \text{Tumor}(a) \quad (5, 8)$$

$$10. \Box_L \text{Tissue}(a) \quad (9, 3)$$

$$11. \Box_H \text{Tissue}(a) \quad (10, 7)$$



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$


Inferences:

$$9. \Box_L \text{Tumor}(a) \quad (5, 8)$$

$$10. \Box_L \text{Tissue}(a) \quad (9, 3)$$

$$11. \Box_H \text{Tissue}(a) \quad (10, 7)$$

$$12. \Box_H \exists y \text{ productOf}(a, y) \wedge \text{Tumor}(y) \quad (9, 6)$$



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$


Inferences:

$$9. \Box_L \text{Tumor}(a) \quad (5, 8)$$

$$10. \Box_L \text{Tissue}(a) \quad (9, 3)$$

$$11. \Box_H \text{Tissue}(a) \quad (10, 7)$$

$$12. \Box_H \exists y \text{ productOf}(a, y) \wedge \text{Tumor}(y) \quad (9, 6)$$



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$

Inferences:


$$9. \Box_L \text{Tumor}(a) \quad (5, 8)$$

$$10. \Box_L \text{Tissue}(a) \quad (9, 3)$$

$$11. \Box_H \text{Tissue}(a) \quad (10, 7)$$

$$12. \Box_H \exists y \text{ productOf}(a, y) \wedge \text{Tumor}(y) \quad (9, 6)$$

$$13. \Box_H \exists y \text{ Process}(y) \quad (12, 2)$$



Knowledge Integration - Standpoint Logic

$$1. \Box_S(\neg \exists x \text{ Process}(x) \wedge \text{Tissue}(x))$$

$$2. \Box_H(\forall x \text{ Tumor}(x) \rightarrow \text{Process}(x))$$

$$3. \Box_L(\forall x \text{ Tumor}(x) \rightarrow \text{Tissue}(x))$$

$$4. L \leq S \wedge H \leq S$$

$$5. \forall x \Diamond_S(\text{Tumor}(x) \wedge \text{Object}(x)) \rightarrow \Box_L \text{Tumor}(x)$$

$$6. \forall x \Box_H(\exists y \text{ productOf}(x, y) \wedge \text{Tumor}(y)) \leftrightarrow \Diamond_L \text{Tumor}(x)$$

$$7. \forall x \Box_L \text{Tissue}(x) \rightarrow \Box_H \text{Tissue}(x)$$

$$8. \Diamond_S(\text{Patient}(p1) \wedge \text{HasPart}(p1, a) \wedge \text{Tumor}(a) \wedge \text{Object}(a))$$

Inferences:


$$9. \Box_L \text{Tumor}(a) \quad (5, 8)$$

$$10. \Box_L \text{Tissue}(a) \quad (9, 3)$$

$$11. \Box_H \text{Tissue}(a) \quad (10, 7)$$

$$12. \Box_H \exists y \text{ productOf}(a, y) \wedge \text{Tumor}(y) \quad (9, 6)$$

$$13. \Box_H \exists y \text{ Process}(y) \quad (12, 2)$$



Decidability and Complexity




Decidability and Complexity

Goal: Understanding computational cost of reasoning with standpoint-KR languages


We consider fragments of FOSL.

Important distinction: how much do standpoint operators and quantifiers interleave?

- * Sentential fragments often preserve complexity, but have limitations
 - * Monodic fragments have important applications in knowledge integration
 - * Beyond monodic, modal logics easily become undecidable
- + liberal use of modal operators
- + technically challenging



Sentential Fragments



Sentential Fragments

Sentential Fragments

Sentential First Order Standpoint Logic (FOSL):

Sentential Fragments

Sentential First Order Standpoint Logic (FOSL):

Definition (Sentential formula):

Let ϕ be a formula of FOSL. We say that ϕ is *sentential* iff for all subformulas of ϕ of the form $\Box_e \psi$, all variables occurring in ψ are bound by a quantifier.

Sentential Fragments

Sentential First Order Standpoint Logic (FOSL):

Definition (Sentential formula):

Let ϕ be a formula of FOSL. We say that ϕ is *sentential* iff for all subformulas of ϕ of the form $\Box_e \psi$, all variables occurring in ψ are bound by a quantifier.

Eg.:

Sentential Fragments

Sentential First Order Standpoint Logic (FOSL):

Definition (Sentential formula):

Let ϕ be a formula of FOSL. We say that ϕ is *sentential* iff for all subformulas of ϕ of the form $\Box_e \psi$, all variables occurring in ψ are bound by a quantifier.

Eg.: 1. $\Box_s [\forall x \text{ Tumor}(x) \rightarrow (\text{Process}(x) \vee \text{Tissue}(x))]$ 

Sentential Fragments

Sentential First Order Standpoint Logic (FOSL):

Definition (Sentential formula):

Let ϕ be a formula of FOSL. We say that ϕ is *sentential* iff for all subformulas of ϕ of the form $\Box_e \psi$, all variables occurring in ψ are bound by a quantifier.

Eg.:

1. $\Box_s [\forall x \text{ Tumor}(x) \rightarrow (\text{Process}(x) \vee \text{Tissue}(x))]$



2. $\Diamond_T [T] \wedge \Diamond_P [T]$



Sentential Fragments

Sentential First Order Standpoint Logic (FOSL):

Definition (Sentential formula):

Let ϕ be a formula of FOSL. We say that ϕ is *sentential* iff for all subformulas of ϕ of the form $\Box_e \psi$, all variables occurring in ψ are bound by a quantifier.

Eg.:

$$1. \Box_S [\forall x \text{ Tumor}(x) \rightarrow (\text{Process}(x) \vee \text{Tissue}(x))]$$



$$2. \Diamond_T [T] \wedge \Diamond_P [T]$$



$$3. \forall x \Box_P [\text{Tissue}(x)] \rightarrow \Box_T [\text{Tissue}(x)]$$



Sentential Fragments

Sentential First Order Standpoint Logic (FOSL):

Definition (Sentential formula):

Let ϕ be a formula of FOSL. We say that ϕ is *sentential* iff for all subformulas of ϕ of the form $\Box_e \psi$, all variables occurring in ψ are bound by a quantifier.

Eg.:

$$1. \Box_s [\forall x \text{ Tumor}(x) \rightarrow (\text{Process}(x) \vee \text{Tissue}(x))]$$



$$2. \Diamond_T [T] \wedge \Diamond_P [T]$$



$$3. \forall x \Box_P [\text{Tissue}(x)] \rightarrow \Box_T [\text{Tissue}(x)]$$



Theorem (Small Model Property):

A sentential FOSL formula ϕ is satisfiable iff it has a model with at most $|\phi|$ precisifications. That is, for sentential FOSL, satisfiability and $|\phi|$ -satisfiability coincide.

Sentential Fragments

(n-)Equisatisfiable Translation to Plain FOL

$$\text{Trans}_n(\phi) = \bigwedge_{\pi \in \Pi_n} \text{trans}_n(\pi, \phi) \wedge \bigwedge_{\pi \in \Pi_n} *_{\pi},$$

$$\text{trans}_n(\pi, P(t_1, \dots, t_k)) = P_{\pi}(t_1, \dots, t_k)$$

$$\text{trans}_n(\pi, \neg\psi) = \neg\text{trans}_n(\pi, \psi)$$

$$\text{trans}_n(\pi, \psi_1 \wedge \psi_2) = \text{trans}_n(\pi, \psi_1) \wedge \text{trans}_n(\pi, \psi_2)$$

$$\text{trans}_n(\pi, \forall x\psi) = \forall x(\text{trans}_n(\pi, \psi))$$

$$\text{trans}_n(\pi', \Box_e \psi) = \bigwedge_{\pi \in \Pi_n} (\text{trans}_{\mathcal{E}}(\pi, e) \rightarrow \text{trans}_n(\pi, \psi))$$

$$\text{trans}_{\mathcal{E}}(\pi, s) = s_{\pi}$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cup e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \vee \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cap e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \setminus e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \neg\text{trans}_{\mathcal{E}}(\pi, e_2)$$

Sentential Fragments

(n-)Equisatisfiable Translation to Plain FOL

$$\text{Trans}_n(\phi) = \bigwedge_{\pi \in \Pi_n} \text{trans}_n(\pi, \phi) \wedge \bigwedge_{\pi \in \Pi_n} *_{\pi},$$

$$\text{trans}_n(\pi, P(t_1, \dots, t_k)) = P_{\pi}(t_1, \dots, t_k)$$

$$\text{trans}_n(\pi, \neg\psi) = \neg\text{trans}_n(\pi, \psi)$$

$$\text{trans}_n(\pi, \psi_1 \wedge \psi_2) = \text{trans}_n(\pi, \psi_1) \wedge \text{trans}_n(\pi, \psi_2)$$

$$\text{trans}_n(\pi, \forall x\psi) = \forall x(\text{trans}_n(\pi, \psi))$$

$$\text{trans}_n(\pi', \Box_e \psi) = \bigwedge_{\pi \in \Pi_n} (\text{trans}_{\mathcal{E}}(\pi, e) \rightarrow \text{trans}_n(\pi, \psi))$$

$$\text{trans}_{\mathcal{E}}(\pi, s) = s_{\pi}$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cup e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \vee \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cap e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \setminus e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \neg\text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{Example: } \phi = \neg \Box_R p(a) \wedge \Box_{R \cap B} p(a)$$

Sentential Fragments

(n-)Equisatisfiable Translation to Plain FOL

$$\text{Trans}_n(\phi) = \bigwedge_{\pi \in \Pi_n} \text{trans}_n(\pi, \phi) \wedge \bigwedge_{\pi \in \Pi_n} *_{\pi},$$

$$\text{trans}_n(\pi, P(t_1, \dots, t_k)) = P_{\pi}(t_1, \dots, t_k)$$

$$\text{trans}_n(\pi, \neg\psi) = \neg\text{trans}_n(\pi, \psi)$$

$$\text{trans}_n(\pi, \psi_1 \wedge \psi_2) = \text{trans}_n(\pi, \psi_1) \wedge \text{trans}_n(\pi, \psi_2)$$

$$\text{trans}_n(\pi, \forall x\psi) = \forall x(\text{trans}_n(\pi, \psi))$$

$$\text{trans}_n(\pi', \Box_e \psi) = \bigwedge_{\pi \in \Pi_n} (\text{trans}_{\mathcal{E}}(\pi, e) \rightarrow \text{trans}_n(\pi, \psi))$$

$$\text{trans}_{\mathcal{E}}(\pi, s) = s_{\pi}$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cup e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \vee \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cap e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \setminus e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \neg\text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{Example: } \phi = \neg\Box_R p(a) \wedge \Box_{R \cap B} p(a)$$

$$\begin{aligned} \text{Trans}_3(\phi) = & \neg((R_1 \rightarrow p_1(a)) \wedge (R_2 \rightarrow p_2(a)) \wedge (R_3 \rightarrow p_3(a))) \\ & \wedge \\ & (((R_1 \wedge B_1) \rightarrow p_1(a)) \wedge ((R_2 \wedge B_2) \rightarrow p_2(a)) \wedge ((R_3 \wedge B_3) \rightarrow p_3(a))) \\ & \wedge \\ & *_1 \wedge *_2 \wedge *_3, \end{aligned}$$

Sentential Fragments

(n-)Equisatisfiable Translation to Plain FOL

$$\text{Trans}_n(\phi) = \bigwedge_{\pi \in \Pi_n} \text{trans}_n(\pi, \phi) \wedge \bigwedge_{\pi \in \Pi_n} *_{\pi},$$

$$\text{trans}_n(\pi, \mathbf{P}(t_1, \dots, t_k)) = \mathbf{P}_{\pi}(t_1, \dots, t_k)$$

$$\text{trans}_n(\pi, \neg\psi) = \neg\text{trans}_n(\pi, \psi)$$

$$\text{trans}_n(\pi, \psi_1 \wedge \psi_2) = \text{trans}_n(\pi, \psi_1) \wedge \text{trans}_n(\pi, \psi_2)$$

$$\text{trans}_n(\pi, \forall x\psi) = \forall x(\text{trans}_n(\pi, \psi))$$

$$\text{trans}_n(\pi', \Box_e \psi) = \bigwedge_{\pi \in \Pi_n} (\text{trans}_{\mathcal{E}}(\pi, e) \rightarrow \text{trans}_n(\pi, \psi))$$

$$\text{trans}_{\mathcal{E}}(\pi, s) = s_{\pi}$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cup e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \vee \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cap e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \setminus e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \neg\text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{Example: } \phi = \neg \Box_R p(a) \wedge \Box_{R \cap B} p(a)$$

$$\begin{aligned} \text{Trans}_3(\phi) = & \neg((R_1 \rightarrow p_1(a)) \wedge (R_2 \rightarrow p_2(a)) \wedge (R_3 \rightarrow p_3(a))) \\ & \wedge \\ & (((R_1 \wedge B_1) \rightarrow p_1(a)) \wedge ((R_2 \wedge B_2) \rightarrow p_2(a)) \wedge ((R_3 \wedge B_3) \rightarrow p_3(a))) \\ & \wedge \\ & *_1 \wedge *_2 \wedge *_3, \end{aligned}$$

FOL model

Sentential Fragments

(n-)Equisatisfiable Translation to Plain FOL

$$\text{Trans}_n(\phi) = \bigwedge_{\pi \in \Pi_n} \text{trans}_n(\pi, \phi) \wedge \bigwedge_{\pi \in \Pi_n} *_{\pi},$$

$$\text{trans}_n(\pi, P(t_1, \dots, t_k)) = P_{\pi}(t_1, \dots, t_k)$$

$$\text{trans}_n(\pi, \neg\psi) = \neg\text{trans}_n(\pi, \psi)$$

$$\text{trans}_n(\pi, \psi_1 \wedge \psi_2) = \text{trans}_n(\pi, \psi_1) \wedge \text{trans}_n(\pi, \psi_2)$$

$$\text{trans}_n(\pi, \forall x\psi) = \forall x(\text{trans}_n(\pi, \psi))$$

$$\text{trans}_n(\pi', \Box_e \psi) = \bigwedge_{\pi \in \Pi_n} (\text{trans}_{\mathcal{E}}(\pi, e) \rightarrow \text{trans}_n(\pi, \psi))$$

$$\text{trans}_{\mathcal{E}}(\pi, s) = s_{\pi}$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cup e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \vee \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cap e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \setminus e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \neg\text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{Example: } \phi = \neg \Box_R p(a) \wedge \Box_{R \cap B} p(a)$$

$$\begin{aligned} \text{Trans}_3(\phi) = & \neg((R_1 \rightarrow p_1(a)) \wedge (R_2 \rightarrow p_2(a)) \wedge (R_3 \rightarrow p_3(a))) \\ & \wedge \\ & (((R_1 \wedge B_1) \rightarrow p_1(a)) \wedge ((R_2 \wedge B_2) \rightarrow p_2(a)) \wedge ((R_3 \wedge B_3) \rightarrow p_3(a))) \\ & \wedge \\ & *_1 \wedge *_2 \wedge *_3, \end{aligned}$$

$a \bullet$

FOL model

Sentential Fragments

(n-)Equisatisfiable Translation to Plain FOL

$$\text{Trans}_n(\phi) = \bigwedge_{\pi \in \Pi_n} \text{trans}_n(\pi, \phi) \wedge \bigwedge_{\pi \in \Pi_n} *_{\pi},$$

$$\text{trans}_n(\pi, P(t_1, \dots, t_k)) = P_{\pi}(t_1, \dots, t_k)$$

$$\text{trans}_n(\pi, \neg\psi) = \neg\text{trans}_n(\pi, \psi)$$

$$\text{trans}_n(\pi, \psi_1 \wedge \psi_2) = \text{trans}_n(\pi, \psi_1) \wedge \text{trans}_n(\pi, \psi_2)$$

$$\text{trans}_n(\pi, \forall x\psi) = \forall x(\text{trans}_n(\pi, \psi))$$

$$\text{trans}_n(\pi', \Box_e \psi) = \bigwedge_{\pi \in \Pi_n} (\text{trans}_{\mathcal{E}}(\pi, e) \rightarrow \text{trans}_n(\pi, \psi))$$

$$\text{trans}_{\mathcal{E}}(\pi, s) = s_{\pi}$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cup e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \vee \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cap e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \setminus e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \neg\text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{Example: } \phi = \neg\Box_R p(a) \wedge \Box_{R \cap B} p(a)$$

$$\begin{aligned} \text{Trans}_3(\phi) = & \neg((R_1 \rightarrow p_1(a)) \wedge (R_2 \rightarrow p_2(a)) \wedge (R_3 \rightarrow p_3(a))) \\ & \wedge \\ & (((R_1 \wedge B_1) \rightarrow p_1(a)) \wedge ((R_2 \wedge B_2) \rightarrow p_2(a)) \wedge ((R_3 \wedge B_3) \rightarrow p_3(a))) \\ & \wedge \\ & *_1 \wedge *_2 \wedge *_3, \end{aligned}$$

$\neg p_1$	$*_1$	R_1	$\neg B_1$
$a \bullet p_2$	$*_2$	R_2	B_2
p_3	$*_3$	$\neg R_3$	B_3

FOL model

Sentential Fragments

(n-)Equisatisfiable Translation to Plain FOL

$$\text{Trans}_n(\phi) = \bigwedge_{\pi \in \Pi_n} \text{trans}_n(\pi, \phi) \wedge \bigwedge_{\pi \in \Pi_n} *_{\pi},$$

$$\text{trans}_n(\pi, P(t_1, \dots, t_k)) = P_{\pi}(t_1, \dots, t_k)$$

$$\text{trans}_n(\pi, \neg\psi) = \neg\text{trans}_n(\pi, \psi)$$

$$\text{trans}_n(\pi, \psi_1 \wedge \psi_2) = \text{trans}_n(\pi, \psi_1) \wedge \text{trans}_n(\pi, \psi_2)$$

$$\text{trans}_n(\pi, \forall x\psi) = \forall x(\text{trans}_n(\pi, \psi))$$

$$\text{trans}_n(\pi', \Box_e \psi) = \bigwedge_{\pi \in \Pi_n} (\text{trans}_{\mathcal{E}}(\pi, e) \rightarrow \text{trans}_n(\pi, \psi))$$

$$\text{trans}_{\mathcal{E}}(\pi, s) = s_{\pi}$$


$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cup e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \vee \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cap e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \setminus e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \neg\text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{Example: } \phi = \neg\Box_R p(a) \wedge \Box_{R \cap B} p(a)$$

$$\begin{aligned} \text{Trans}_3(\phi) = & \neg((R_1 \rightarrow p_1(a)) \wedge (R_2 \rightarrow p_2(a)) \wedge (R_3 \rightarrow p_3(a))) \\ & \wedge \\ & (((R_1 \wedge B_1) \rightarrow p_1(a)) \wedge ((R_2 \wedge B_2) \rightarrow p_2(a)) \wedge ((R_3 \wedge B_3) \rightarrow p_3(a))) \\ & \wedge \\ & *_1 \wedge *_2 \wedge *_3, \end{aligned}$$



FOSL model

$\neg p_1$	$*_1$	R_1	$\neg B_1$
$a \bullet p_2$	$*_2$	R_2	B_2
p_3	$*_3$	$\neg R_3$	B_3

FOL model

Sentential Fragments

(n-)Equisatisfiable Translation to Plain FOL

$$\text{Trans}_n(\phi) = \bigwedge_{\pi \in \Pi_n} \text{trans}_n(\pi, \phi) \wedge \bigwedge_{\pi \in \Pi_n} *_{\pi},$$

$$\text{trans}_n(\pi, \mathbf{P}(t_1, \dots, t_k)) = \mathbf{P}_{\pi}(t_1, \dots, t_k)$$

$$\text{trans}_n(\pi, \neg\psi) = \neg\text{trans}_n(\pi, \psi)$$

$$\text{trans}_n(\pi, \psi_1 \wedge \psi_2) = \text{trans}_n(\pi, \psi_1) \wedge \text{trans}_n(\pi, \psi_2)$$

$$\text{trans}_n(\pi, \forall x\psi) = \forall x(\text{trans}_n(\pi, \psi))$$

$$\text{trans}_n(\pi', \Box_e \psi) = \bigwedge_{\pi \in \Pi_n} (\text{trans}_{\mathcal{E}}(\pi, e) \rightarrow \text{trans}_n(\pi, \psi))$$

$$\text{trans}_{\mathcal{E}}(\pi, s) = s_{\pi}$$


$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cup e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \vee \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cap e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \setminus e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \neg\text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{Example: } \phi = \neg\Box_R p(a) \wedge \Box_{R \cap B} p(a)$$

$$\begin{aligned} \text{Trans}_3(\phi) = & \neg((R_1 \rightarrow p_1(a)) \wedge (R_2 \rightarrow p_2(a)) \wedge (R_3 \rightarrow p_3(a))) \\ & \wedge \\ & (((R_1 \wedge B_1) \rightarrow p_1(a)) \wedge ((R_2 \wedge B_2) \rightarrow p_2(a)) \wedge ((R_3 \wedge B_3) \rightarrow p_3(a))) \\ & \wedge \\ & *_1 \wedge *_2 \wedge *_3, \end{aligned}$$



FOSL model

FOL model

Sentential Fragments

(n-)Equisatisfiable Translation to Plain FOL

$$\text{Trans}_n(\phi) = \bigwedge_{\pi \in \Pi_n} \text{trans}_n(\pi, \phi) \wedge \bigwedge_{\pi \in \Pi_n} *_{\pi},$$

$$\text{trans}_n(\pi, P(t_1, \dots, t_k)) = P_{\pi}(t_1, \dots, t_k)$$

$$\text{trans}_n(\pi, \neg\psi) = \neg\text{trans}_n(\pi, \psi)$$

$$\text{trans}_n(\pi, \psi_1 \wedge \psi_2) = \text{trans}_n(\pi, \psi_1) \wedge \text{trans}_n(\pi, \psi_2)$$

$$\text{trans}_n(\pi, \forall x\psi) = \forall x(\text{trans}_n(\pi, \psi))$$

$$\text{trans}_n(\pi', \Box_e \psi) = \bigwedge_{\pi \in \Pi_n} (\text{trans}_{\mathcal{E}}(\pi, e) \rightarrow \text{trans}_n(\pi, \psi))$$

$$\text{trans}_{\mathcal{E}}(\pi, s) = s_{\pi}$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cup e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \vee \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cap e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \setminus e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \neg\text{trans}_{\mathcal{E}}(\pi, e_2)$$

Sentential Fragments

(n-)Equisatisfiable Translation to Plain FOL

$$\text{Trans}_n(\phi) = \bigwedge_{\pi \in \Pi_n} \text{trans}_n(\pi, \phi) \wedge \bigwedge_{\pi \in \Pi_n} *_{\pi},$$

$$\text{trans}_n(\pi, P(t_1, \dots, t_k)) = P_{\pi}(t_1, \dots, t_k)$$

$$\text{trans}_n(\pi, \neg\psi) = \neg\text{trans}_n(\pi, \psi)$$

$$\text{trans}_n(\pi, \psi_1 \wedge \psi_2) = \text{trans}_n(\pi, \psi_1) \wedge \text{trans}_n(\pi, \psi_2)$$

$$\text{trans}_n(\pi, \forall x\psi) = \forall x(\text{trans}_n(\pi, \psi))$$

$$\text{trans}_n(\pi', \Box_e \psi) = \bigwedge_{\pi \in \Pi_n} (\text{trans}_{\mathcal{E}}(\pi, e) \rightarrow \text{trans}_n(\pi, \psi))$$

$$\text{trans}_{\mathcal{E}}(\pi, s) = s_{\pi}$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cup e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \vee \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cap e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \setminus e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \neg\text{trans}_{\mathcal{E}}(\pi, e_2)$$

Lemma:

A formula ϕ is n-satisfiable in FOSL if and only if $\text{Trans}_n(\phi)$ is satisfiable in first-order logic.

Sentential Fragments

(n-)Equisatisfiable Translation to Plain FOL

$$\text{Trans}_n(\phi) = \bigwedge_{\pi \in \Pi_n} \text{trans}_n(\pi, \phi) \wedge \bigwedge_{\pi \in \Pi_n} *_{\pi},$$

$$\text{trans}_n(\pi, P(t_1, \dots, t_k)) = P_{\pi}(t_1, \dots, t_k)$$

$$\text{trans}_n(\pi, \neg\psi) = \neg\text{trans}_n(\pi, \psi)$$

$$\text{trans}_n(\pi, \psi_1 \wedge \psi_2) = \text{trans}_n(\pi, \psi_1) \wedge \text{trans}_n(\pi, \psi_2)$$

$$\text{trans}_n(\pi, \forall x\psi) = \forall x(\text{trans}_n(\pi, \psi))$$

$$\text{trans}_n(\pi', \Box_e \psi) = \bigwedge_{\pi \in \Pi_n} (\text{trans}_{\mathcal{E}}(\pi, e) \rightarrow \text{trans}_n(\pi, \psi))$$

$$\text{trans}_{\mathcal{E}}(\pi, s) = s_{\pi}$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cup e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \vee \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \cap e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \text{trans}_{\mathcal{E}}(\pi, e_2)$$

$$\text{trans}_{\mathcal{E}}(\pi, e_1 \setminus e_2) = \text{trans}_{\mathcal{E}}(\pi, e_1) \wedge \neg\text{trans}_{\mathcal{E}}(\pi, e_2)$$

Lemma:

A formula ϕ is n-satisfiable in FOSL if and only if $\text{Trans}_n(\phi)$ is satisfiable in first-order logic.

Theorem:

Let F be a "translation-friendly" fragment of FOL. Then the satisfiability of the sentential standpoint- F fragment of FOSL,

- is decidable iff it is for F , and
- has the same complexity as F (if at least NP)


Decidable Sentential Framgments

- By small model property and generic translation, complexity of decidable fragments is preserved:
 - ➔ S Guarded fragment (GF) $\rightarrow 2\text{ExpTime}$
 - ➔ S Triguarded fragment (TGF) $\rightarrow 2\text{NExpTime}$
 - ➔ S Counting 2-variable fragment (C^2) $\rightarrow \text{NExpTime}$
 - ➔ Standpoint OWL 2 $\rightarrow 2\text{NExpTime}$ (some extra tricks required)




Decidable Sentential Framgments

- By small model property and generic translation, complexity of decidable fragments is preserved:
 - ➔ S Guarded fragment (GF) → 2ExpTime
 - ➔ S Triguarded fragment (TGF) → 2NExpTime
 - ➔ S Counting 2-variable fragment (C²) → NExpTime
 - ➔ Standpoint OWL 2 → 2NExpTime (some extra tricks required)
- Result via polynomial equisatisfiable translation → practical implementations



Monodic Fragments



Monodic Standpoint Description Logics

Monodic Standpoint Description Logics

Monodic modal extensions of DLs can lead to a blowup in complexity.

Tractable Diversity: Scalable Multiperspective Ontology Management via Standpoint \mathcal{EL}

Lucía Gómez Álvarez, Sebastian Rudolph, Hannes Straß; (*IJCAI 2023*)

Pushing the Boundaries of Tractable Multiperspective Reasoning: A deduction calculus for Standpoint \mathcal{EL}^+

Lucía Gómez Álvarez, Sebastian Rudolph, Hannes Straß; (*KR 2023*)

Monodic Standpoint Description Logics

Monodic modal extensions of DLs can lead to a blowup in complexity.

Tractable Diversity: Scalable Multiperspective Ontology Management via Standpoint \mathcal{EL}

Lucía Gómez Álvarez, Sebastian Rudolph, Hannes Straß; (*IJCAI 2023*)

Pushing the Boundaries of Tractable Multiperspective Reasoning: A deduction calculus for Standpoint \mathcal{EL}^+

Lucía Gómez Álvarez, Sebastian Rudolph, Hannes Straß; (*KR 2023*)

➡ Complexity of the satisfiability of Standpoint- \mathcal{EL}^+ ➡ **PTime** (deduction calculus)

Monodic Standpoint Description Logics

Monodic modal extensions of DLs can lead to a blowup in complexity.

Tractable Diversity: Scalable Multiperspective Ontology Management via Standpoint \mathcal{EL}

Lucía Gómez Álvarez, Sebastian Rudolph, Hannes Straß; (*IJCAI 2023*)

Pushing the Boundaries of Tractable Multiperspective Reasoning: A deduction calculus for Standpoint \mathcal{EL}^+

Lucía Gómez Álvarez, Sebastian Rudolph, Hannes Straß; (*KR 2023*)

- ➔ Complexity of the satisfiability of Standpoint- \mathcal{EL}^+ ➔ **PTime** (deduction calculus)
- ➔ Tractability is easily lost:

Monodic Standpoint Description Logics

Monodic modal extensions of DLs can lead to a blowup in complexity.

Tractable Diversity: Scalable Multiperspective Ontology Management via Standpoint \mathcal{EL}

Lucía Gómez Álvarez, Sebastian Rudolph, Hannes Straß; (*IJCAI 2023*)

Pushing the Boundaries of Tractable Multiperspective Reasoning: A deduction calculus for Standpoint \mathcal{EL}^+

Lucía Gómez Álvarez, Sebastian Rudolph, Hannes Straß; (*KR 2023*)

- ➔ Complexity of the satisfiability of Standpoint- \mathcal{EL}^+ ➔ **PTime** (deduction calculus)
- ➔ Tractability is easily lost:
 - Empty standpoints ➔ **NP-hard**

Monodic Standpoint Description Logics

Monodic modal extensions of DLs can lead to a blowup in complexity.

Tractable Diversity: Scalable Multiperspective Ontology Management via Standpoint \mathcal{EL}

Lucía Gómez Álvarez, Sebastian Rudolph, Hannes Straß; (IJCAI 2023)

Pushing the Boundaries of Tractable Multiperspective Reasoning: A deduction calculus for Standpoint \mathcal{EL}^+

Lucía Gómez Álvarez, Sebastian Rudolph, Hannes Straß; (KR 2023)

- ➔ Complexity of the satisfiability of Standpoint- \mathcal{EL}^+ ➔ PTime (deduction calculus)
- ➔ Tractability is easily lost:
 - Empty standpoints ➔ NP-hard
 - Rigid roles ➔ CoNP-hard

Monodic Standpoint Description Logics

Monodic modal extensions of DLs can lead to a blowup in complexity.

Tractable Diversity: Scalable Multiperspective Ontology Management via Standpoint \mathcal{EL}

Lucía Gómez Álvarez, Sebastian Rudolph, Hannes Straß; (IJCAI 2023)

Pushing the Boundaries of Tractable Multiperspective Reasoning: A deduction calculus for Standpoint \mathcal{EL}^+

Lucía Gómez Álvarez, Sebastian Rudolph, Hannes Straß; (KR 2023)

- ➔ Complexity of the satisfiability of Standpoint- \mathcal{EL}^+ ➔ **PTime** (deduction calculus)
- ➔ Tractability is easily lost:
 - Empty standpoints ➔ **NP-hard**
 - Rigid roles ➔ **CoNP-hard**
 - Nominal Concepts ➔ **ExpTime-hard**

Monodic Standpoint Description Logics

Monodic Standpoint Description Logics

Monodic modal extensions of DLs can lead to a blowup in complexity.

Reasoning in \mathcal{SHIQ} with Axiom- and Concept-Level Standpoint Modalities

Lucía Gómez Álvarez, Sebastian Rudolph; (KR 2024)

Monodic Standpoint Description Logics

Monodic modal extensions of DLs can lead to a blowup in complexity.

Reasoning in \mathcal{SHIQ} with Axiom- and Concept-Level Standpoint Modalities

Lucía Gómez Álvarez, Sebastian Rudolph; (KR 2024)

➔ Complexity of the satisfiability of Standpoint- \mathcal{SHIQ}^+ ➔ ExpTime-complete

Monodic Standpoint Description Logics

Monodic modal extensions of DLs can lead to a blowup in complexity.

Reasoning in \mathcal{SHIQ} with Axiom- and Concept-Level Standpoint Modalities

Lucía Gómez Álvarez, Sebastian Rudolph; (KR 2024)

- ➔ Complexity of the satisfiability of Standpoint- \mathcal{SHIQ}^+ ➔ ExpTime-complete
- ➔ Small Model Property (lost with nominal concepts)

Standpoint \mathcal{SHIQ}



The description logic \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I \rangle$ of concept, role, individual names

Syntax:

The **set of concepts** is given by

$$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r . C \mid \exists \leq nr . C$$

With $A \in N_C, r \in N_R$


Substance $\exists \text{sensitiveTo} . \text{Nut}$
 Substance $\sqcap \neg \text{Dangerous} \quad \exists \leq 1 \text{sensitiveTo} . \text{Substance}$

The **set of axioms** includes:

- GCIs and RIAs: $C \sqsubseteq D, R \sqsubseteq R', R \circ R \sqsubseteq R$
- Assertions: $C(a), r(a, b)$

$(\text{Peanut} \sqsubseteq \text{Substance}) \wedge \neg (\exists \text{sensitiveTo} . \text{Peanut})(p)$

Semantics: $\mathcal{I} = \langle \Delta, \cdot^{\mathcal{I}} \rangle$



Towards Standpoint- \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I \rangle$ of concept, role, individual

Syntax:

The **set of concepts** is given by

$$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r . C \mid \exists \leq nr . C$$

With $A \in N_C, r \in N_R$

Substance $\exists \text{sensitiveTo} . \text{Nut}$
 Substance $\sqcap \neg \text{Dangerous} \quad \exists \leq 1 \text{sensitiveTo} . \text{Substance}$

The **set of axioms** includes:

- GCIs and RIAs: $C \sqsubseteq D, R \sqsubseteq R', R \circ R \sqsubseteq R$
- Assertions: $C(a), r(a, b)$

(Peanut \sqsubseteq Substance) $(\exists \text{sensitiveTo} . \Diamond_p \text{Nut})(p)$



Towards Standpoint- \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I, N_S \rangle$ of concept, role, individual and **standpoint** names

Syntax:

The **set of concepts** is given by

$$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r . C \mid \exists \leq nr . C$$

With $A \in N_C, r \in N_R$

Substance $\exists \text{sensitiveTo} . \text{Nut}$
 Substance $\sqcap \neg \text{Dangerous} \quad \exists \leq 1 \text{sensitiveTo} . \text{Substance}$

The **set of axioms** includes:

- GCIs and RIAs: $C \sqsubseteq D, R \sqsubseteq R', R \circ R \sqsubseteq R$
- Assertions: $C(a), r(a, b)$

(Peanut \sqsubseteq Substance) $(\exists \text{sensitiveTo} . \Diamond_p \text{Nut})(p)$



Towards Standpoint- \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I, N_S \rangle$ of concept, role, individual and **standpoint** names, $*$ $\in N_S$ (universal standpoint).

Syntax:

The **set of concepts** is given by

$$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r. C \mid \exists \leq nr. C$$

With $A \in N_C, r \in N_R$

Substance $\exists \text{sensitiveTo} . \text{Nut}$
 Substance $\sqcap \neg \text{Dangerous} \quad \exists \leq 1 \text{sensitiveTo} . \text{Substance}$

The **set of axioms** includes:

- GCIs and RIAs: $C \sqsubseteq D, R \sqsubseteq R', R \circ R \sqsubseteq R$
- Assertions: $C(a), r(a, b)$

(Peanut \sqsubseteq Substance) $(\exists \text{sensitiveTo} . \Diamond_p \text{Nut})(p)$



Towards Standpoint- \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I, N_S \rangle$ of concept, role, individual and **standpoint** names, $* \in N_S$ (universal standpoint).

Syntax:

The **set of concepts** is given by

$$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r. C \mid \exists \leq nr. C \mid \odot_s C$$

With $A \in N_C, r \in N_R, s \in N_S, \odot \in \{\Box, \Diamond\}$.

Substance $\exists \text{sensitiveTo} . \text{Nut}$
 Substance $\sqcap \neg \text{Dangerous} \quad \exists \leq 1 \text{sensitiveTo} . \text{Substance}$

The **set of axioms** includes:

- GCIs and RIAs: $C \sqsubseteq D, R \sqsubseteq R', R \circ R \sqsubseteq R$
- Assertions: $C(a), r(a, b)$

(Peanut \sqsubseteq Substance) $(\exists \text{sensitiveTo} . \Diamond_p \text{Nut})(p)$



Towards Standpoint- \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I, N_S \rangle$ of concept, role, individual and **standpoint** names, $* \in N_S$ (universal standpoint).

Syntax:

The **set of concepts** is given by

$$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r. C \mid \exists \leq nr. C \mid \odot_s C$$

With $A \in N_C, r \in N_R, s \in N_S, \odot \in \{\Box, \Diamond\}$.

Substance $\exists \text{sensitiveTo} . \text{Nut}$ $\Diamond_s \text{Dangerous}$
 Substance $\sqcap \neg \text{Dangerous}$ $\exists \leq 1 \text{sensitiveTo} . \text{Substance}$

The **set of axioms** includes:

- GCIs and RIAs: $C \sqsubseteq D, R \sqsubseteq R', R \circ R \sqsubseteq R$
- Assertions: $C(a), r(a, b)$

(Peanut \sqsubseteq Substance) $(\exists \text{sensitiveTo} . \Diamond_p \text{Nut})(p)$



Towards Standpoint- \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I, N_S \rangle$ of concept, role, individual and **standpoint** names, $* \in N_S$ (universal standpoint).

Syntax:

The **set of concepts** is given by

$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r. C \mid \exists \leq nr. C \mid \odot_s C$

With $A \in N_C, r \in N_R, s \in N_S, \odot \in \{\Box, \Diamond\}$.

Substance $\exists \text{sensitiveTo} . \text{Nut}$ $\Diamond_s \text{Dangerous}$
 Substance $\sqcap \neg \text{Dangerous}$ $\exists \leq 1 \text{sensitiveTo} . \text{Substance}$

Formulas are $\odot_s (\lambda_1 \wedge \dots \wedge \lambda_n)$ for $\lambda_i \in \{\mathcal{E}, \neg \mathcal{E}\}$, \mathcal{E} :

- GCIs and RIAs: $C \sqsubseteq D, R \sqsubseteq R', R \circ R \sqsubseteq R$
- Assertions: $C(a), r(a, b)$

$\Box_L (\text{Peanut} \sqsubseteq \text{Substance}) \quad \Box_L (\exists \text{sensitiveTo} . \Diamond_p \text{Nut})(p)$



Towards Standpoint- \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I, N_S \rangle$ of concept, role, individual and **standpoint** names, $* \in N_S$ (universal standpoint).

Syntax:

The **set of concepts** is given by

$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r. C \mid \exists \leq nr. C \mid \odot_s C$

With $A \in N_C, r \in N_R, s \in N_S, \odot \in \{\Box, \Diamond\}$.

Substance $\exists \text{sensitiveTo} . \text{Nut}$ $\Diamond_s \text{Dangerous}$
 Substance $\sqcap \neg \text{Dangerous}$ $\exists \leq 1 \text{sensitiveTo} . \text{Substance}$

Formulas are $\odot_s (\lambda_1 \wedge \dots \wedge \lambda_n)$ for $\lambda_i \in \{\mathcal{E}, \neg \mathcal{E}\}$, \mathcal{E} :

- GCIs and RIAs: $C \sqsubseteq D, R \sqsubseteq R', R \circ R \sqsubseteq R$
- Assertions: $C(a), r(a, b)$

$\Box_L (\text{Peanut} \sqsubseteq \text{Substance}) \quad \Box_L (\exists \text{sensitiveTo} . \Diamond_p \text{Nut})(p)$

Semantics: $\mathcal{D} = \langle \Delta, \Pi, \sigma, \gamma \rangle$



Towards Standpoint- \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I, N_S \rangle$ of concept, role, individual and **standpoint** names, $*$ $\in N_S$ (universal standpoint).

Syntax:

The **set of concepts** is given by

$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r. C \mid \exists \leq nr. C \mid \odot_s C$

With $A \in N_C, r \in N_R, s \in N_S, \odot \in \{\square, \diamond\}$.


Substance $\exists \text{sensitiveTo} . \text{Nut}$ $\diamond_s \text{Dangerous}$
 Substance $\sqcap \neg \text{Dangerous}$ $\exists \leq 1 \text{sensitiveTo} . \text{Substance}$

Formulas are $\odot_s (\lambda_1 \wedge \dots \wedge \lambda_n)$ for $\lambda_i \in \{\mathcal{E}, \neg \mathcal{E}\}$, \mathcal{E} :

- GCIs and RIAs: $C \sqsubseteq D$, $R \sqsubseteq R'$, $R \circ R \sqsubseteq R$
- Assertions: $C(a)$, $r(a, b)$

$\square_L (\text{Peanut} \sqsubseteq \text{Substance})$ $\square_L (\exists \text{sensitiveTo} . \diamond_p \text{Nut})(p)$

Semantics: $\mathcal{D} = \langle \Delta, \Pi, \sigma, \gamma \rangle$



Towards Standpoint- \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I, N_S \rangle$ of concept, role, individual and **standpoint** names, $* \in N_S$ (universal standpoint).

Syntax:

The **set of concepts** is given by

$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r. C \mid \exists \leq nr. C \mid \odot_s C$

With $A \in N_C, r \in N_R, s \in N_S, \odot \in \{ \Box, \Diamond \}$.


Substance $\exists \text{sensitiveTo} . \text{Nut}$ $\Diamond_s \text{Dangerous}$
 Substance $\sqcap \neg \text{Dangerous}$ $\exists \leq 1 \text{sensitiveTo} . \text{Substance}$

Formulas are $\odot_s (\lambda_1 \wedge \dots \wedge \lambda_n)$ for $\lambda_i \in \{ \mathcal{E}, \neg \mathcal{E} \}$, \mathcal{E} :

- GCIs and RIAs: $C \sqsubseteq D, R \sqsubseteq R', R \circ R \sqsubseteq R$
- Assertions: $C(a), r(a, b)$

$\Box_L (\text{Peanut} \sqsubseteq \text{Substance}) \quad \Box_L (\exists \text{sensitiveTo} . \Diamond_p \text{Nut})(p)$

Semantics: $\mathcal{D} = \langle \Delta, \Pi, \sigma, \gamma \rangle$



Towards Standpoint- \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I, N_S \rangle$ of concept, role, individual and **standpoint** names, $* \in N_S$ (universal standpoint).

Syntax:

The **set of concepts** is given by

$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r. C \mid \exists \leq nr. C \mid \odot_s C$

With $A \in N_C, r \in N_R, s \in N_S, \odot \in \{\square, \diamond\}$.


Substance $\exists \text{sensitiveTo} . \text{Nut}$ $\diamond_s \text{Dangerous}$
 Substance $\sqcap \neg \text{Dangerous}$ $\exists \leq 1 \text{sensitiveTo} . \text{Substance}$

Formulas are $\odot_s (\lambda_1 \wedge \dots \wedge \lambda_n)$ for $\lambda_i \in \{\mathcal{E}, \neg \mathcal{E}\}$, \mathcal{E} :

- GCIs and RIAs: $C \sqsubseteq D$, $R \sqsubseteq R'$, $R \circ R \sqsubseteq R$
- Assertions: $C(a)$, $r(a, b)$

$\square_L (\text{Peanut} \sqsubseteq \text{Substance})$ $\square_L (\exists \text{sensitiveTo} . \diamond_p \text{Nut})(p)$

Semantics: $\mathcal{D} = \langle \Delta, \Pi, \sigma, \gamma \rangle$



Towards Standpoint- \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I, N_S \rangle$ of concept, role, individual and **standpoint** names, $* \in N_S$ (universal standpoint).

Syntax:

The **set of concepts** is given by

$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r. C \mid \exists \leq nr. C \mid \odot_s C$

With $A \in N_C, r \in N_R, s \in N_S, \odot \in \{\square, \diamond\}$.

Substance $\exists \text{sensitiveTo} . \text{Nut}$ $\diamond_s \text{Dangerous}$
 Substance $\sqcap \neg \text{Dangerous}$ $\exists \leq 1 \text{sensitiveTo} . \text{Substance}$


Formulas are $\odot_s (\lambda_1 \wedge \dots \wedge \lambda_n)$ for $\lambda_i \in \{\mathcal{E}, \neg \mathcal{E}\}$, \mathcal{E} :

- GCIs and RIAs: $C \sqsubseteq D$, $R \sqsubseteq R'$, $R \circ R \sqsubseteq R$
- Assertions: $C(a)$, $r(a, b)$

$\square_L (\text{Peanut} \sqsubseteq \text{Substance})$ $\square_L (\exists \text{sensitiveTo} . \diamond_p \text{Nut})(p)$

Semantics: $\mathcal{D} = \langle \Delta, \Pi, \sigma, \gamma \rangle$

- γ maps each $\pi \in \Pi$ to a \mathcal{SHIQ} interpretation $\mathcal{I} = \langle \Delta, \cdot^{\mathcal{I}} \rangle$



Towards Standpoint- \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I, N_S \rangle$ of concept, role, individual and **standpoint** names, $* \in N_S$ (universal standpoint).

Syntax:

The **set of concepts** is given by

$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r. C \mid \exists \leq nr. C \mid \odot_s C$

With $A \in N_C, r \in N_R, s \in N_S, \odot \in \{\square, \diamond\}$.

Substance $\exists \text{sensitiveTo} . \text{Nut}$ $\diamond_s \text{Dangerous}$
 Substance $\sqcap \neg \text{Dangerous}$ $\exists \leq 1 \text{sensitiveTo} . \text{Substance}$


Formulas are $\odot_s (\lambda_1 \wedge \dots \wedge \lambda_n)$ for $\lambda_i \in \{\mathcal{E}, \neg \mathcal{E}\}$, \mathcal{E} :

- GCIs and RIAs: $C \sqsubseteq D$, $R \sqsubseteq R'$, $R \circ R \sqsubseteq R$
- Assertions: $C(a)$, $r(a, b)$

$\square_L (\text{Peanut} \sqsubseteq \text{Substance})$ $\square_L (\exists \text{sensitiveTo} . \diamond_p \text{Nut})(p)$

Semantics: $\mathcal{D} = \langle \Delta, \Pi, \sigma, \gamma \rangle$

- γ maps each $\pi \in \Pi$ to a \mathcal{SHIQ} interpretation $\mathcal{I} = \langle \Delta, \cdot^{\mathcal{I}} \rangle$
- σ maps each $s \in N_S$ to a subset of Π



Towards Standpoint- \mathcal{SHIQ}

Vocabulary $\langle N_C, N_R, N_I, N_S \rangle$ of concept, role, individual and **standpoint** names, $* \in N_S$ (universal standpoint).

Syntax:

The **set of concepts** is given by

$C ::= \top \mid A \mid \neg C \mid C_1 \sqcap C_2 \mid \exists r. C \mid \exists \leq nr. C \mid \odot_s C$

With $A \in N_C, r \in N_R, s \in N_S, \odot \in \{\square, \diamond\}$.

Substance $\exists \text{sensitiveTo} . \text{Nut}$ $\diamond_s \text{Dangerous}$
 Substance $\sqcap \neg \text{Dangerous}$ $\exists \leq 1 \text{sensitiveTo} . \text{Substance}$


Formulas are $\odot_s (\lambda_1 \wedge \dots \wedge \lambda_n)$ for $\lambda_i \in \{\mathcal{E}, \neg \mathcal{E}\}$, \mathcal{E} :

- GCIs and RIAs: $C \sqsubseteq D$, $R \sqsubseteq R'$, $R \circ R \sqsubseteq R$
- Assertions: $C(a)$, $r(a, b)$

$\square_L (\text{Peanut} \sqsubseteq \text{Substance})$ $\square_L (\exists \text{sensitiveTo} . \diamond_P \text{Nut})(p)$

Semantics: $\mathcal{D} = \langle \Delta, \Pi, \sigma, \gamma \rangle$

- γ maps each $\pi \in \Pi$ to a \mathcal{SHIQ} interpretation $\mathcal{I} = \langle \Delta, \cdot^{\mathcal{I}} \rangle$
- σ maps each $s \in N_S$ to a subset of Π



Small Models for Standpoint \mathcal{SHIQ}



Small model property for $\mathcal{S}_{\mathcal{SHIQ}}$

Normalisation:

- Sharpenings not using 0:

$$- s' \preceq s \qquad s_1 \cap s_2 \preceq s$$

- GCIs:

$$- \Box_s (T \sqsubseteq C) \qquad \text{with } C \text{ in NNF}$$

- Other modalised axioms :

$$- \Box_s \xi \qquad \text{with } \xi \text{ any RI, transitivity axiom, role assertion, or concept assertion } C(a) \text{ with } C \text{ in NNF}$$

Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

Normalisation:

- Sharpenings not using 0:
 - $s' \preceq s$ $s_1 \cap s_2 \preceq s$
- GCIs:
 - $\Box_s (T \sqsubseteq C)$ with C in NNF
- Other modalised axioms :
 - $\Box_s \xi$ with ξ any RI, transitivity axiom, role assertion, or concept assertion $C(a)$ with C in NNF

Lemma 1. *Any $\mathbb{S}_{\mathcal{SHIQ}}$ KB \mathcal{K} can be transformed into a KB in normal form \mathcal{K}' such that*

- \mathcal{K} and \mathcal{K}' are equisatisfiable
- \mathcal{K}' is linear in the size of \mathcal{K}
- \mathcal{K}' can be computed in PTime

Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

Normalisation:

- Sharpenings not using 0:
 - $s' \preceq s$ $s_1 \cap s_2 \preceq s$
- GCIs:
 - $\Box_s (T \sqsubseteq C)$ with C in NNF
- Other modalised axioms :
 - $\Box_s \xi$ with ξ any RI, transitivity axiom, role assertion, or concept assertion $C(a)$ with C in NNF

Lemma 1. Any $\mathbb{S}_{\mathcal{SHIQ}}$ KB \mathcal{K} can be transformed into a KB in normal form \mathcal{K}' such that

- \mathcal{K} and \mathcal{K}' are equisatisfiable
- \mathcal{K}' is linear in the size of \mathcal{K}
- \mathcal{K}' can be computed in PTime

Notice that \Diamond_s only occurs at the concept level

Small model property for \mathcal{S}_{SHIQ}


Small model property for \mathcal{S}_{SHIQ}

Tidy models

Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

Tidy models

$$\mathcal{K} = \{ \Box_{\star} (\top \sqsubseteq D), \\ \Box_{\star} (\top \sqsubseteq \Diamond_{\star} C) \}$$




Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

Tidy models

Intuitively, we want to pick the necessary elements from \mathcal{D}^o :

$$\mathcal{K} = \{ \Box_{\star} (\top \sqsubseteq D), \Box_{\star} (\top \sqsubseteq \Diamond_{\star} C) \}$$




Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

Tidy models

Intuitively, we want to pick the necessary elements from \mathcal{D}^o :

- Witness standpoint non-emptiness
- Witness $\Diamond_s C$ membership

$$\mathcal{K} = \{ \Box_\star (\top \sqsubseteq D), \Box_\star (\top \sqsubseteq \Diamond_\star C) \}$$




Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

Tidy models

Intuitively, we want to pick the necessary elements from \mathcal{D}^o :

- Witness standpoint non-emptiness
 \Rightarrow From \mathcal{D}^o , take one π from each s
- Witness $\Diamond_s C$ membership

$$\mathcal{K} = \{ \Box_\star (\top \sqsubseteq D), \Box_\star (\top \sqsubseteq \Diamond_\star C) \}$$



Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

Tidy models


\mathcal{D} is *tidy* if $\Pi_{\mathcal{K}}$ consists of:

- π_s for every standpoint s

Intuitively, we want to pick the necessary elements from \mathcal{D}^o :

- Witness standpoint non-emptiness
 \Rightarrow From \mathcal{D}^o , take one π from each s
- Witness $\Diamond_s C$ membership

$$\mathcal{K} = \{ \Box_{\star} (\top \sqsubseteq D), \\ \Box_{\star} (\top \sqsubseteq \Diamond_{\star} C) \}$$




Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

Tidy models

\mathcal{D} is *tidy* if $\Pi_{\mathcal{K}}$ consists of:


- π_s for every standpoint s
- Witness standpoint non-emptiness
 \Rightarrow From \mathcal{D}^o , take one π from each s
- Witness $\Diamond_s C$ membership
 - How do we pick witnesses?

$$\mathcal{K} = \{ \Box_{\star} (T \sqsubseteq D), \Box_{\star} (T \sqsubseteq \Diamond_{\star} C) \}$$



Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

$$\mathcal{K} = \{ \Box_{\star} (\top \sqsubseteq D), \Box_{\star} (\top \sqsubseteq \Diamond_{\star} C) \}$$



Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$


Tidy models

\mathcal{D} is *tidy* if $\Pi_{\mathcal{K}}$ consists of:

- π_s for every standpoint s

For witnessing $\Diamond_s C$ membership:

$$\mathcal{K} = \{ \Box_{\star} (\top \sqsubseteq D), \\ \Box_{\star} (\top \sqsubseteq \Diamond_{\star} C) \}$$



Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

Tidy models


\mathcal{D} is *tidy* if $\Pi_{\mathcal{K}}$ consists of:

- π_s for every standpoint s
- $\pi_{s,C}^a$ for each $\Diamond_s C$ and a

For witnessing $\Diamond_s C$ membership:

- A witness for each **named individual** a

$$\mathcal{K} = \{ \Box_{\star} (\top \sqsubseteq D), \Box_{\star} (\top \sqsubseteq \Diamond_{\star} C) \}$$



Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

Tidy models


\mathcal{D} is *tidy* if $\Pi_{\mathcal{K}}$ consists of:

- π_s for every standpoint s
- $\pi_{s,C}^a$ for each $\Diamond_s C$ and a

For witnessing $\Diamond_s C$ membership:

- A witness for each **named individual** a
- For **unnamed individuals**:

$$\mathcal{K} = \{ \Box_{\star} (\top \sqsubseteq D), \Box_{\star} (\top \sqsubseteq \Diamond_{\star} C) \}$$



Small model property for \mathcal{S}_{SHIQ}

Tidy models


\mathcal{D} is *tidy* if $\Pi_{\mathcal{K}}$ consists of:

- π_s for every standpoint s
- $\pi_{s,C}^a$ for each $\Diamond_s C$ and a

For witnessing $\Diamond_s C$ membership:

- A witness for each **named individual** a
- For **unnamed individuals**:

$$\mathcal{K} = \{ \Box_{\star} (\top \sqsubseteq D), \Box_{\star} (\top \sqsubseteq \Diamond_{\star} C) \}$$



- ❖ in SHIQ, the disjoint union of two or more models will be a model again
- ❖ many precisifications can co-exist inside one precisification!

Small model property for \mathcal{S}_{SHIQ}

Tidy models


\mathcal{D} is *tidy* if $\Pi_{\mathcal{K}}$ consists of:

- π_s for every standpoint s
- $\pi_{s,C}^a$ for each $\Diamond_s C$ and a
- $\pi_{s,C}^0, \pi_{s,C}^1$ for each $\Diamond_s C$

For witnessing $\Diamond_s C$ membership:

- A witness for each **named individual** a
- For **unnamed individuals**:
 - ➔ Squeeze infinite copies of all s precisifications
 - ➔ Arrange them so for each δ , either $\pi_{s,C}^0$ or $\pi_{s,C}^1$ deals with the $\Diamond_s C$ membership


$$\mathcal{K} = \{ \Box_{\star} (\top \sqsubseteq D), \Box_{\star} (\top \sqsubseteq \Diamond_{\star} C) \}$$



- ❖ in SHIQ, the disjoint union of two or more models will be a model again
- ❖ many precisifications can co-exist inside one precisification!


Small model property for $\mathcal{S}_{\mathcal{SHIQ}}$

$$\mathcal{K} = \{ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{\text{GP}} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{\text{GP}} \text{Allergy}) \}$$



Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$


$$\mathcal{K} = \{ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{\text{GP}} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{\text{GP}} \text{Allergy}) \}$$



Δ

Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$


$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$



$$\Delta <\delta_1, 0> <\delta_2, 0> <\delta_3, 0>$$

Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$


$$\mathcal{K} = \{ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{\text{GP}} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{\text{GP}} \text{Allergy}) \}$$



$$\Delta \quad \langle \delta_1, 0 \rangle \quad \langle \delta_2, 0 \rangle \quad \langle \delta_3, 0 \rangle \quad \langle \delta_1, 1 \rangle \quad \langle \delta_2, 1 \rangle \quad \langle \delta_3, 1 \rangle$$

Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$


$$\mathcal{K} = \{ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{\text{GP}} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{\text{GP}} \text{Allergy}) \}$$



$$\Delta \quad \langle \delta_1, 0 \rangle \quad \langle \delta_2, 0 \rangle \quad \langle \delta_3, 0 \rangle \quad \langle \delta_1, 1 \rangle \quad \langle \delta_2, 1 \rangle \quad \langle \delta_3, 1 \rangle \quad \langle \delta_1, 2 \rangle \quad \langle \delta_2, 2 \rangle \quad \langle \delta_3, 2 \rangle$$

Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$


$$\mathcal{K} = \{ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{\text{GP}} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{\text{GP}} \text{Allergy}) \}$$



$$\Delta \quad \langle \delta_1, 0 \rangle \quad \langle \delta_2, 0 \rangle \quad \langle \delta_3, 0 \rangle \quad \langle \delta_1, 1 \rangle \quad \langle \delta_2, 1 \rangle \quad \langle \delta_3, 1 \rangle \quad \langle \delta_1, 2 \rangle \quad \langle \delta_2, 2 \rangle \quad \langle \delta_3, 2 \rangle \quad \langle \delta_1, 3 \rangle \quad \langle \delta_2, 3 \rangle \quad \langle \delta_3, 3 \rangle$$

Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$


$$\mathcal{K} = \{ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{\text{GP}} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{\text{GP}} \text{Allergy}) \}$$



$$\Delta \quad <\delta_1,0> \quad <\delta_2,0> \quad <\delta_3,0> \quad <\delta_1,1> \quad <\delta_2,1> \quad <\delta_3,1> \quad <\delta_1,2> \quad <\delta_2,2> \quad <\delta_3,2> \quad <\delta_1,3> \quad <\delta_2,3> \quad <\delta_3,3> \dots$$


Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$



Small model property for $\mathcal{S}_{\mathcal{SHIQ}}$


$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$



Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

$$\mathcal{K} = \{ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{\text{GP}} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{\text{ED}} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{\text{GP}} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$	\dots
π_{ED}	δ_1	$\pi_1, 0$	$\pi_1, 1$	$\pi_1, 2$	$\pi_1, 3$	
	δ_2	$\pi_1, 0$	$\pi_1, 1$	$\pi_1, 2$	$\pi_1, 3$	
	δ_3	$\pi_1, 0$	$\pi_1, 1$	$\pi_1, 2$	$\pi_1, 3$	
π_{GP}	δ_1	$\pi_4, 0$	$\pi_4, 1$	$\pi_4, 2$	$\pi_4, 3$	
	δ_2	$\pi_4, 0$	$\pi_4, 1$	$\pi_4, 2$	$\pi_4, 3$	
	δ_3	$\pi_4, 0$	$\pi_4, 1$	$\pi_4, 2$	$\pi_4, 3$	



Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Small model property for $\mathcal{S}_{\mathcal{SHIQ}}$

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Small model property for $\mathcal{S}_{\mathcal{SHIQ}}$

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Small model property for \mathcal{S}_{SHIQ}

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Small model property for \mathcal{S}_{SHIQ}

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Small model property for \mathcal{S}_{SHIQ}

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Small model property for \mathcal{S}_{SHIQ}

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Small model property for $\mathbb{S}_{\mathcal{SHIQ}}$

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Small model property for $\mathcal{S}_{\mathcal{SHIQ}}$

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Small model property for $\mathcal{S}_{\mathcal{SHIQ}}$

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Small model property for $\mathcal{S}_{\mathcal{SHIQ}}$

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Small model property for \mathcal{S}_{SHIQ}

$$\mathcal{K} = \{ \square_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \square_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \square_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \diamond_{GP} \text{Allergy}) \}$$


Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Small model property for $\mathcal{S}_{\mathcal{SHIQ}}$

$$\mathcal{K} = \{ \Box_{ED} (\text{Allergy} \sqsubseteq \text{AntibodyRelease}), \\ \Box_{GP} (\text{Allergy} \sqsubseteq = 1\text{SensitivityTo} . \text{Substance}), \\ \Box_{ED} (\text{Allergy} \sqsubseteq \exists \text{TriggeredBy} . \Diamond_{GP} \text{Allergy}) \}$$

Π	Δ	$f(\pi, \delta, k), g(\pi, \delta, k)$				
		$k = 0$	$k = 1$	$k = 2$	$k = 3$...
$\pi_{GP, Allergy}^0$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_3, 0$	$\pi_5, 0$	$\pi_4, 0$	$\pi_5, 1$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
$\pi_{GP, Allergy}^1$	δ_1	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	
	δ_2	$\pi_5, 0$	$\pi_3, 0$	$\pi_5, 1$	$\pi_4, 0$	
	δ_3	$\pi_3, 0$	$\pi_4, 0$	$\pi_5, 0$	$\pi_3, 1$	



Future Research Goals and Challenges

Future Research Goals and Challenges

Goal: towards a viable framework for reasoning with heterogeneous knowledge communities

Future Research Goals and Challenges

Goal: towards a viable framework for reasoning with heterogeneous knowledge communities

Objectives:

Future Research Goals and Challenges

Goal: towards a viable framework for reasoning with heterogeneous knowledge communities

Objectives:

(O1) Decidability and
complexity

Future Research Goals and Challenges

Goal: towards a viable framework for reasoning with heterogeneous knowledge communities

Objectives:




(O1) Decidability and
complexity

(O2) Efficient algorithms and
implementations

Future Research Goals and Challenges

Goal: towards a viable framework for reasoning with heterogeneous knowledge communities


Objectives:



Future Research Goals and Challenges

Goal: towards a viable framework for reasoning with heterogeneous knowledge communities

Objectives:




Challenge: Expressivity — Efficiency trade-off

Future Research Goals and Challenges

Goal: towards a viable framework for reasoning with heterogeneous knowledge communities

Objectives:




Challenge: Expressivity — Efficiency trade-off

* Knowledge available is highly diverse

Future Research Goals and Challenges

Goal: towards a viable framework for reasoning with heterogeneous knowledge communities

Objectives:




Challenge: Expressivity — Efficiency trade-off

- * Knowledge available is highly diverse
- * Multi-perspective frameworks give rise to complex reasoning tasks

Future Research Goals and Challenges

Goal: towards a viable framework for reasoning with heterogeneous knowledge communities

Objectives:



Challenge: Expressivity — Efficiency trade-off

- * Knowledge available is highly diverse
- * Multi-perspective frameworks give rise to complex reasoning tasks
- * The Semantic Web contains extremely large knowledge sources