

Implementing the Core Chase for **Horn- \mathcal{ALCH}**

Internship supervised by:
Jean-François Baget and David Carral
INRIA, Montpellier, GRAPHIK team

Maël Abily

2021

Entailment: a fundamental problem in knowledge representation

Conjunctive query entailment problem

Determine if the knowledge base K entails the query Q

Entailment: a fundamental problem in knowledge representation

Conjunctive query entailment problem

Determine if the knowledge base K entails the query Q

Knowledge base $K =$

Rules	Facts (Initial Factbase)
$\alpha = \text{Mother}(x) \rightarrow \text{Parent}(x)$	$\text{Mother}(\mathbf{Marie})$
$\beta = \text{Parent}(x) \rightarrow \exists y. \text{IsTheParentOf}(x, y)$	$\text{IsTheSisterOf}(\mathbf{Marie}, x)$
$\gamma = \text{IsTheParentOf}(x, y) \rightarrow \text{Human}(y)$	

Entailment: a fundamental problem in knowledge representation

Conjunctive query entailment problem

Determine if the knowledge base K entails the query Q

Knowledge base $K =$

Rules	Facts (Initial Factbase)
$\alpha = \text{Mother}(x) \rightarrow \text{Parent}(x)$	$\text{Mother}(\mathbf{Marie})$
$\beta = \text{Parent}(x) \rightarrow \exists y. \text{IsTheParentOf}(x, y)$	$\text{IsTheSisterOf}(\mathbf{Marie}, x)$
$\gamma = \text{IsTheParentOf}(x, y) \rightarrow \text{Human}(y)$	

Query $Q = \{\text{IsTheParentOf}(\mathbf{Marie}, x), \text{Human}(x)\}$

One of the solution to resolve the conjunctive query entailment problem:

The Chase

Knowledge base $K =$

$\alpha = \text{Mother}(x) \rightarrow \text{Parent}(x)$ $\beta = \text{Parent}(x) \rightarrow \exists y. \text{IsTheParentOf}(x, y)$ $\gamma = \text{IsTheParentOf}(x, y) \rightarrow \text{Human}(y)$	$\text{Mother}(\mathbf{Marie})$
---	---------------------------------

Query $Q = \{ \text{IsTheParentOf}(\mathbf{Marie}, x), \text{Human}(x) \}$

One of the solution to resolve the conjunctive query entailment problem:

The Chase

Knowledge base $K =$

$\alpha = \text{Mother}(x) \rightarrow \text{Parent}(x)$ $\beta = \text{Parent}(x) \rightarrow \exists y. \text{IsTheParentOf}(x, y)$ $\gamma = \text{IsTheParentOf}(x, y) \rightarrow \text{Human}(y)$	$\text{Mother}(\mathbf{Marie})$ $\text{Parent}(\mathbf{Marie})$
---	--

Query $Q = \{ \text{IsTheParentOf}(\mathbf{Marie}, x), \text{Human}(x) \}$

One of the solution to resolve the conjunctive query entailment problem: The Chase

Knowledge base $K =$

$\alpha = \text{Mother}(x) \rightarrow \text{Parent}(x)$	$\text{Mother}(\mathbf{Marie})$
$\beta = \text{Parent}(x) \rightarrow \exists y. \text{IsTheParentOf}(x, y)$	$\text{Parent}(\mathbf{Marie})$
$\gamma = \text{IsTheParentOf}(x, y) \rightarrow \text{Human}(y)$	$\text{IsTheParentOf}(\mathbf{Marie}, y_0)$

$$y_0 = f_{\beta}^y(\mathbf{Marie})$$

Query $Q = \{\text{IsTheParentOf}(\mathbf{Marie}, x), \text{Human}(x)\}$

One of the solution to resolve the conjunctive query entailment problem:

The Chase

Knowledge base $K =$

$\alpha = \text{Mother}(x) \rightarrow \text{Parent}(x)$	$\text{Mother}(\mathbf{Marie})$
$\beta = \text{Parent}(x) \rightarrow \exists y. \text{IsTheParentOf}(x, y)$	$\text{Parent}(\mathbf{Marie})$
$\gamma = \text{IsTheParentOf}(x, y) \rightarrow \text{Human}(y)$	$\text{IsTheParentOf}(\mathbf{Marie}, y_0)$
	$\text{Human}(y_0)$

$$y_0 = f_{\beta}^y(\mathbf{Marie})$$

Query $Q = \{\text{IsTheParentOf}(\mathbf{Marie}, x), \text{Human}(x)\}$

One of the solution to resolve the conjunctive query entailment problem:

The Chase

Knowledge base $K =$

$\alpha = \text{Mother}(x) \rightarrow \text{Parent}(x)$ $\beta = \text{Parent}(x) \rightarrow \exists y. \text{IsTheParentOf}(x, y)$ $\gamma = \text{IsTheParentOf}(x, y) \rightarrow \text{Human}(y)$	$\text{Mother}(\mathbf{Marie})$ $\text{Parent}(\mathbf{Marie})$ $\text{IsTheParentOf}(\mathbf{Marie}, y_0)$ $\text{Human}(y_0)$
---	--

$$y_0 = f_{\beta}^y(\mathbf{Marie})$$

Query $Q = \{\text{IsTheParentOf}(\mathbf{Marie}, x), \text{Human}(x)\}$

• $\xrightarrow{\text{IsTheParentOf}} y_0: \text{Human}$

Marie: Mother, Parent

The chase computes a universal model

Definition


A factbase U is a universal model of a knowledge base K if for every query Q , K entails Q if and only if U entails Q .

Theorem

For a knowledge base K , the result of the oblivious chase on K is an universal model of K .

The oblivious chase


one rule: $\alpha = R(x, y) \rightarrow \exists z. R(y, z) \wedge R(z, y)$ where $R = \text{IsTheFriendOf}$
two facts: $R(\mathbf{Francis}, \mathbf{Bob}), R(\mathbf{Bob}, \mathbf{Francis})$



The oblivious chase

one rule: $\alpha = R(x, y) \rightarrow \exists z. R(y, z) \wedge R(z, y)$ where $R = \text{IsTheFriendOf}$

two facts: $R(\mathbf{Francis}, \mathbf{Bob}), R(\mathbf{Bob}, \mathbf{Francis})$




$$z_1 = f_{\alpha}^z(\mathbf{Francis}, \mathbf{Bob})$$

The oblivious chase

one rule: $\alpha = R(x, y) \rightarrow \exists z. R(y, z) \wedge R(z, y)$ where $R = \text{IsTheFriendOf}$

two facts: $R(\mathbf{Francis}, \mathbf{Bob}), R(\mathbf{Bob}, \mathbf{Francis})$




$$z_1 = f_{\alpha}^Z(\mathbf{Francis}, \mathbf{Bob})$$

$$z_2 = f_{\alpha}^Z(\mathbf{Bob}, z_1)$$

The oblivious chase

one rule: $\alpha = R(x, y) \rightarrow \exists z. R(y, z) \wedge R(z, y)$ where $R = \text{IsTheFriendOf}$
two facts: $R(\mathbf{Francis}, \mathbf{Bob}), R(\mathbf{Bob}, \mathbf{Francis})$



$$z_1 = f_{\alpha}^Z(\mathbf{Francis}, \mathbf{Bob})$$

$$z_2 = f_{\alpha}^Z(\mathbf{Bob}, z_1)$$

The core chase

Definition

A core of a factbase F is one of the minimal subset of F that is logically equivalent to F .

For example, if $F = \{Human(x), Human(\mathbf{Marie})\}$, then $Core(F) = \{Human(\mathbf{Marie})\}$.

The core chase


Definition

A core of a factbase F is one of the minimal subset of F that is logically equivalent to F .

one rule: $\alpha = R(x, y) \rightarrow \exists z. R(y, z) \wedge R(z, y)$

two facts: $R(\mathbf{Francis}, \mathbf{Bob}), R(\mathbf{Bob}, \mathbf{Francis})$

$z_1 = f_\alpha^z(\mathbf{Francis}, \mathbf{Bob}), z_0 = f_\alpha^z(\mathbf{Bob}, \mathbf{Francis})$



The core chase


Definition

A core of a factbase F is one of the minimal subset of F that is logically equivalent to F .

one rule: $\alpha = R(x, y) \rightarrow \exists z. R(y, z) \wedge R(z, y)$

two facts: $R(\mathbf{Francis}, \mathbf{Bob}), R(\mathbf{Bob}, \mathbf{Francis})$

$z_1 = f_\alpha^z(\mathbf{Francis}, \mathbf{Bob}), z_0 = f_\alpha^z(\mathbf{Bob}, \mathbf{Francis})$



The core chase


Definition

A core of a factbase F is one of the minimal subset of F that is logically equivalent to F .

one rule: $\alpha = R(x, y) \rightarrow \exists z. R(y, z) \wedge R(z, y)$

two facts: $R(\mathbf{Francis}, \mathbf{Bob}), R(\mathbf{Bob}, \mathbf{Francis})$

$z_1 = f_\alpha^z(\mathbf{Francis}, \mathbf{Bob}), z_0 = f_\alpha^z(\mathbf{Bob}, \mathbf{Francis})$



The core chase


Definition

A core of a factbase F is one of the minimal subset of F that is logically equivalent to F .

one rule: $\alpha = R(x, y) \rightarrow \exists z. R(y, z) \wedge R(z, y)$

two facts: $R(\mathbf{Francis}, \mathbf{Bob}), R(\mathbf{Bob}, \mathbf{Francis})$

$z_1 = f_\alpha^z(\mathbf{Francis}, \mathbf{Bob}), z_0 = f_\alpha^z(\mathbf{Bob}, \mathbf{Francis})$



The core chase


Definition

A core of a factbase F is one of the minimal subset of F that is logically equivalent to F .

one rule: $\alpha = R(x, y) \rightarrow \exists z. R(y, z) \wedge R(z, y)$

two facts: $R(\mathbf{Francis}, \mathbf{Bob}), R(\mathbf{Bob}, \mathbf{Francis})$

$z_1 = f_\alpha^z(\mathbf{Francis}, \mathbf{Bob}), z_0 = f_\alpha^z(\mathbf{Bob}, \mathbf{Francis})$



The core chase


Definition

A core of a factbase F is one of the minimal subset of F that is logically equivalent to F .

one rule: $\alpha = R(x, y) \rightarrow \exists z. R(y, z) \wedge R(z, y)$

two facts: $R(\mathbf{Francis}, \mathbf{Bob}), R(\mathbf{Bob}, \mathbf{Francis})$

$z_1 = f_\alpha^z(\mathbf{Francis}, \mathbf{Bob}), z_0 = f_\alpha^z(\mathbf{Bob}, \mathbf{Francis})$



The core chase is the best in term of terminaison

Theorem

The knowledge base K admits a finite universal model if and only if the core chase terminates on K . In this case, the core chase computes a universal model.

The goals of my internship

- The core chase is hard to compute but it terminates more often.
- Computing the core of a factbase is NP-complete.

The goals of my internship

- The core chase is hard to compute but it terminates more often.
- Computing the core of a factbase is NP-complete.
- Identify a fragment of rules such that we can quickly compute the core.
- Give an algorithm.
- Prove the correctness and the completeness of the algorithm.

Our restriction: **Horn- \mathcal{ALCH}**

The rules are of the form:

$$A(x) \rightarrow \exists y. R(x, y) \wedge B(y) \quad (1)$$

$$A(x) \wedge B(x) \rightarrow C(x) \quad (2)$$


$$A(x) \wedge R(x, y) \rightarrow B(y) \quad (3)$$

$$R(x, y) \wedge B(y) \rightarrow A(x) \quad (4)$$


$$R(x, y) \wedge S(x, y) \rightarrow V(x, y) \quad (5)$$

The saturation of the initial factbase will create facts that have a tree shape.

Example




Example




$$A(x) \rightarrow \exists y. R(x, y) \wedge B(y)$$

Example




$$A(x) \rightarrow \exists y. R(x, y) \wedge B(y)$$

Example




$$A(x) \wedge B(x) \rightarrow C(x)$$

Example




$$A(x) \wedge R(x, y) \rightarrow B(y)$$

Example



$$R(x, y) \wedge B(y) \rightarrow A(x)$$


Example



$$R(x, y) \wedge S(x, y) \rightarrow V(x, y)$$


A better algorithm in this restriction: The merge chase

The variable z is mergeable on the term t :



A better algorithm in this restriction: The merge chase

The variable z is mergeable on the term t :




Theorem

If the variable z is mergeable on the term t , the facts generated on z can be generated on t .

A better algorithm in this restriction: The merge chase

The variable z is mergeable on the term t :




Theorem

If the variable z is mergeable on the term t , the facts generated on z can be generated on t .


A better algorithm in this restriction: The merge chase

The atomic merge




A better algorithm in this restriction: The merge chase

The atomic merge




A better algorithm in this restriction: The merge chase

The atomic merge



A better algorithm in this restriction: The merge chase


The atomic merge



The merge

Definition

For a factbase F , $Merge(F)$ is obtained by applying all the possible atomic mergings on F .



The merge chase

Theorem

For a factbase F , $\text{Merge}(F)$ is a core.


Definition

The merge chase for a **Horn- \mathcal{ALCH}** knowledge base K is the core chase where we replace the computation of a core by the merge operation.


Corollary

*The **Horn- \mathcal{ALCH}** knowledge base K admits a finite universal model if and only if the merge chase terminates on K . In this case, the merge chase computes a universal model.*


The atomic merging operation has to be applied exhaustively




The atomic merging operation has to be applied exhaustively




The atomic merging operation has to be applied exhaustively




The atomic merging operation has to be applied exhaustively



The atomic merging operation has to be applied exhaustively



The atomic merging operation has to be applied exhaustively



- Theoretical study of an alternative of the core chase in **Horn- \mathcal{ALCH}**
 - define the merging operation;
 - prove the correctness and completeness of the merge chase;

Conclusion

- Theoretical study of an alternative of the core chase in **Horn- \mathcal{ALCH}**
 - define the merging operation;
 - prove the correctness and completeness of the merge chase;
- Furtherwork before publication
 - Extend our work to **Horn- \mathcal{ALCHI}** : $R(x, y) \wedge S(x, y) \rightarrow T(\textcolor{red}{y}, \textcolor{red}{x})$;
 - Experimentation on the Graal platform using standard benchmark.

