

# REWRITING THE DESCRIPTION LOGIC *ALCHIQ* TO DISJUNCTIVE EXISTENTIAL RULES

DAVID CARRAL AND MARKUS KRÖTZSCH

KNOWLEDGE-BASED SYSTEMS GROUP



TECHNISCHE  
UNIVERSITÄT  
DRESDEN

FEBRUARY 10, 2021

LINK TO THE PAPER:

[iccl.inf.tu-dresden.de/web/  
Inproceedings3244/en](http://iccl.inf.tu-dresden.de/web/Inproceedings3244/en)

# REWRITINGS

## Definition

Consider fragments  $\mathcal{L}$  and  $\mathcal{L}'$  of FOL. An  $\mathcal{L}'$ -theory  $\mathcal{T}'$  is a *rewriting* of an  $\mathcal{L}$ -theory  $\mathcal{T}$  if, for all fact sets  $\mathcal{F}$  over the signature of  $\mathcal{T}$ , we have that  $\mathcal{T} \cup \mathcal{F}$  and  $\mathcal{T}' \cup \mathcal{F}$  are equisatisfiable. If we can always compute such a rewriting,  $\mathcal{L}$  is *rewritable* to  $\mathcal{L}'$ .

# REWRITINGS

## Definition

Consider fragments  $\mathcal{L}$  and  $\mathcal{L}'$  of FOL. An  $\mathcal{L}'$ -theory  $\mathcal{T}'$  is a *rewriting* of an  $\mathcal{L}$ -theory  $\mathcal{T}$  if, for all fact sets  $\mathcal{F}$  over the signature of  $\mathcal{T}$ , we have that  $\mathcal{T} \cup \mathcal{F}$  and  $\mathcal{T}' \cup \mathcal{F}$  are equisatisfiable. If we can always compute such a rewriting,  $\mathcal{L}$  is *rewritable* to  $\mathcal{L}'$ .

## Motivation

# REWRITINGS

## Definition

Consider fragments  $\mathcal{L}$  and  $\mathcal{L}'$  of FOL. An  $\mathcal{L}'$ -theory  $\mathcal{T}'$  is a *rewriting* of an  $\mathcal{L}$ -theory  $\mathcal{T}$  if, for all fact sets  $\mathcal{F}$  over the signature of  $\mathcal{T}$ , we have that  $\mathcal{T} \cup \mathcal{F}$  and  $\mathcal{T}' \cup \mathcal{F}$  are equisatisfiable. If we can always compute such a rewriting,  $\mathcal{L}$  is *rewritable* to  $\mathcal{L}'$ .

## Motivation

- Theoretical: understand the expressivity of FOL fragments.

# REWRITINGS

## Definition

Consider fragments  $\mathcal{L}$  and  $\mathcal{L}'$  of FOL. An  $\mathcal{L}'$ -theory  $\mathcal{T}'$  is a *rewriting* of an  $\mathcal{L}$ -theory  $\mathcal{T}$  if, for all fact sets  $\mathcal{F}$  over the signature of  $\mathcal{T}$ , we have that  $\mathcal{T} \cup \mathcal{F}$  and  $\mathcal{T}' \cup \mathcal{F}$  are equisatisfiable. If we can always compute such a rewriting,  $\mathcal{L}$  is *rewritable* to  $\mathcal{L}'$ .

## Motivation

- Theoretical: understand the expressivity of FOL fragments.
- Practical: reuse existing reasoners across FOL fragments.

# REWRITINGS

## Definition

Consider fragments  $\mathcal{L}$  and  $\mathcal{L}'$  of FOL. An  $\mathcal{L}'$ -theory  $\mathcal{T}'$  is a *rewriting* of an  $\mathcal{L}$ -theory  $\mathcal{T}$  if, for all fact sets  $\mathcal{F}$  over the signature of  $\mathcal{T}$ , we have that  $\mathcal{T} \cup \mathcal{F}$  and  $\mathcal{T}' \cup \mathcal{F}$  are equisatisfiable. If we can always compute such a rewriting,  $\mathcal{L}$  is *rewritable* to  $\mathcal{L}'$ .

## Motivation

- Theoretical: understand the expressivity of FOL fragments.
- Practical: reuse existing reasoners across FOL fragments.
  - ▶ Assume that  $\mathcal{L}$  is rewritable to  $\mathcal{L}'$ .

# REWRITINGS

## Definition

Consider fragments  $\mathcal{L}$  and  $\mathcal{L}'$  of FOL. An  $\mathcal{L}'$ -theory  $\mathcal{T}'$  is a *rewriting* of an  $\mathcal{L}$ -theory  $\mathcal{T}$  if, for all fact sets  $\mathcal{F}$  over the signature of  $\mathcal{T}$ , we have that  $\mathcal{T} \cup \mathcal{F}$  and  $\mathcal{T}' \cup \mathcal{F}$  are equisatisfiable. If we can always compute such a rewriting,  $\mathcal{L}$  is *rewritable* to  $\mathcal{L}'$ .

## Motivation

- Theoretical: understand the expressivity of FOL fragments.
- Practical: reuse existing reasoners across FOL fragments.
  - ▶ Assume that  $\mathcal{L}$  is rewritable to  $\mathcal{L}'$ .
  - ▶ Consider  $\mathcal{T} \cup \mathcal{F}$  with  $\mathcal{T}$  an  $\mathcal{L}$ -theory and  $\mathcal{F}$  a fact set.

# REWRITINGS

## Definition

Consider fragments  $\mathcal{L}$  and  $\mathcal{L}'$  of FOL. An  $\mathcal{L}'$ -theory  $\mathcal{T}'$  is a *rewriting* of an  $\mathcal{L}$ -theory  $\mathcal{T}$  if, for all fact sets  $\mathcal{F}$  over the signature of  $\mathcal{T}$ , we have that  $\mathcal{T} \cup \mathcal{F}$  and  $\mathcal{T}' \cup \mathcal{F}$  are equisatisfiable. If we can always compute such a rewriting,  $\mathcal{L}$  is *rewritable* to  $\mathcal{L}'$ .

## Motivation

- Theoretical: understand the expressivity of FOL fragments.
- Practical: reuse existing reasoners across FOL fragments.
  - ▶ Assume that  $\mathcal{L}$  is rewritable to  $\mathcal{L}'$ .
  - ▶ Consider  $\mathcal{T} \cup \mathcal{F}$  with  $\mathcal{T}$  an  $\mathcal{L}$ -theory and  $\mathcal{F}$  a fact set.
  - ▶ Compute an equisatisfiable theory  $\mathcal{T}' \cup \mathcal{F}$  with  $\mathcal{T}' \in \mathcal{L}'$ .



# REWRITINGS

## Definition

Consider fragments  $\mathcal{L}$  and  $\mathcal{L}'$  of FOL. An  $\mathcal{L}'$ -theory  $\mathcal{T}'$  is a *rewriting* of an  $\mathcal{L}$ -theory  $\mathcal{T}$  if, for all fact sets  $\mathcal{F}$  over the signature of  $\mathcal{T}$ , we have that  $\mathcal{T} \cup \mathcal{F}$  and  $\mathcal{T}' \cup \mathcal{F}$  are equisatisfiable. If we can always compute such a rewriting,  $\mathcal{L}$  is *rewritable* to  $\mathcal{L}'$ .

## Motivation

- Theoretical: understand the expressivity of FOL fragments.
- Practical: reuse existing reasoners across FOL fragments.
  - ▶ Assume that  $\mathcal{L}$  is rewritable to  $\mathcal{L}'$ .
  - ▶ Consider  $\mathcal{T} \cup \mathcal{F}$  with  $\mathcal{T}$  an  $\mathcal{L}$ -theory and  $\mathcal{F}$  a fact set.
  - ▶ Compute an equisatisfiable theory  $\mathcal{T}' \cup \mathcal{F}$  with  $\mathcal{T}' \in \mathcal{L}'$ .
  - ▶ Use an  $\mathcal{L}'$ -reasoner to decide if  $\mathcal{T}' \cup \mathcal{F}$  is satisfiable.

# REWRITINGS

## Definition

Consider fragments  $\mathcal{L}$  and  $\mathcal{L}'$  of FOL. An  $\mathcal{L}'$ -theory  $\mathcal{T}'$  is a *rewriting* of an  $\mathcal{L}$ -theory  $\mathcal{T}$  if, for all fact sets  $\mathcal{F}$  over the signature of  $\mathcal{T}$ , we have that  $\mathcal{T} \cup \mathcal{F}$  and  $\mathcal{T}' \cup \mathcal{F}$  are equisatisfiable. If we can always compute such a rewriting,  $\mathcal{L}$  is *rewritable* to  $\mathcal{L}'$ .

## Motivation

- Theoretical: understand the expressivity of FOL fragments.
- Practical: reuse existing reasoners across FOL fragments.
  - ▶ Assume that  $\mathcal{L}$  is rewritable to  $\mathcal{L}'$ .
  - ▶ Consider  $\mathcal{T} \cup \mathcal{F}$  with  $\mathcal{T}$  an  $\mathcal{L}$ -theory and  $\mathcal{F}$  a fact set.
  - ▶ Compute an equisatisfiable theory  $\mathcal{T}' \cup \mathcal{F}$  with  $\mathcal{T}' \in \mathcal{L}'$ .
  - ▶ Use an  $\mathcal{L}'$ -reasoner to decide if  $\mathcal{T}' \cup \mathcal{F}$  is satisfiable.
  - ▶ The result determines whether  $\mathcal{T} \cup \mathcal{F}$  is satisfiable.

# REWRITINGS

## Definition

Consider fragments  $\mathcal{L}$  and  $\mathcal{L}'$  of FOL. An  $\mathcal{L}'$ -theory  $\mathcal{T}'$  is a *rewriting* of an  $\mathcal{L}$ -theory  $\mathcal{T}$  if, for all fact sets  $\mathcal{F}$  over the signature of  $\mathcal{T}$ , we have that  $\mathcal{T} \cup \mathcal{F}$  and  $\mathcal{T}' \cup \mathcal{F}$  are equisatisfiable. If we can always compute such a rewriting,  $\mathcal{L}$  is *rewritable* to  $\mathcal{L}'$ .

## Motivation

- Theoretical: understand the expressivity of FOL fragments.
- Practical: reuse existing reasoners across FOL fragments.

## Contribution

# REWRITINGS

## Definition

Consider fragments  $\mathcal{L}$  and  $\mathcal{L}'$  of FOL. An  $\mathcal{L}'$ -theory  $\mathcal{T}'$  is a *rewriting* of an  $\mathcal{L}$ -theory  $\mathcal{T}$  if, for all fact sets  $\mathcal{F}$  over the signature of  $\mathcal{T}$ , we have that  $\mathcal{T} \cup \mathcal{F}$  and  $\mathcal{T}' \cup \mathcal{F}$  are equisatisfiable. If we can always compute such a rewriting,  $\mathcal{L}$  is *rewritable* to  $\mathcal{L}'$ .

## Motivation

- Theoretical: understand the expressivity of FOL fragments.
- Practical: reuse existing reasoners across FOL fragments.

## Contribution

Establish that *ALCHIQ* is rewritable into rule-based languages.

# THE DL *ALCHIQ*: SYNTAX AND SEMANTICS

## Definition: *ALCHIQ*

$$A \sqcap B \sqsubseteq C$$

$$A \sqsubseteq B \sqcup C$$

$$A \sqsubseteq \forall R.B$$

$$A \sqsubseteq \exists R.B$$

$$A \sqsubseteq \leq 1 R.B$$

$$R \sqcap S \sqsubseteq V$$

$$R \sqsubseteq S \sqcup V$$

$$R^- \sqsubseteq S$$

$$A(x) \wedge B(x) \rightarrow C(x)$$

$$A(x) \rightarrow B(x) \vee C(x)$$

$$A(x) \wedge R(x, y) \rightarrow B(y)$$

$$A(x) \rightarrow \exists y. R(x, y) \wedge B(y)$$

$$A(x) \wedge R(x, y) \wedge B(y) \wedge R(x, z) \wedge B(z) \rightarrow y \approx z$$

$$R(x, y) \wedge S(x, y) \rightarrow V(x, y)$$

$$R(x, y) \rightarrow S(x, y) \vee V(x, y)$$

$$R(y, x) \rightarrow S(x, y)$$

In the above,  $A$ ,  $B$ , and  $C$  are unary predicates (i.e., concept names) and  $R$ ,  $S$ , and  $V$  are binary predicates (i.e., role names)

## Definition

A *disjunctive existential rule* is a FOL formula of the form

$$\forall \vec{x}. \left( \beta[\vec{x}] \rightarrow \bigvee_{i=1}^n \exists \vec{y}_i. \eta_i[\vec{x}_i, \vec{y}_i] \right).$$

where  $\beta[\vec{x}]$  and  $\eta_i[\vec{x}_i, \vec{y}_i]$  are atom conjunctions using variables in the lists  $\vec{x}_{(i)}$  and  $\vec{y}_i$ , such that  $\vec{x}_i \subseteq \vec{x}$  and  $\vec{x} \cap \vec{y}_i = \emptyset$  for all  $1 \leq i \leq n$ .

# DATALOG<sup>∃</sup>: SYNTAX AND SEMANTICS

## Definition

A *disjunctive existential rule* is a FOL formula of the form

$$\forall \vec{x}. \left( \beta[\vec{x}] \rightarrow \bigvee_{i=1}^n \exists \vec{y}_i. \eta_i[\vec{x}_i, \vec{y}_i] \right).$$

where  $\beta[\vec{x}]$  and  $\eta_i[\vec{x}_i, \vec{y}_i]$  are atom conjunctions using variables in the lists  $\vec{x}_{(i)}$  and  $\vec{y}_i$ , such that  $\vec{x}_i \subseteq \vec{x}$  and  $\vec{x} \cap \vec{y}_i = \emptyset$  for all  $1 \leq i \leq n$ .

## Definition

- Datalog<sup>∃</sup>: all sets of disjunctive existential rules.
- Datalog<sup>∃</sup>: Datalog<sup>∃</sup> without disjunction.
- Datalog<sup>∃</sup>: Datalog<sup>∃</sup> without existential quantifiers.
- Datalog: Datalog<sup>∃</sup> without disjunctions.

# REWRITINGS OF DL-TYPE LOGICS TO RULE LANGUAGES

[Hustadt et al., 2007]	$ALCHIQ$	Datalog <sup>∨</sup>	exp. †
[Eiter et al., 2012]	Horn- $SHIQ$	Datalog	exp. †
[Rudolph et al., 2012]	$SHIQb_s$	Datalog <sup>∨</sup>	exp. †
[Bienvenu et al., 2014]	$SHI$	Datalog <sup>∨</sup>	exp. †
[Carral et al., 2018]	Horn- $ALCHOIQ$	Datalog	exp. †
[Carral et al., 2019b]	Horn- $SHIQ$	Datalog	exp. †
<hr/>			
[Ortiz et al., 2010]	Horn- $ALCHOIQ$	Datalog	poly.
[Ahmetaj et al., 2016]	$ALCHIO$	Datalog <sup>∨</sup>	poly.
[Krötzsch, 2011]	$\mathcal{EL}^{++}$	Datalog	poly. †
[Carral et al., 2019a]	Horn- $ALC$	Datalog <sup>∃</sup>	poly. †
†: rules of bounded size that does not depend on input			



# REWRITINGS OF DL-TYPE LOGICS TO RULE LANGUAGES

[Hustadt et al., 2007]	$\mathcal{ALCHIQ}$	Datalog <sup>∨</sup>	exp. †
[Eiter et al., 2012]	Horn- $\mathcal{SHIQ}$	Datalog	exp. †
[Rudolph et al., 2012]	$\mathcal{SHIQb}_s$	Datalog <sup>∨</sup>	exp. †
[Bienvenu et al., 2014]	$\mathcal{SHI}$	Datalog <sup>∨</sup>	exp. †
[Carral et al., 2018]	Horn- $\mathcal{ALCHOIQ}$	Datalog	exp. †
[Carral et al., 2019b]	Horn- $\mathcal{SHIQ}$	Datalog	exp. †
<hr/>			
[Ortiz et al., 2010]	Horn- $\mathcal{ALCHOIQ}$	Datalog	poly.
[Ahmetaj et al., 2016]	$\mathcal{ALCHIO}$	Datalog <sup>∨</sup>	poly.
[Krötzsch, 2011]	$\mathcal{EL}^{++}$	Datalog	poly. †
[Carral et al., 2019a]	Horn- $\mathcal{ALC}$	Datalog <sup>∃</sup>	poly. †
†: rules of bounded size that does not depend on input			

## Remark

All rewriting techniques from expressive DLs to  $\text{Datalog}^{(\vee)}$  produce rule sets of exponential size or unbounded arity.

## Theorem 1

*ALCHIQ* is poly-time rewritable into terminating Datalog <sup>$\forall\exists$</sup>  rules **of bounded size**.

## Theorem 1

*ALCHIQ* is poly-time rewritable into terminating Datalog <sup>$\forall\exists$</sup>  rules **of bounded size**.

## Definition: Terminating Datalog <sup>$\forall\exists$</sup>

Language of all sets  $\mathcal{R}$  of disjunctive existential rules that terminate with respect to the Datalog-first restricted chase.

# RESULTS

## Theorem 1

*ALCHIQ* is poly-time rewritable into terminating Datalog <sup>$\forall\exists$</sup>  rules **of bounded size**.

## Definition: Terminating Datalog <sup>$\forall\exists$</sup>

Language of all sets  $\mathcal{R}$  of disjunctive existential rules that terminate with respect to the Datalog-first restricted chase.

## Theorem 2

*ALCHIQ* is poly-time rewritable to Datalog <sup>$\forall$</sup>  rules (of unbounded size).

## Simplified Theorem

$\mathcal{ALC}$  is poly-time rewritable into terminating Datalog <sup>$\forall\exists$</sup>  rules of bounded size.

# RESULTS

## Simplified Theorem

$\mathcal{ALC}$  is poly-time rewritable into terminating Datalog <sup>$\forall\exists$</sup>  rules of bounded size.

## Definition: $\mathcal{ALC}$

$$A \sqcap B \sqsubseteq C$$

$$A \sqsubseteq B \sqcup C$$

$$A \sqsubseteq \forall R.B$$

$$A \sqsubseteq \exists R.B$$

$$A(x) \wedge B(x) \rightarrow C(x)$$

$$A(x) \rightarrow B(x) \vee C(x)$$

$$A(x) \wedge R(x, y) \rightarrow B(y)$$

$$A(x) \rightarrow \exists y. R(x, y) \wedge B(y)$$

In the above,  $A$ ,  $B$ , and  $C$  are unary predicates (i.e., concept names) and  $R$  is a binary predicate (i.e., role name)

## Definition: $\mathcal{ALC}$ Rewritings

Consider a theory  $\mathcal{T}$  of  $\mathcal{ALC}$  axioms and a sequence  $A_1, \dots, A_n$  containing all of the classes in  $\mathcal{T}$ . Then, the following set of Datalog <sup>$\forall\exists$</sup>  rules is a terminating rewriting for  $\mathcal{T}$ :

$$\begin{aligned}
 & \{A(x) \wedge B(x) \rightarrow C(x) \mid A \sqcap B \sqsubseteq C \in \mathcal{T}\} \cup \{A(x) \rightarrow B(x) \vee C(x) \mid A \sqsubseteq B \sqcup C \in \mathcal{T}\} \cup \\
 & \{A(x) \wedge R(x, y) \rightarrow B(y) \mid A \sqsubseteq \forall R.B \in \mathcal{T}\} \cup \\
 & \{A(x) \rightarrow \exists y.R(x, y) \wedge B(y) \wedge Succ(x, y) \mid A \sqsubseteq \exists R.B \in \mathcal{T}\} \cup \\
 & \{\rightarrow A(x) \vee A^-(x), A(x) \wedge A^-(x) \rightarrow \perp \mid A \in \mathbf{Classes}(\mathcal{T})\} \cup \\
 & \{A_1(x) \wedge A_1(z) \rightarrow SameClasses_1(x, z), A_1^-(x) \wedge A_1^-(z) \rightarrow SameClasses_1(x, z)\} \cup \\
 & \{SameClasses_{i-1}(x, z) \wedge A_i(x) \wedge A_i(z) \rightarrow SameClasses_i(x, z), \\
 & \quad SameClasses_{i-1}(x, z) \wedge A_i^-(x) \wedge A_i^-(z) \rightarrow SameClasses_i(x, z) \mid 2 \leq i \leq n\} \cup \\
 & \{SameClasses_n(x, y) \rightarrow SameType(x, y)\} \cup \\
 & \{SameType(x, z) \wedge Succ(x, y) \wedge R(x, y) \rightarrow Succ(z, y) \wedge R(z, y) \mid R \in \mathbf{Roles}(\mathcal{T})\}
 \end{aligned}$$




# THANK YOU FOR YOUR ATTENTION!

LINK TO THE PAPER:




[iccl.inf.tu-dresden.de/web/Inproceedings3244/en](http://iccl.inf.tu-dresden.de/web/Inproceedings3244/en)






# REFERENCES I

-  AHMETAJ, S., ORTIZ, M., AND SIMKUS, M. (2016).  
**POLYNOMIAL DATALOG REWRITINGS FOR EXPRESSIVE DESCRIPTION LOGICS WITH CLOSED PREDICATES.**  
In Kambhampati, S., editor, *Proc. 25th Int. Joint Conf. on Artif. Intell. (IJCAI 2016)*, pages 878–885. IJCAI/AAAI Press.
-  BIENVENU, M., TEN CATE, B., LUTZ, C., AND WOLTER, F. (2014).  
**ONTOLOGY-BASED DATA ACCESS: A STUDY THROUGH DISJUNCTIVE DATALOG, CSP, AND MMSNP.**  
*ACM Transactions of Database Systems*, 39(4):33:1–33:44.
-  CARRAL, D., DRAGOSTE, I., AND KRÖTZSCH, M. (2018).  
**THE COMBINED APPROACH TO QUERY ANSWERING IN HORN-*ALCHOIQ*.**  
In Thielscher, M., Toni, F., and Wolter, F., editors, *Proc. 16th Int. Conf. on Principles of Knowledge Representation and Reasoning (KR 2018)*, pages 339–348. AAAI Press.

## REFERENCES II

-  CARRAL, D., DRAGOSTE, I., KRÖTZSCH, M., AND LEWE, C. (2019A).  
**CHASING SETS: HOW TO USE EXISTENTIAL RULES FOR EXPRESSIVE REASONING.**  
In Kraus, S., editor, *Proc. 28th Int. Joint Conf. on Artif. Intell. (IJCAI 2019)*, pages 1624–1631. [ijcai.org](http://ijcai.org).
-  CARRAL, D., GONZÁLEZ, L., AND KOOPMANN, P. (2019B).  
**FROM HORN-*SRIQ* TO DATALOG: A DATA-INDEPENDENT TRANSFORMATION THAT PRESERVES ASSERTION ENTAILMENT.**  
In *Proc. 33rd AAAI Conf. on Artificial Intelligence (AAAI 2019)*, pages 2736–2743. AAAI Press.
-  EITER, T., ORTIZ, M., SIMKUS, M., TRAN, T.-K., AND XIAO, G. (2012).  
**QUERY REWRITING FOR HORN-*SHIQ* PLUS RULES.**  
In Hoffmann, J. and Selman, B., editors, *Proc. 26th AAAI Conf. on Artificial Intelligence (AAAI 2012)*. AAAI Press.

## REFERENCES III

-  HUSTADT, U., MOTIK, B., AND SATTLER, U. (2007).  
**REASONING IN DESCRIPTION LOGICS BY A REDUCTION TO DISJUNCTIVE DATALOG.**  
*J. Automated Reasoning*, 39(3):351–384.
-  KRÖTZSCH, M. (2011).  
**EFFICIENT RULE-BASED INFERENCING FOR OWL EL.**  
In Walsh, T., editor, *Proc. 22nd Int. Joint Conf. on Artif. Intell. (IJCAI 2011)*, pages 2668–2673. IJCAI/AAAI.
-  ORTIZ, M., RUDOLPH, S., AND SIMKUS, M. (2010).  
**WORST-CASE OPTIMAL REASONING FOR THE HORN-DL FRAGMENTS OF OWL 1 AND 2.**  
In Lin, F., Sattler, U., and Truszczynski, M., editors, *Proc. 12th Int. Conf. on Principles of Knowledge Representation and Reasoning (KR 2010)*. AAAI Press.

## REFERENCES IV



RUDOLPH, S., KRÖTZSCH, M., AND HITZLER, P. (2012).

**TYPE-ELIMINATION-BASED REASONING FOR THE DESCRIPTION LOGIC**  
***SHIQ<sub>B</sub>* USING DECISION DIAGRAMS AND DISJUNCTIVE DATALOG.**  
*Logical Methods in Computer Science*, 8(1).