Reasoning methods in Automated Thoerem Proving

Presentation at BOREAL team's seminar

Julie Cailler

7 février 2023

PhD student in the MaREL team
LIRMM, Université de Montpellier, CNRS

Formal methods and proofs

Formal methods

« Formal method are mathematically rigorous techniques for the specification, development, and verification of software and hardware systems. »

More precisely

- Critical system (life, money)
- Safety by proving ($\neq$ tests)
- But expensive and hard to understand

How to make a proof?

Data

- A language
- Some hypothesis (or not)
- A goal

Inference rules

$$\frac{H1 \qquad H2}{C}$$

How to make a proof?

Data

- A language
- Some hypothesis (or not)
- A goal

Inference rules

$$\frac{A \qquad A \Rightarrow B}{B}$$

Valid and satisifable

Validity

- Always true
- Proof by refutation ($\neg F$ is unsatisfiable)
- Theorem proving

Satisfiability

- True in at least one interpretation
- Building an interpretation
- Constraints solving, find bugs or counter-example

Many possibilites!

Different ways to make a proof

- Hand
- Proof assistant
- Automated theorem prover

Depending of the context

- Valid or satisfiable
- Logic (classical, modal, ...)
- Reasoning inside theories

Logic, expressivity and automation



Logic, expressivity and automation

Propositional logic	Fragments of Theories	First-order logic	Higher-order logic	Intuitionist type theory
SAT provers	Decision procedure	SMT provers	First-order provers	Higher-order provers	Interactive proof assistants

Many ways to prove, depending of what you get and what you want!

Automated reasoning

Automated reasoning

Automated theorem proving

Given a set of hypothesis and a goal, automatically find a proof!

Reasoning methods in first-order logic

- Saturation based methods
- Tableaux based methods
- Inverse method

Resolution

Context and use

- 1960 by Davis and Putnam
- Saturation based
- Split the original formula into clauses
- Resolve clauses and try to find the empty one

Pros

- Gives the best practical results
- Easy to implement

Cons

- Breaks the initial formula into clauses
- No proof

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

CNF :

$$\{\neg A\}, \{A \vee A\}, \{\neg B \vee A\}$$

$$\{\neg A\}$$

$$\{A \vee A\}$$

$$\{\neg B \vee A\}$$

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

CNF :

$$\{\neg A\}, \{A \vee A\}, \{\neg B \vee A\}$$

$\{\neg A\}$

$\{A \vee A\}$ —— $\{A\}$

$\{\neg B \vee A\}$

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

CNF : $\{\neg A\}, \{A \vee A\}, \{\neg B \vee A\}$



$\{\neg B \vee A\}$

Method of analytics tableaux

Context and use

- 1955 by Beth and Hintikka
- Sequent based
- Tree structure
- Reduce goal to subgoals and try to solve them

Pros

- Gives a proof of the initial formula
- Useful in non-classical logic
- Good match with interactive theorem provers

Cons

- Slower than resolution
- Harder to implement

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

$$\frac{\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)}{(A \Rightarrow B) \Rightarrow A, \neg A}\ \alpha_{\neg\Rightarrow}$$

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

$$\dfrac{\dfrac{\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)}{(A \Rightarrow B) \Rightarrow A, \neg A}\,\alpha_{\neg\Rightarrow}}{\neg(A \Rightarrow B) \qquad A}\,\beta_{\Rightarrow}$$

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

$$\dfrac{\dfrac{\dfrac{\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)}{(A \Rightarrow B) \Rightarrow A, \neg A}\,\alpha_{\neg\Rightarrow}}{\dfrac{\neg(A \Rightarrow B)}{A, \neg B}\,\alpha_{\neg\Rightarrow} \qquad \dfrac{A}{\odot}\,\odot}\,\beta_{\Rightarrow}}{}$$

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

$$\dfrac{\dfrac{\dfrac{\dfrac{\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)}{(A \Rightarrow B) \Rightarrow A, \neg A}\,\alpha_{\neg\Rightarrow}}{\dfrac{\neg(A \Rightarrow B)}{A, \neg B}\,\alpha_{\neg\Rightarrow}}\,\beta_{\Rightarrow} \qquad \dfrac{A}{\odot}\,\odot}{\odot}\,\odot$$

Inverse method

Context and use

- 1964 by S.Ju. Maslov
- Construct goals from previously proved subgoals
- Use a saturation algorithm
- Forward-chaining proof-search
- Subformula property

Pros

- Gives a proof of the initial formula
- Isomorphic to skolem chase

Cons

- Few implementations
- Slower than resolution and tableaux
- Harder to implement

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

Rules needed : $\dfrac{\neg P \qquad Q}{P \Rightarrow Q} \Rightarrow$ $\qquad$ $\dfrac{P, \neg Q}{\neg(P \Rightarrow Q)} \neg \Rightarrow$

Available axioms : $\dfrac{}{\Gamma, A, \neg A}\, ax$ $\qquad$ $\dfrac{}{\Gamma, B, \neg B}\, ax$

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

Rules needed : $\dfrac{\neg P \qquad Q}{P \Rightarrow Q} \Rightarrow$ $\qquad$ $\dfrac{P, \neg Q}{\neg(P \Rightarrow Q)} \neg \Rightarrow$

Available axioms : $\dfrac{}{\Gamma, A, \neg A}\, ax$ $\qquad$ $\dfrac{}{\Gamma, B, \neg B}\, ax$

$$\frac{}{A, \neg A}\, ax$$

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

Rules needed : $\dfrac{\neg P \qquad Q}{P \Rightarrow Q} \Rightarrow$ $\qquad$ $\dfrac{P, \neg Q}{\neg(P \Rightarrow Q)} \neg \Rightarrow$

Available axioms : $\dfrac{}{\Gamma, A, \neg A}\, ax$ $\qquad$ $\dfrac{}{\Gamma, B, \neg B}\, ax$

$$\frac{}{A, \neg A, \neg B}\, ax$$

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

Rules needed : $\dfrac{\neg P \qquad Q}{P \Rightarrow Q} \Rightarrow$ $\qquad$ $\dfrac{P, \neg Q}{\neg(P \Rightarrow Q)} \neg \Rightarrow$

Available axioms : $\dfrac{}{\Gamma, A, \neg A}\, ax$ $\qquad$ $\dfrac{}{\Gamma, B, \neg B}\, ax$

$$\dfrac{\dfrac{}{A, \neg A, \neg B}\, ax}{\neg(A \Rightarrow B)} \neg \Rightarrow$$

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

Rules needed : $\dfrac{\neg P \qquad Q}{P \Rightarrow Q} \Rightarrow$ $\qquad$ $\dfrac{P, \neg Q}{\neg(P \Rightarrow Q)} \neg \Rightarrow$

Available axioms : $\dfrac{}{\Gamma, A, \neg A}\, ax$ $\qquad$ $\dfrac{}{\Gamma, B, \neg B}\, ax$

$$\dfrac{\dfrac{}{A, \neg A, \neg B}\, ax}{\neg(A \Rightarrow B)} \neg \Rightarrow \qquad \dfrac{}{A, \neg A}\, ax$$

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

Rules needed : $\dfrac{\neg P \qquad Q}{P \Rightarrow Q} \Rightarrow$ $\qquad$ $\dfrac{P, \neg Q}{\neg(P \Rightarrow Q)} \neg \Rightarrow$

Available axioms : $\dfrac{}{\Gamma, A, \neg A}\, ax$ $\qquad$ $\dfrac{}{\Gamma, B, \neg B}\, ax$

$$\dfrac{\dfrac{\dfrac{}{A, \neg A, \neg B}\, ax}{\neg(A \Rightarrow B)} \neg \Rightarrow \qquad \dfrac{}{A, \neg A}\, ax}{(A \Rightarrow B) \Rightarrow A} \Rightarrow$$

Example

Formula to prove

$$\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)$$

Rules needed : $\dfrac{\neg P \qquad Q}{P \Rightarrow Q} \Rightarrow$ $\qquad$ $\dfrac{P, \neg Q}{\neg(P \Rightarrow Q)} \neg \Rightarrow$

Available axioms : $\dfrac{}{\Gamma, A, \neg A}\, ax$ $\qquad$ $\dfrac{}{\Gamma, B, \neg B}\, ax$

$$\dfrac{\dfrac{\dfrac{}{A, \neg A, \neg B}\, ax}{\neg(A \Rightarrow B)} \neg \Rightarrow \qquad \dfrac{}{A, \neg A}\, ax}{(A \Rightarrow B) \Rightarrow A} \Rightarrow$$
$$\dfrac{}{\neg(((A \Rightarrow B) \Rightarrow A) \Rightarrow A)} \neg \Rightarrow$$

To go further

Reasoning with theory

Core provers

- SAT solver
- First-order theorem prover
- ...

Specific provers

- Decision procedure
- Background reasoner
- Equality reasoning

Nesting dolls principle

Expressive logic,
semi-automated tools
(ex : Proof assistants)

Limited logic,
efficient provers
(ex : SAT)

Intermediate tools
(ex : first-order prover,
background reasoners)

SMT = SAT + Theory solver



Isabelle


Isabelle
Isabelle
sledgehammer
nitpick
SMT solver
FOL prover
Model finder
Decision procedure
(ex : simplex)
SAT solver

Conclusion

Combinations of techniques

- Automated reasoning makes formal method more accessible
- Various methods for various situations
- Cooperation is the key

To go further

- Portfolio approach
- Unification
- Graph algorithms

Thank you for you attention!